

OVERVIEW OF THE TEST AND MEASUREMENT FUNCTIONS

The voltage testers by Testboy impress with their user-friendly handling as well as their durable and safe design. They also meet all professional requirements of modern voltage testers.

     		
	4000 828 945	
		ST 105 PROMAT
	Display	optical, acoustic, vibrating
	Measuring range	12-1000 V AC
	Surge protection category	CAT IV 1000 V
	Integr. LED torch	Yes
	Other	-
		No continuity testing
	4000 828 945	TB113
		optical + acoustic
		12-1000 V AC
		CAT IV 600 V / CAT III 1000 V
		Yes
		-
		No continuity testing
		4000 828 925
		TB 114
		optical + vibrating
		12-1000 V AC
		CAT IV 600 V / CAT III 1000 V
		Yes
		-
		No continuity testing
		4000 828 926
		TB 115 bit
		optical
		12-1000 V AC
		CAT IV 600 V / CAT III 1000 V
		No
		BIT mount incl. 2 bits and bag
		No continuity testing
		4000 828 944
		DMM 10 (Promat)
		LCD, illuminated
		0 - 600 V
		0 - 600 V
		0 - 10 A
		0 - 10 A
		-20 °C - 200 °C with temperature sensor
		600 Ohm - 60 MOhm
		Yes (continuity per acoustic signal below 50 Ω)
		Yes
		up to 60mF
		No
		CAT III 600 V
		380g
		2x type AA
		Yes
		4000 828 844
		Testboy 20 Plus
		optical 0-20 Ω/acoustic 0-250 Ω
		4.5 V
		optical ~10 mA/acoustic ~2 mA
		Yes
		up to 300 V
		CAT II 300 V
		Yes
		4000 828 942
		Testboy 40 Plus
		optical, 8 LEDs
		6-400 V AC/DC
		CAT III 400 V
		Yes (+, - LED)
		IP 65
		via measurement object
		4000 828 927
		Testboy 40 Simple
		10 LEDs for voltage, polarity, continuity and ELV
		12 - 690 V AC/DC
		CAT IV 300 V / CAT III 600V / CAT II 690V
		Yes (+, - LED)
		IP 54
		2x 1.5 V Type AAA micro
		4000 828 074