

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

Version number: GHS 1.0

Date of compilation: 2025-01-21

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name** TECWERK FARBEINDRINGMITTEL ROT - 500 ml  
**Unique formula identifier (UFI)** X740-Y0KG-R00F-7H9P

**Article number** 2000 354 550

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses** General use

### 1.3 Details of the supplier of the safety data sheet

NORDWEST Handel AG  
Robert-Schuman-Str. 17  
44263 Dortmund  
Germany

Telephone: +49 231 2222-3001

Telefax: +49 231 2222-3099

Website: www.nordwest.com

**e-mail (competent person)** sdb@nordwest.com

### 1.4 Emergency telephone number

Poison centre			
Country	Name	Postal code/city	Telephone
Austria	Vergiftungsinformationszentrale (VIZ)		<b>+43 (0)1 406 43 43</b>
Germany	Gemeinsamen Giftinformationszentrum (GGIZ) der Laender Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thuringen c/o HELIOS Klinikum Erfurt	99089 Erfurt	<b>+49-361-730730</b>
Luxembourg	Poison Centre Luxemburg		<b>(+352) 8002 5500</b>
Switzerland	Tox Info Suisse		<b>+145, 24h oder +41 44 251 51 51</b>

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 (CLP)**

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.10	aspiration hazard	1	Asp. Tox. 1	H304
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

**The most important adverse physicochemical, human health and environmental effects**

Spillage and fire water can cause pollution of watercourses.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP)**

**Signal word** danger

**Pictograms**

GHS02, GHS07



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

## Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

## Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/eye protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Supplemental hazard information

EUH208 Contains N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine. May produce an allergic reaction.

**Child-resistant fastening** yes

**Tactile warning of danger** yes

**Hazardous ingredients for labelling** Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), heavy arom.

## 2.3 Other hazards

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .






## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
CAS No 106-97-8  EC No 203-448-7  Index No 601-004-00-0  REACH Reg. No 01- 2119474691- 32-xxxx	butane	25 – < 50	Flam. Gas 1B / H221 Press. Gas C / H280	 	C GHS-HC U(b)	
CAS No 74-98-6  EC No 200-827-9  Index No 601-003-00-5  REACH Reg. No 01- 2119486944- 21	propane	10 – < 25	Flam. Gas 1A / H220 Press. Gas L / H280	 	GHS-HC U(c)	
CAS No 112-34-5  EC No	2-(2-butoxyethoxy)ethanol	10 – < 25	Eye Irrit. 2 / H319		GHS-HC IOELV	

# Safety Data Sheet








according to Regulation (EC) No. 1907/2006 (REACH)

**TECWERK**

**2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml**

Version number: GHS 1.0

Date of compilation: 2025-01-21

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
203-961-6 Index No 603-096-00-8 REACH Reg. No 01- 2119475104- 44-xxxx						
CAS No 64742-47-8 EC No 265-149-8 Index No 649-422-00-2 REACH Reg. No 01- 2119456620- 43	Distillates (petroleum), hydro-treated light	5 – < 10	Flam. Liq. 3 / H226 STOT SE 3 / H336 Asp. Tox. 1 / H304	  		
CAS No 64742-94-5 EC No 265-198-5 Index No 649-424-00-3 REACH Reg. No 01- 2119510128- 50-xxxx	Solvent naphtha (petroleum), heavy arom.	1 – < 5	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	  	GHS-HC	
CAS No 56358-10-2 EC No 260-125-3 REACH Reg. No 01- 2120767269- 40-xxxx	N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine	< 1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1B / H317 Aquatic Chronic 4 / H413			

## Notes

- C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)
- IOELV: Substance with a community indicative occupational exposure limit value
- U(b): The allocation to the group 'compressed gas' is based on the physical state in which the gas is packaged
- U(c): The allocation to the group 'liquefied gas' is based on the physical state in which the gas is packaged

Hazardous ingredients, Specific Conc. Limits, M-factors, ATE				
Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
Solvent naphtha (petroleum), heavy arom.	-	-	>5.28 mg/l/4h	inhalation: vapour

## Remarks

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, BC-powder

#### Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

#### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

## 7.2 Conditions for safe storage, including any incompatibilities

### Managing of associated risks

#### Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

#### Packaging compatibilities

Keep only in original container.

#### Storage class (LGK) TRGS 510

LGK 2 B (aerosol dispensers or lighters)

## 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	2-(2-butoxyethoxy)ethanol	112-34-5	AGW	10	67	15	100.5			va, Y	TRGS 900
DE	butyl diglycol	112-34-5	MAK	10	67	15	100.5			va, DE-MAK-2	DFG
DE	polyethylene glycol (PEG 200-600)	25322-68-3	AGW		200		400			i, Y	TRGS 900
DE	Polyethylene glycols (PEG) (average molecular weight 200-600)	25322-68-3	MAK		250		500			i	DFG
DE	Distillates (petroleum), hydro-treated light	64742-47-8	MAK		5		20			r, aerosol	DFG
DE	Distillates (petroleum), hydro-treated light	64742-47-8	MAK	50	350	100	700			vap	DFG
DE	distillates (petroleum), hydro-treated light (C9 - C14 aliphatics)	64742-47-8	AGW		300		600			Y	TRGS 900
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900
EU	2-(2-butoxyethoxy)ethanol	112-34-5	IOEL V	10	67.5	15	101.2				2006/15/EC

#### Notation

aerosol as aerosols

Ceiling-C ceiling value is a limit value above which exposure should not occur

DE-MAK-2 MAK value for the sum of the air concentrations of butyl diglycol and butyl diglycol acetate.

i inhalable fraction

r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

va as vapours and aerosols

vap as vapours

Y a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

**TECWERK**

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	56 mg/kg	aquatic organisms	water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	11 mg/l	aquatic organisms	water	intermittent release

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)



Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

#### Eye/face protection

Use protective eyewear to guard against splash of liquids.

#### Skin protection

##### Hand protection

Wear protective gloves. (Splash protection)

##### Type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

##### Breakthrough times of the glove material

>480 minutes (permeation: level 6)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

## Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

## Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Full face mask/half mask/quarter mask (EN 136/140).

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White).

## Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	aerosol (spray aerosol)
Colour	red
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	5 vol% - 15 vol%
Flash point	-88.6 °C at 1,013 hPa
Auto-ignition temperature	210 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not relevant
Solubility(ies)	not determined

#### Partition coefficient

Partition coefficient n-octanol/water (log value) this information is not available

Vapour pressure 4,200 hPa at 20 °C

#### Density and/or relative density

Density 0.6882 – 0.6936 g/ml (calculated value)

Relative vapour density information on this property is not available

### 9.2 Other information

Information with regard to physical hazard classes there is no additional information

#### Other safety characteristics

Temperature class (EU, acc. to ATEX) T3 (maximum permissible surface temperature on the equipment: 200°C)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

#### Hints to prevent fire or explosion

Protect from sunlight.

### 10.5 Incompatible materials

Oxidisers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

## Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## Classification according to GHS (1272/2008/EC, CLP)

### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed or in contact with skin.

### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Solvent naphtha (petroleum), heavy arom.	64742-94-5	inhalation: vapour	>5.28 mg/l/4h

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

Contains N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine. May produce an allergic reaction.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)

### Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Solvent naphtha (petroleum), heavy arom.	64742-94-5	LL50	17 mg/l	fish	24 h
Solvent naphtha (petroleum), heavy arom.	64742-94-5	EL50	4.6 mg/l	aquatic invertebrates	24 h

### 12.2 Persistence and degradability

### Degradability of components

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
2-(2-butoxyethoxy)ethanol	112-34-5	oxygen depletion	85 %	28 d		ECHA

### 12.3 Bioaccumulative potential

Data are not available.

### Bioaccumulative potential of components

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
2-(2-butoxyethoxy)ethanol	112-34-5		1 (pH value: 7, 20 °C)	



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
N-(2-ethylhexyl)-1-[[3-methyl-4-[[3-methylphenyl]azo]phenyl]azo]naphthalen-2-amine	56358-10-2		11.89	

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .

## 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .

## 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

##### List of wastes, (Recommendations)

##### Product residues

16 05 04\* Gases in pressure containers (including halons) containing hazardous substances

##### Packagings

15 01 04 Metallic packaging

##### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN UN 1950

IMDG-Code UN 1950

ICAO-TI UN 1950

### 14.2 UN proper shipping name

ADR/RID/ADN AEROSOLS

IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

### 14.3 Transport hazard class(es)

ADR/RID/ADN 2 (2.1)

IMDG-Code 2.1

ICAO-TI 2.1

### 14.4 Packing group

not assigned

### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code

5F

Danger label(s)

2.1



Special provisions (SP)

190, 327, 344, 625

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

Excepted quantities (EQ) E0  
Limited quantities (LQ) 1 L  
Transport category (TC) 2  
Tunnel restriction code (TRC) D

## International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant -  
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 1 L  
EmS F-D, S-U  
Stowage category -

## International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167, A802  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

#### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

#### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

#### Water Framework Directive (WFD)

none of the ingredients are listed

#### Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

#### Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

#### National regulations (Germany)

#### Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water hazard class) 1 slightly hazardous to water

#### Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m <sup>3</sup>	3)

#### Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m<sup>3</sup>, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

#### National inventories

Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed

#### Legend

REACH Reg. REACH registered substances

### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

TECWERK

2000 354 550 - TECWERK FARBEINDRINGMITTEL ROT - 500 ml

Version number: GHS 1.0

Date of compilation: 2025-01-21

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations.
2006/15/EC.	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).
ADR/RID/ADN.	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).
AGW.	Workplace exposure limit.
Aquatic Chronic.	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
ATE.	Acute Toxicity Estimate.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
Ceiling-C.	Ceiling value.
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD.	Chemical oxygen demand.
DFG.	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DGR.	Dangerous Goods Regulations (see IATA/DGR).
DNEL.	Derived No-Effect Level.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
ED.	Endocrine disruptor.
EINECS.	European Inventory of Existing Commercial Chemical Substances.
EL50.	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms.
ELINCS.	European List of Notified Chemical Substances.
Ems.	Emergency Schedule.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
ICAO-TI.	Technical instructions for the safe transport of dangerous goods by air.
IMDG.	International Maritime Dangerous Goods Code.
IMDG-Code.	International Maritime Dangerous Goods Code.
Index No.	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008.
IOELV.	Indicative occupational exposure limit value.
Lgk.	Lagerklasse (storage class according to TRGS 510, Germany).
LL50.	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality.
Log KOW.	n-Octanol/water.
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Skin Corr.	Corrosive to skin.
Skin Irrit.	Irritant to skin.
Skin Sens.	Skin sensitisation.
STEL.	Short-term exposure limit.
STOT SE.	Specific target organ toxicity - single exposure.
SVHC.	Substance of Very High Concern.
TRGS.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 900.	Arbeitsplatzgrenzwerte (TRGS 900).
TWA.	Time-weighted average.
VPvB.	Very Persistent and very Bioaccumulative.

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.  
Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.  
Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

H220.	Extremely flammable gas.
H221.	Flammable gas.
H222.	Extremely flammable aerosol.
H226.	Flammable liquid and vapour.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H304.	May be fatal if swallowed and enters airways.
H315.	Causes skin irritation.
H317.	May cause an allergic skin reaction.
H319.	Causes serious eye irritation.
H336.	May cause drowsiness or dizziness.
H411.	Toxic to aquatic life with long lasting effects.
H412.	Harmful to aquatic life with long lasting effects.
H413.	May cause long lasting harmful effects to aquatic life.

### Disclaimer

This SDS has been compiled and is solely intended for this product. This information is based on the present state of our knowledge and does not constitute an assurance of product properties nor establishes contract legal rights. All data about health and safety are only for information. They should therefore not be construed as specifications.