



Version number: GHS 2.0 Revision: 2025-08-07 Replaces version of: 2025-01-20 (GHS 1)

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name TECWERK ROSTUMWANDLER - 400 ml

Unique formula identifier (UFI) AQ30-X0F3-W00G-8FT9

**Article number** 2000 354 676

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses** General use

1 pack performance coating

1.3 Details of the supplier of the safety data sheet

NORDWEST Handel AG Robert-Schuman-Str. 17 44263 Dortmund Germany

Telephone: +49 231 2222-3001 Telefax: +49 231 2222-3099 Website: www.nordwest.com

e-mail (competent person) sdb@nordwest.com

1.4 Emergency telephone number

Poison centre									
Country	Name	Postal code/city	Telephone						
Austria	Vergiftungsinformationszentrale (VIZ)		+43 (0)1 406 43 43						
Germany	Gemeinsamen Giftinformationszentrum (GGIZ) der Laender Mecklenburg-Vor- pommern, Sachsen, Sachsen-Anhalt und Thueringen c/o HELIOS Klinikum Erfurt	99089 Erfurt	+49-361-730730						
Luxembourg	Poison Centre Luxemburg		(+352) 8002 5500						
Switzerland	Tox Info Suisse		+145, 24h oder +41 44 251 51 51						

## **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	1	Aerosol 1	H222,H229
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

<u>Signal word</u> danger

**Pictograms** 

GHS02, GHS07



**Hazard statements** 

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Germany: en Page: 1 / 12



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Replaces version of: 2025-01-20 (GHS 1) Revision: 2025-08-07

<u>Precautionary statements</u> P101 P102

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source. P210

P211 P251

Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area.

P280 P410+P412

Wear protective gloves/eye protection.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental hazard information EUH066 Repeated Repeated exposure may cause skin dryness or cracking.

Hazardous ingredients for labelling N-butyl acetate, acetone, propan-2-ol

Other hazards 2.3

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

**Endocrine disrupting properties** 

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

### SECTION 3: Composition/information on ingredients

#### 3.1 **Substances**

Not relevant (mixture)

#### 3.2 **Mixtures**

#### Description of the mixture

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
CAS No 123-86-4	N-butyl acetate	25 - < 50	Flam. Liq. 3 / H226 STOT SE 3 / H336	<u>(1)</u>	GHS-HC IOELV	
EC No 204-658-1						
Index No 607-025-00-1						
REACH Reg. No 01- 2119485493- 29-xxxx						
CAS No 67-64-1	acetone	10-<25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	<u>(1)</u>	IOELV	
EC No 200-662-2			3101 35 37 11330	•		
Index No 606-001-00-8						
REACH Reg. No 01- 2119471330- 49-xxxx						
CAS No 106-97-8	butane	10-<25	Flam. Gas 1B / H221 Press. Gas C / H280		C GHS-HC	
EC No 203-448-7					U(b)	
Index No 601-004-00-0						
REACH Reg. No 01- 2119474691- 32-xxxx						
CAS No 74-98-6	propane	10-<25	Flam. Gas 1A / H220 Press. Gas L / H280		GHS-HC U(c)	
EC No						

Germany: en Page: 2 / 12



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Revision: 2025-08-07

Replaces version of: 2025-01-20 (GHS 1)

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
200-827-9						
Index No 601-003-00-5						
REACH Reg. No 01- 2119486944- 21						
CAS No 67-63-0	propan-2-ol	1-<5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	<u>(1)</u>	GHS-HC	
EC No 200-661-7			3101 35 37 11330			
Index No 603-117-00-0						
REACH Reg. No 01- 2119457558- 25 01- 2119457558- 25-xxxx						

#### Notes

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

GHS- Harmonised classification (the classification of the substance corresponds to the entry in the list according to

HC: 1272/2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

U(b): The allocation to the group 'compressed gas' is based on the physical state in which the gas is packaged U(c): The allocation to the group 'liquefied gas' is based on the physical state in which the gas is packaged

#### Remarks

For full text of abbreviations: see SECTION 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

#### **General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### **Following inhalation**

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

## 4.3 Indication of any immediate medical attention and special treatment needed

none

#### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, BC-powder

#### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

### **Hazardous combustion products**

Germany: en Page: 3 / 12



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Revision: 2025-08-07

Replaces version of: 2025-01-20 (GHS 1)

Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

#### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

#### **Environmental precautions** 6.2

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### Methods and material for containment and cleaning up 6.3

#### Advice on how to contain a spill

Covering of drains

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

#### SECTION 7: Handling and storage

#### Precautions for safe handling

#### Recommendations

### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

#### Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. <a href="Packaging compatibilities">Packaging compatibilities</a>

Keep only in original container.

## Storage class (LGK) TRGS 510

LGK 2 B (aerosol dispensers or lighters)

#### 7.3 Specific end use(s)

See section 16 for a general overview.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/m³ ]	STEL [ppm]	STEL [mg/m³ ]	Ceiling- C [ppm]	Ceiling- C [mg/m³ ]	Nota- tion	Source
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	1-butyl acetate	123-86-4	MAK	100	480	200	960				DFG
DE	n-butyl acetate	123-86-4	AGW	62	300	124	600			Υ	TRGS 900
DE	propan-2-ol	67-63-0	AGW	200	500	400	1,000			Υ	TRGS 900
DE	acetone	67-64-1	AGW	500	1,200	1,000	2,400			Y	TRGS 900
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900
EU	n-butyl acetate	123-86-4	IOEL	50	241	150	723				2019/

Page: 4 / 12 Germany: en



according to Regulation (EC) No. 1907/2006 (REACH)

## 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Replaces version of: 2025-01-20 (GHS 1) Revision: 2025-08-07

Occupational exposure limit values (Workplace Exposure Limits)											
Coun- try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/m³ ]	STEL [ppm]	STEL [mg/m³ ]	Ceiling- C [ppm]	Ceiling- C [mg/m³ ]	Nota- tion	Source
			٧								1831/ EU
EU	acetone	67-64-1	IOEL V	500	1,210						2000/ 39/EC

#### **Notation**

Ceiling-C ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) STEL

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

Biologica	Biological limit values									
Country	Name of agent	Parameter	Notation	Identifier	Value	Source				
DE	propan-2-ol	acetone		BLV	25 mg/l	TRGS 903				
DE	propan-2-ol	acetone		BLV	25 mg/l	TRGS 903				
DE	acetone	acetone		BAT	50 mg/l	DFG				
DE	acetone	acetone		BAT (BAR)	2.5 mg/l	DFG				
DE	acetone	acetone		BLV	50 mg/l	TRGS 903				

Relevant DNELs of	components					
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
N-butyl acetate	123-86-4	DNEL	300 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	chronic - local ef- fects
N-butyl acetate	123-86-4	DNEL	600 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	acute - local ef- fects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
N-butyl acetate	123-86-4	DNEL	48 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	960 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	acute - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	2,420 mg/m³	human, inhalat- ory	worker (industry)	acute - local ef- fects
acetone	67-64-1	DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
propan-2-ol	67-63-0	DNEL	1,723 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic effects
propan-2-ol	67-63-0	DNEL	500 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	chronic - systemic effects
propan-2-ol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Germany: en Page: 5 / 12



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Replaces version of: 2025-01-20 (GHS 1) Revision: 2025-08-07

Relevant PNECs of	components					
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
N-butyl acetate	123-86-4	PNEC	0.18 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.018 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	marine water	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.36 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	water	intermittent re- lease
N-butyl acetate	123-86-4	PNEC	35.6 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.981 <sup>mg</sup> / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.098 <sup>mg</sup> / kg	aquatic organ- isms	marine sediment	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.09 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)
acetone	67-64-1	PNEC	21 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	water	intermittent re- lease
acetone	67-64-1	PNEC	10.6 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 <sup>mg</sup> / <sub>I</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)
propan-2-ol	67-63-0	PNEC	160 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	water	short-term (single instance)
propan-2-ol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	water	intermittent re- lease
propan-2-ol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)
propan-2-ol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	marine water	short-term (single instance)
propan-2-ol	67-63-0	PNEC	2,251 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
propan-2-ol	67-63-0	PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
propan-2-ol	67-63-0	PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	marine sediment	short-term (single instance)
propan-2-ol	67-63-0	PNEC	28 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)

#### 8.2 **Exposure controls**

### **Appropriate engineering controls**

General ventilation.

Individual protection measures (personal protective equipment)







Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Page: 6 / 12 Germany: en



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Revision: 2025-08-07 Replaces version of: 2025-01-20 (GHS 1)

## Eye/face protection

Use protective eyewear to guard against splash of liquids.

#### Skin protection Hand protection

Wear protective gloves. (Splash protection)

#### Type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

#### Breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Full face mask/half mask/quarter mask (EN 136/140). Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White).

#### **Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

**Physical state** aerosol (spray aerosol)

Colour transparent Odour characteristic Melting point/freezing point not determined Boiling point or initial boiling point and boiling range -161.5 °C at 1.013 hPa

**Flammability** 

flammable aerosol in accordance with GHS criteria

Lower and upper explosion limit 50 g/m<sup>3</sup> - 335 g/m<sup>3</sup> / 2.2 vol% - 15 vol%

Flash point -88.6 °C at 1,013 hPa

**Auto-ignition temperature** 287 °C (auto-ignition temperature (liquids and gases))

**Decomposition temperature** not relevant pH (value) not determined **Kinematic viscosity** not relevant Solubility(ies) not determined

**Partition coefficient** 

Partition coefficient n-octanol/water this information is not available

(log value)

4.200 hPa at 20 °C Vapour pressure

Density and/or relative density

Density 0.7222 g/ml (calculated value)

Relative vapour density information on this property is not available

9.2 Other information

Information with regard to physical there is no additional information

hazard classes

Other safety characteristics

Temperature class (EU, acc. to ATEX) T3 (maximum permissible surface temperature on the equipment: 200°C)

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

#### 10.2 **Chemical stability**

See below "Conditions to avoid".

#### Possibility of hazardous reactions 10.3

No known hazardous reactions.

#### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

#### Hints to prevent fire or explosion

Protect from sunlight.

#### 10.5 Incompatible materials

Page: 7 / 12 Germany: en



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Revision: 2025-08-07 Replaces version of: 2025-01-20 (GHS 1)

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

#### **Acute toxicity**

Shall not be classified as acutely toxic.

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

#### Other information

Repeated exposure may cause skin dryness or cracking.

## 11.2 Information on other hazards

There is no additional information.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)

#### 12.2 Persistence and degradability

Data are not available

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq$  0,1%.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

#### 12.7 Other adverse effects

Data are not available

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

### List of wastes. (Recommendations)

#### Product

08 01 11\* Waste paint and varnish containing organic solvents or other hazardous substances

#### **Product residues**

16 05 04\* Gases in pressure containers (including halons) containing hazardous substances

#### **Packagings**

Germany: en Page: 8 / 12



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Revision: 2025-08-07 Replaces version of: 2025-01-20 (GHS 1)

15 01 04 Metallic packaging

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

#### SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN UN 1950
IMDG-Code UN 1950
ICAO-TI UN 1950

14.2 UN proper shipping name

ADR/RID/ADN AEROSOLS IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

 ADR/RID/ADN
 2 (2.1)

 IMDG-Code
 2.1

 ICAO-TI
 2.1

**14.4** Packing group not assigned

**14.5** Environmental hazards non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code 5F Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D

#### International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant - Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -

### International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167
Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Germany: en Page: 9 / 12



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Revision: 2025-08-07 Version number: GHS 2.0 Replaces version of: 2025-01-20 (GHS 1)

#### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed **Deco-Paint Directive (2004/42/EC)** 

665.3 <sup>g</sup>/<sub>I</sub> **VOC content** 

Maximum VOC content limit								
Product category	Product subcategory	Coating	Туре	VOC g/l				
vehicle refinishing products	special finishes	all types		840				

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

#### Regulation on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) No 2019/1148: All suspicious transactions as well as the loss and theft of significant quantities must be reported to the competent authority.

Explosives precursors which are subject to restrictions								
Name of substance	CAS No	Type of registration	Remarks	Limit value	Upper limit value for the purpose of licensing under Art- icle 5(3)			
acetone	67-64-1	Annex II						

#### Legend

Annex II Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported

#### Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

#### National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water

1 slightly hazardous to water

hazard class)

#### Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentra- tion	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 <sup>kg</sup> / <sub>h</sub>	50 <sup>mg</sup> / <sub>m³</sub>	3)

#### **Notation**

a total mass flow of 0.50 kg/h or a total mass concentration of  $50 \text{ mg/m}^3$ , each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

#### **National inventories**

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed

#### Leaend

REACH Reg. REACH registered substances

#### 15.2 **Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

Page: 10 / 12 Germany: en



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Revision: 2025-08-07 Replaces version of: 2025-01-20 (GHS 1)

#### **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
5.2	Special hazards arising from the substance or mixture	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.	yes
7.1	Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Use only in well-ventilated areas.	Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.	yes
12.5	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not con- tain a PBT-/vPvB-substance at a concentration of $\geq$ 0,1%.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0,1%.	yes

#### Abbreviations and acronyms

Descriptions of used abbreviations.

Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC. Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways). 2019/1831/EU.

ADN

ADR.

ADR/RID/ADN.

ADR/RID/ AGW. CAS. Ceiling-C. CLP. DFG.

Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).

Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).

Workplace exposure limit.

Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).

Ceiling value.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.

DGR. DNEL EC No.

ED.
EINECS.
ELINCS.
EmS.
Eye Dam.
Eye Irrit.
Flam. Gas.
Flam. Liq.
GHS.
IATA/DGR.
ICAO-II.
IMDG.
IMDG-Code.
Index No.
IOELV.
LGK.
NLP.

PBT. PNEC.

Ppm. Press. Gas. REACH. RID.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.

Dangerous Goods Regulations (see IATA/DGR).
Derived No-Effect Level.

The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
European Inventory of Existing Commercial Chemical Substances.
European Inventory of Existing Commercial Chemical Substances.
European Inventory of Existing Commercial Substances.
European Inst of Notified Chemical Substance of Chemicals.
Every European Institutions for the Safe transport of dangerous goods by air.
International Maritime Dangerous Goods Code.
International Maritime Dangerou

STEL. STOT SE. SVHC. TRGS. TRGS 900. TRGS 903. TWA.

#### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No.

1907/2006 (REACH), amended by 2020/878/EU.
Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Page: 11 / 12 Germany: en



according to Regulation (EC) No. 1907/2006 (REACH)

#### 2000 354 676 - TECWERK ROSTUMWANDLER - 400 ml

Version number: GHS 2.0 Replaces version of: 2025-01-20 (GHS 1) Revision: 2025-08-07

H221. H222. H225. H226. H229. H280. H319.	Extremely flammable gas. Flammable gas. Extremely flammable aerosol. Highly flammable liquid and vapour. Flammable liquid and vapour. Pressurised container: May burst if heated. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
---	---

List of relevant phrases (code and full text as stated in section 2 and 3)

#### Disclaimer

This SDS has been compiled and is solely intended for this product. This information is based on the present state of our knowledge and does not constitute an assurance of product properties nor establishes contract legal rights. All data about health and safety are only for information. They should therefore not be construed as specifications.

Page: 12 / 12 Germany: en