

Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX SX90 PLUS

Article number:

04741000, 04742000, 04743000, 04744000

UFI: D960-405A-Y00C-4A3Y

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Penetrating oil Anticorrosion additive

Lubricant

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

(Contd. on page 2)



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 1)

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/inational/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/this mixture contains components that exhibit or are suspected of exhibiting endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

List II

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and mineral oil with additives in petroleum distillate

EC No 926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2%	25-<
Reg.nr.: 01-2119456620-43-xxxx	aromatics Alternative CAS number: 64742-47-8 Sp. Tox. 1, H304, EUH066	
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil, petroleum Sp. Tox. 1, H304 Asp. Tox. 1, H304	25-<
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<1
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<1
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<
CAS: 1474044-79-5 EC No 939-717-7 Reg.nr.: 01-2119980985-16-xxxx	calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) Alternative CAS number: 57855-77-3 Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<:
CAS: 110-25-8 EC number: 701-177-3 Reg.nr.: 01-2119488991-20-xxxx	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1); Acute Tox. 4, H332; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	<1'
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46-xxxx	2,6-di-tert-butyl-p-cresol Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	<0.2

Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons

Additional information: For the wording of the listed hazard phrases refer to section 16.

≥30%



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Drowsiness

Nausea

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel

Do not inhale gases / fumes / aerosols.

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

(Contd. on page 4)



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 3)

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

When using product on electrical parts disconnect them from power supply first. Before re-assembly, let dry for 2 minutes.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with lin	nit values that require monitoring at the workplace:
Hydrocarbons, C11	I-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics
RCP-TWA (EU)	Long-term value: 1200 mg/m³, 165 ppm Vapour / Total Hydrocarbons
CAS: 106-97-8 buta	ne
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
OEL (Ireland)	Short-term value: 1000 ppm
CAS: 74-98-6 propa	nne
OEL (Ireland)	Asphx
CAS: 75-28-5 isobu	tane
OEL (Ireland)	Short-term value: 1000 ppm
CAS: 128-37-0 2,6-0	di-tert-butyl-p-cresol
WEL (Great Britain)	Long-term value: 10 mg/m³
OEL (Ireland)	Long-term value: 2 mg/m³

____ ģi



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 4) Regulatory information WEL (Great Britain): EH40/2020 OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work **DNELs** CAS: 8042-47-5 White mineral oil, petroleum DNEL 40 mg/kg (consumer) (long-term exposure - systemic effects) Oral Dermal DNEL 92 mg/kg bw/day (consumer) (long-term exposure - systemic effects) 220 mg/kg bw/day (worker) (long-term exposure - systemic effects) Inhalative | DNEL | 35 mg/m³ (consumer) (long-term exposure - systemic effects) DNEL 160 mg/m³ (worker) (long-term exposure - systemic effects) CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) DNEL 10 mg/kg (worker) (longterm systematic effects) Dermal Inhalative | DNEL | 5 mg/m³ (worker) (longterm systematic effects) CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine Oral DNEL 92 mg/kg (consumer) (acute systematic effects) DNEL 5 mg/kg (consumer) (longterm systematic effects) Dermal DNEL 50 mg/kg (consumer) (acute systematic effects) 10 mg/kg (worker) (longterm systematic effects) DNEL 5 mg/kg (consumer) (longterm systematic effects) 100 mg/kg (worker) (acute systematic effects) Inhalative DNEL 9 mg/m³ (consumer) (acute locale effects) 18 mg/m³ (worker) (acute locale effects) DNEL 0.005 mg/m³ (consumer) (longterm local effects) 0.01 mg/m³ (worker) (longterm local effects) DNEL 0.1 mg/m³ (consumer) (longterm systematic effects) 0.2 mg/m³ (worker) (longterm systematic effects) CAS: 128-37-0 2,6-di-tert-butyl-p-cresol DNEL 0.25 mg/kg bw/day (vls) Oral DNEL | 0.25 mg/kg (vls) Dermal 0.5 mg/kg (wls) Inhalative DNEL 0.435 mg/m³ (vls) 1.76 mg/m3 (wls) **PNECs** CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) Oral PNEC 22.2 mg/kg food (human) PNEC 10 mg/l (KS) 0.004 mg/l (water (fresh water)) 0.0004 mg/l (water (sea water)) PNEC 69 mg/kg (sediment (fresh water)) 6.9 mg/kg (sediment (sea water)) 13.9 mg/kg (soil) CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine PNEC 0.0043 mg/l (sporadic release) 0.00043 mg/l (water (fresh water)) 0.000043 mg/l (water (sea water)) CAS: 128-37-0 2,6-di-tert-butyl-p-cresol PNEC 0.017 mg/l (sewage plant) 0.0002 mg/l (freshwater (Süßwasser)) 0.00002 mg/l (sediment (sea water)) PNEC 0.054 mg/kg (gro) 0.458 mg/kg (sediment (fresh water)) 0.046 mg/kg (sediment (sea water))



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 5)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed.

Respiratory protection:

Not required in normal cases

If the occupational exposure limit is exceeded: The following breathing protection is recommended: Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: Brown Odour: Solvent-like Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

Not applicable, as aerosol. range **Flammability** Extremely flammable aerosol.

Lower and upper explosion limit

0.6 Vol % (Hydrocarbons, C11-C14, n-alkanes, Lower:

isoalkanes, cyclics, < 2% aromatics)

Upper: 7 Vol % (Hydrocarbons, C11-C14, n-alkanes,

Not determined.

isoalkanes, cyclics, < 2% aromatics)

Flash point: Not applicable, as aerosol.

Decomposition temperature: Not determined. pН Not applicable. Viscosity:

Kinematic viscosity at 40 °C <20.5 mm²/s

(Active ingredient data)

Solubility water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure: Density and/or relative density

Density at 20 °C: 0.83-0.85 g/cm3 (Active ingredient data) Not determined.

Vapour density

9.2 Other information

Appearance:

Form: Aerosol

(Contd. on page 7)



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 6)

Important information on protection of health and

environment, and on safety.

Ignition temperature: Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air

mixture.

Change in condition
Evaporation rate

Not determined.

Information with regard to physical hazard classes
Explosives Void
Flammable gases Void
Aerosols

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
Hydrocari	bons, C11-	-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50/8h	>5,000 mg/m³ (rat) (OECD 403)	
CAS: 804	CAS: 8042-47-5 White mineral oil, petroleum		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
CAS: 147	CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)		
Oral	LD50	>2,500 mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rabbit)	

(Contd. on page 8)



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

		(Contd. of page	
Inhalative	LD50	>20 mg/l (rat)	
CAS: 110	-25-8 (Z)-N	-methyl-N-(1-oxo-9-octadecenyl)glycine	
Oral	LD50	5,000 mg/kg (rat) (OECD 401)	
		>5,000 mg/kg (Ratte) (OECD 420)	
Inhalative	LC50 / 4h	1.37 mg/m³ (rat)	
		1.8 mg/m³ (Ratte) (OECD 403)	
CAS: 128	CAS: 128-37-0 2,6-di-tert-butyl-p-cresol		
Oral	LD50	>5,000 mg/kg (rat) (OECD-Prüfrichtlinie 401)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)	
Skin corr	osion/irrita	ntion Based on available data, the classification criteria are not met.	
Serious e	ye damage	e/irritation Based on available data, the classification criteria are not met.	
Respirato	ory or skin	sensitisation Based on available data, the classification criteria are not met.	
Germ cell	l mutageni	city Based on available data, the classification criteria are not met.	
Carcinog	Carcinogenicity Based on available data, the classification criteria are not met.		
Reproduc	tive toxici	ty Based on available data, the classification criteria are not met.	
STOT-sin	gle exposi	ure Based on available data, the classification criteria are not met.	
STOT-repeated exposure Based on available data, the classification criteria are not met.			

Additional toxicological information:

Repeated dose toxicity

CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

Oral NOAEL 90 d 100 mg/kg (rat) (OECD 408, 90d, target organ: liver)

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

The product contains substances suspected of causing endocrine disruptions with health effects.

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol List II

SECTION 12: Ecological information

Aquatic toxicity:	
Hydrocarbons, C11-C1	4, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)
CAS: 8042-47-5 White I	mineral oil, petroleum
NOELR	>100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50 / 96h	>1,000 mg/l (Leuciscus idus) (OECD 203)
EC50 / 48h	>100 mg/l (daphnia)
NOEC/NOEL	≥100 mg/l (fish) (96h)
	≥100 mg/l (algae) (72h)
	≥100 mg/l (daphnia) (48h)
CAS: 106-97-8 butane	
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
CAS: 74-98-6 propane	•
LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

CAS: 75 1	28-5 isobutane	(Contd. of
CAS: /5-2		e 27.98 mg/l (fish)
		27.96 mg/l (ilsn) 7.71 mg/l (algae)
CAS: 147		cium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)
Inhalative		>20 mg/L (rat)
IIIIIaialive		>0.28 mg/l (fish)
	NOEL 21 d	2.2-10 mg/l (daphnia)
	EC50	>0.27 mg/l (daphnia)
	EC50 / 48h	>0.27 mg/l (daphnia) >0.27 mg/l (daphnia)
	IC50 / 48h	>0.27 mg/l (daphnia) >0.27 mg/l (daphnia)
		>0.27 mg/l (algae)
CAS: 110		ethyl-N-(1-oxo-9-octadecenyl)glycine
CA3. 110		6.8 mg/l (fish)
		50 mg/l (activated sludge)
		0.43 mg/l (Daphnia magna)
		6.3 mg/l (Scenedesmus subspicatus)
	EC30 / 1211	0.91 mg/l (Desmodesmus subspicatus) (OECD 201)
CAC: 120	27 0 2 6 di to	rt-butyl-p-cresol
CA3. 120	-	0.758 mg/l (algae)
		0.199 mg/l (fish)
		0.48 mg/l (Daphnia magna)
		0.053 mg/l (Oryzias latipes)
	NOEC / 21 a	0.069 mg/l (Daphnia magna)
	istence and d	
•		4, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	ation 69 % (2	
		mineral oil, petroleum
_	-	28d (OECD 301B))
		ethyl-N-(1-oxo-9-octadecenyl)glycine
CSB	2,400 m	• •
Biodegrad	ation 85 % (C	ECD 301 B Ready Biodegradability CO2 Evolution)
12.3 Bioa	ccumulative p	otential
		cium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)
	3.16	
log POW		
CAC. 440	25_8 (7)_N_ma	ethyl-N-(1-oxo-9-octadecenyl)glycine

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

(Contd. on page 10)



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 9)

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	n
14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es) ADR/RID/ADN	
Class	2 5F Gases.
Label IMDG, IATA	2.1
Class Label	2.1 Gases. 2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	see Sections 6-8
Stowage Code	Warning: Gases. SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according	
instruments	Not applicable.
Transport/Additional information:	
ADR/RID/ADN Limited quantities (LQ) Transport category	1L 2



Printing date 26.06.2023 Version: 9.00 (replaces version 8.01) Revision: 21.07.2022

(Contd. of page 10)

Tunnel restriction code UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 50.52 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS **REGULATION (EU) 2019/1148**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1 On basis of test data

Date of previous version: 22.04.2021 Version number of previous version: 8.01

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases - Category 1A

(Contd. on page 12)



Version: 9.00 (replaces version 8.01) Printing date 26.06.2023 Revision: 21.07.2022

(Contd. of page 11)

Aerosol 1: Aerosols - Category 1

: Aerosols - Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
* Data compared to the previous version altered.