

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **ZINK-ALU-SPRAY - 400 ml**

Article number: 4000 354070

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the preparation: Lacquer

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Nordwest Handel AG

Berliner Str. 26 - 36

D-58135 Hagen

Phone: +49 (0)2331/4610

Fax: +49 (0)2331/461389

Further information obtainable from: Datenblatt ausstellender Bereich/fachkundige Person: [sdb@nordwest.com](mailto:sdb@nordwest.com)

### 1.4 Emergency telephone number:

Deutschland:

Giftinformationszentrum (GIZ), Mainz - Tel. +49(0)6131/19240 (24 h von Mo. – So.)

Österreich:

Vergiftungsinformationszentrale der Gesundheit Österreich Tel. +43 1 406 43 43

Schweiz:

Tox Info Suisse Tel. 145, 24h oder +41 44 251 51 51

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02

GHS07

Signal word Danger

#### Hazard-determining components of labelling:

ethyl acetate

acetone

#### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing mist/vapours/spray.

P273 Avoid release to the environment.

(Contd. on page 2)

DE

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

**Trade name: ZINK-ALU-SPRAY - 400 ml**

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

|                                                                                                      |                                                                                               |         |
|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|---------|
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0                                     | butane<br>Flam. Gas 1, H220; Press. Gas, H280                                                 | 25-40%  |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5                                      | propane<br>Flam. Gas 1, H220; Press. Gas, H280                                                | 10-<25% |
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Index number: 607-022-00-5<br>Reg.nr.: 01-2119475103-46        | ethyl acetate<br>Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336                      | 10-<25% |
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Index number: 606-001-00-8<br>Reg.nr.: 01-2119471330-49-xxxx    | acetone<br>Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336                            | 10-<25% |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Index number: 601-022-00-9                                    | xylene<br>Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315     | 3-5%    |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Index number: 607-025-00-1                                     | n-butyl acetate<br>Flam. Liq. 3, H226; STOT SE 3, H336                                        | 1-<3%   |
| CAS: 64742-48-9<br>EINECS: 265-150-3<br>Index number: 649-327-00-6<br>Reg.nr.: 01-2119457273-39-XXXX | Naphtha (petroleum), hydrotreated heavy<br>Flam. Liq. 3, H226; Asp. Tox. 1, H304              | 1-<3%   |
| CAS: 7429-90-5<br>EINECS: 231-072-3<br>Index number: 013-002-00-1                                    | aluminium powder (stabilised)<br>Flam. Sol. 1, H228; Water-react. 2, H261                     | 1-<3%   |
| CAS: 7440-66-6<br>EINECS: 231-175-3<br>Index number: 030-001-01-9                                    | zinc powder -zinc dust (stabilized)<br>Aquatic Acute 1, H400; Aquatic Chronic 1, H410         | ≤1%     |
| CAS: 78-78-4<br>EINECS: 201-142-8<br>Index number: 601-006-00-1                                      | isopentane<br>Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336 | 0,3-<1% |

## SECTION 4: First aid measures

**4.1 Description of first aid measures**

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.
 DE  
 (Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: ZINK-ALU-SPRAY - 400 ml

(Contd. of page 2)

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.  
Recommended storage temperature: 10-30 °C.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

### 106-97-8 butane

|               |                                                    |
|---------------|----------------------------------------------------|
| AGW (Germany) | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm |
|               | 4(II);DFG                                          |

### 74-98-6 propane

|               |                                                    |
|---------------|----------------------------------------------------|
| AGW (Germany) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
|               | 4(II);DFG                                          |

### 141-78-6 ethyl acetate

|               |                                                   |
|---------------|---------------------------------------------------|
| AGW (Germany) | Long-term value: 1500 mg/m <sup>3</sup> , 400 ppm |
|               | 2(I);DFG, Y                                       |

### 67-64-1 acetone

|               |                                                   |
|---------------|---------------------------------------------------|
| AGW (Germany) | Long-term value: 1200 mg/m <sup>3</sup> , 500 ppm |
|               | 2(I);DFG, EU                                      |

### 1330-20-7 xylene

|               |                                                  |
|---------------|--------------------------------------------------|
| AGW (Germany) | Long-term value: 440 mg/m <sup>3</sup> , 100 ppm |
|               | 2(II);DFG, EU, H                                 |

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: ZINK-ALU-SPRAY - 400 ml

(Contd. of page 3)

**123-86-4 n-butyl acetate**

AGW (Germany) Long-term value: 300 mg/m<sup>3</sup>, 62 ppm  
2(l);Y, AGS

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

MAK (Germany) Long-term value: 300 mg/m<sup>3</sup>, 50 ppm  
vgl. Abschn. Xc

**7440-66-6 zinc powder -zinc dust (stabilized)**

MAK (Germany) Long-term value: 0,1A\* 2E\*\* mg/m<sup>3</sup>  
\*alveolengängig; \*\*eintembar

**· DNELs****141-78-6 ethyl acetate**

|            |      |                                                                                                                                                                                             |
|------------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Oral       | DNEL | 4,5 mg/kg/bw/day (population) (Long-term - systemic effects)                                                                                                                                |
| Dermal     | DNEL | 37 mg/kg bw/day (population) (Long-term - systemic effects)<br>63 mg/kg bw/day (worker) (Long-term - systemic effects)                                                                      |
| Inhalative | DNEL | 734 mg/m <sup>3</sup> (population) (Acute - systemic effects)<br>1468 mg/m <sup>3</sup> (worker) (Acute - systemic effects)<br>734 mg/m <sup>3</sup> (population) ((Acute - local effects)) |

**67-64-1 acetone**

|            |      |                               |
|------------|------|-------------------------------|
| Oral       | DNEL | 62 mg/kg/bw/day (human)       |
| Dermal     | DNEL | 62 mg/kg bw/day (human)       |
| Inhalative | DNEL | 200 mg/m <sup>3</sup> (human) |

**1330-20-7 xylene**

|            |      |                                                                                                                                    |
|------------|------|------------------------------------------------------------------------------------------------------------------------------------|
| Dermal     | DNEL | 108 mg/kg bw/day (population) (long term - systemic-effects)<br>180 mg/kg bw/day (worker) (long-term - systemic effects)           |
| Inhalative | DNEL | 14,8 mg/m <sup>3</sup> (population) (long-term - systemic-effects)<br>77 mg/m <sup>3</sup> (worker) (long-term - systemic-effects) |

**· PNECs****141-78-6 ethyl acetate**

PNEC 650 mg/l (STP)  
PNEC sediment 0,34 mg/kg dw (Bel) (freshwater)

**· Ingredients with biological limit values:****67-64-1 acetone**

BGW (Germany) 80 mg/l  
Untersuchungsmaterial: Urin  
Probennahmezeitpunkt: Expositionsende bzw. Schichtende  
Parameter: Aceton

**1330-20-7 xylene**

BGW (Germany) 1,5 mg/l  
Untersuchungsmaterial: Vollblut  
Probennahmezeitpunkt: Expositionsende bzw. Schichtende  
Parameter: Xylol  
  
2 g/l  
Untersuchungsmaterial: Urin  
Probennahmezeitpunkt: Expositionsende bzw. Schichtende  
Parameter: Methylhippur-(Tolur-)Säure

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

**· Respiratory protection:**

Not necessary if room is well-ventilated.  
When used properly and under normal conditions, breathing protection is not required.

· **Protection of hands:** Not required.

(Contd. on page 5)

DE

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.11.2015

Revision: 09.11.2015

Trade name: ZINK-ALU-SPRAY - 400 ml

(Contd. of page 4)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **As protection from splashes gloves made of the following materials are suitable:** PVC or PE gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Light weight protective clothing

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Silver grey

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not applicable for an aerosol \*

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 365 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Protect from sunlight and temperatures above 50 °C. Development of explosive vapor / air mixtures.

· **Explosion limits:**

Lower: 1,5 Vol %

Upper: 13,0 Vol %

· **Vapour pressure at 20 °C:** 4200 hPa

· **Density at 20 °C:** 0,663 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **9.2 Other information**

\* The final mixture in the aerosol is formed only after the addition of the pressurized gas. Some data are not measurable in a hermetically sealed, pressurized container.

## SECTION 10: Stability and reactivity

· **10.1 Reactivity**

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

DE  
(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: ZINK-ALU-SPRAY - 400 ml

(Contd. of page 5)

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity:

#### LD/LC50 values relevant for classification:

##### 141-78-6 ethyl acetate

|            |          |                        |
|------------|----------|------------------------|
| Oral       | LD50     | 5620 mg/kg (rabbit)    |
| Dermal     | LD50     | > 18000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 56 mg/l (rat)          |

##### 67-64-1 acetone

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | 5800 mg/kg (rat)     |
| Dermal     | LD50     | 20000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 76 mg/l (rat)        |

##### 1330-20-7 xylene

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | > 2000 mg/kg (rat)    |
| Dermal     | LD50     | > 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5 mg/l (rat)          |

##### 123-86-4 n-butyl acetate

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | 13100 mg/kg (rat)    |
| Dermal     | LD50     | >5000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21,0 mg/l (rat)     |

##### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >3000 mg/kg (rab) |

#### Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: Irritating effect.

· Sensitisation: No sensitising effects known.

#### Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

##### 74-98-6 propane

|             |                           |
|-------------|---------------------------|
| EC50 / 48h  | 27,1 mg/l (daphnia magna) |
| EC50 / 72h  | 11,9 mg/l (Algen)         |
| LC50 / 96 h | 49,9 mg/l (fish)          |

##### 141-78-6 ethyl acetate

|             |                                                    |
|-------------|----------------------------------------------------|
| EC50 / 48h  | 717 mg/l (daphnia magna)                           |
|             | 3300 mg/l (Scenedesmus subspicatus)                |
| LC50 / 96 h | 230 mg/l (Pimephales promelas)                     |
| NOEC        | 2,4 mg/l (daphnia magna) (21d; DIN 38412, Part 11) |
| NOEC / 72h  | > 100mg mg/l (Desmodesmus subspicatus) (OECD 201)  |

##### 67-64-1 acetone

|             |                                                     |
|-------------|-----------------------------------------------------|
| EC50 / 48h  | >100 mg/l (daphnia magna)                           |
| LC50        | 20,000 mg/l (rabbit)                                |
| LC50 / 96 h | 7500 mg/l (Leuciscus idus (Aland))                  |
|             | 5540 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) |
| LC50/48h    | 12600 mg/l (daphnia magna)                          |
| NOEC / 16h  | 1700 mg/l (Pseudomonas putida)                      |
| NOEC / 48h  | 4740 mg/l (Pseudokirchneriella subcapitata)         |

##### 1330-20-7 xylene

|             |                    |
|-------------|--------------------|
| LC50 / 96 h | 1 - 10 mg/l (fish) |
|-------------|--------------------|

(Contd. on page 7)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.11.2015

Revision: 09.11.2015

Trade name: ZINK-ALU-SPRAY - 400 ml

(Contd. of page 6)

**123-86-4 n-butyl acetate**

|             |                               |
|-------------|-------------------------------|
| EC50 / 48h  | >10-100< mg/l (daphnia magna) |
| EC50 / 72h  | >100 mg/l (Algen)             |
| LC50 / 96 h | >10-100< mg/l (fish)          |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

|           |                                                                                                                           |
|-----------|---------------------------------------------------------------------------------------------------------------------------|
| 16 05 04* | gases in pressure containers (including halons) containing dangerous substances                                           |
| 15 01 11* | metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers |

- **Uncleaned packaging:**
- **Recommendation:** Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

**SECTION 14: Transport information**

- |                                                                                                                                                                                                                       |                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>                                                                                                           | <p>UN1950</p>                                             |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>                                                           | <p>1950 AEROSOLS<br/>AEROSOLS<br/>AEROSOLS, flammable</p> |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>                                                                                                      |                                                           |
| <div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> | <p>2 5F Gases.<br/>2.1</p>                                |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>                                                                                                                                                 |                                                           |
| <div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> | <p>2.1<br/>2.1</p>                                        |
| <ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>                                                                                                       |                                                           |
| <p>Void</p>                                                                                                                                                                                                           |                                                           |
| <ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>                                                                                            |                                                           |
| <p>No</p>                                                                                                                                                                                                             |                                                           |

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: ZINK-ALU-SPRAY - 400 ml

(Contd. of page 7)

|                                                                                       |                                                |
|---------------------------------------------------------------------------------------|------------------------------------------------|
| · <b>14.6 Special precautions for user</b>                                            | Warning: Gases.                                |
| · <b>Danger code (Kemler):</b>                                                        | -                                              |
| · <b>EMS Number:</b>                                                                  | F-D,S-U                                        |
| · <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                                |
| · <b>Transport/Additional information:</b>                                            |                                                |
| -----                                                                                 |                                                |
| · <b>ADR</b>                                                                          |                                                |
| · <b>Limited quantities (LQ)</b>                                                      | 1L                                             |
| · <b>Excepted quantities (EQ)</b>                                                     | Code: E0<br>Not permitted as Excepted Quantity |
| · <b>Transport category</b>                                                           | 2                                              |
| · <b>Tunnel restriction code</b>                                                      | D                                              |
| -----                                                                                 |                                                |
| · <b>IMDG</b>                                                                         |                                                |
| · <b>Limited quantities (LQ)</b>                                                      | 1L                                             |
| · <b>Excepted quantities (EQ)</b>                                                     | Code: E0<br>Not permitted as Excepted Quantity |
| · <b>UN "Model Regulation":</b>                                                       | UN1950, AEROSOLS, 2.1                          |

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.  
H224 Extremely flammable liquid and vapour.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H228 Flammable solid.  
H261 In contact with water releases flammable gases.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Gas 1: Flammable gases, Hazard Category 1  
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1  
Press. Gas: Gases under pressure: Compressed gas  
Flam. Liq. 1: Flammable liquids, Hazard Category 1  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Flam. Sol. 1: Flammable solids, Hazard Category 1  
Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

**Trade name: ZINK-ALU-SPRAY - 400 ml**

*Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*  
*Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3*

(Contd. of page 8)

DE