

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



revision: 2018-04-04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **STAINLESS STEEL SPRAY - 400 ml**
Article number 4000 354072

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use
paint, coating and lacquer

1.3 Details of the supplier of the safety data sheet

Nordwest Handel AG
Robert-Schuman-Str. 17
44263 Dortmund
Germany

Telephone: +49 (0)231 2222-3001
Telefax: +49 (0)231 2222-3099
Website: www.nordwest.com
e-Mail (competent person):

sdb@nordwest.com

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	Cat. 1	(Aerosol 1)	H222,H229
3.3	serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
3.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	Cat. 3	(STOT SE 3)	H335
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336
4.1C	hazardous to the aquatic environment - chronic hazard	Cat. 3	(Aquatic Chronic 3)	H412

Remarks

For full text of H-phrases: see SECTION 16.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS02, GHS07



H222
H229
H319
H335
H336
H412
P101
P102

Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects.
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTRE/doctor if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazardous ingredients for labelling:

Acetone. Hydrocarbons, C9, aromatics.













2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to EU regulation				
Name of substance	Identifier	Wt%	Classification acc. to 1272/2008/EC	Pictograms
butane	CAS No 106-97-8 EC No 203-448-7 REACH Reg. No 01-2119474691-32	25 – < 50	Flam. Gas 1 / H220 Press. Gas L / H280	 
propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944-21	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	 
acetone	CAS No 67-64-1 EC No 200-662-2 REACH Reg. No 01-2119471330-49	10 – < 25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 
Hydrocarbons, C9, aromatics	CAS No 64742-95-6 EC No 918-668-5 REACH Reg. No 01-2119455851-35-xxxx	10 – < 25	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	   
Aluminium powder (Stabilized)	CAS No 7429-90-5 EC No 231-072-3 REACH Reg. No 01-2119529243-45-xxxx	1 – < 5	Flam. Sol. 1 / H228 Acute Tox. 3 / H331	 

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

Hazardous ingredients acc. to EU regulation				
Name of substance	Identifier	Wt%	Classification acc. to 1272/2008/EC	Pictograms
Naphtha, wasserstoffbehandelt, niedrig siedend	CAS No 64742-48-9 EC No 918-317-6 REACH Reg. No 01-2119474196-32-xxxx	1 – < 5	Asp. Tox. 1 / H304	
Copper	CAS No 7440-50-8 EC No 231-159-6 REACH Reg. No 01-2119480154-42-xxxx	< 1	Acute Tox. 4 / H302 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	
zinc	CAS No 7440-66-6 EC No 231-175-3 REACH Reg. No 01-2119467174-37-xxxx	< 1	Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water. Take off contaminated clothing.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Collect spillage (universal binder).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

• Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

• Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

Observe instructions for use. Keep out of reach of children.

• Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
EU	acetone	67-64-1	IOELV	500	1,210			2017/2398/EU
GB	butane	106-97-8	WEL	600	1,450	750	1,810	EH40/2005
GB	acetone	67-64-1	WEL	500	1,210	1,500	3,620	EH40/2005
GB	aluminium	7429-90-5	WEL		10			EH40/2005
GB	aluminium	7429-90-5	WEL		4			EH40/2005
GB	copper	7440-50-8	WEL		1		2	EH40/2005
GB	copper	7440-50-8	WEL		0.2			EH40/2005

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
acetone	67-64-1	DNEL	2,420 mg/m³	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	64742-95-6	DNEL	150 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	64742-95-6	DNEL	25 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Aluminium powder (Stabilized)	7429-90-5	DNEL	3.72 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
Aluminium powder (Stabilized)	7429-90-5	DNEL	3.72 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Copper	7440-50-8	DNEL	20 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
Copper	7440-50-8	DNEL	137 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Copper	7440-50-8	DNEL	273 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
zinc	7440-66-6	DNEL	83 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
zinc	7440-66-6	DNEL	5 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

• relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
acetone	67-64-1	PNEC	21 mg/l	aquatic organisms	water	intermittent release
Copper	7440-50-8	PNEC	7.8 µg/l	aquatic organisms	freshwater	short-term (single instance)
Copper	7440-50-8	PNEC	230 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Copper	7440-50-8	PNEC	87 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Copper	7440-50-8	PNEC	676 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Copper	7440-50-8	PNEC	65 mg/kg	terrestrial organisms	soil	short-term (single instance)
Copper	7440-50-8	PNEC	5.2 µg/l	aquatic organisms	marine water	short-term (single instance)
zinc	7440-66-6	PNEC	20.6 µg/l	aquatic organisms	freshwater	short-term (single instance)
zinc	7440-66-6	PNEC	6.1 µg/l	aquatic organisms	marine water	short-term (single instance)
zinc	7440-66-6	PNEC	100 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
zinc	7440-66-6	PNEC	117.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
zinc	7440-66-6	PNEC	56.5 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
zinc	7440-66-6	PNEC	35.6 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

• hand protection

Wear protective gloves. (Splash protection)

• type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection

Full face mask/half mask/quarter mask (EN 136/140)

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White)

Environmental exposure controls

Use appropriate container to avoid environmental contamination.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state

aerosol (spray aerosol)

Colour

different

Odour

characteristic

Other physical and chemical parameters

Melting point/freezing point

not applicable (aerosol)

Initial boiling point and boiling range

not applicable (aerosol)

Flash point

not applicable (aerosol)

Flammability (solid, gas)

flammable aerosol in accordance with GHS criteria

Explosive limits

• lower explosion limit (LEL)

0.6 vol%

• upper explosion limit (UEL)

15 vol%

Vapour pressure

4,200 hPa at 20 °C

Density

0.6824 g/ml (calculated value)

Solubility(ies)

not determined

Partition coefficient

n-octanol/water (log KOW)

This information is not available.

Auto-ignition temperature

>200 °C

Viscosity

not relevant (aerosol)

Explosive properties

none

Oxidising properties

none

9.2 Other information

There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. - Keep away from heat.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

high temperatures

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

• Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Aluminium powder (Stabilized)	7429-90-5	inhalation: dust/mist	0.888 mg/l/4h
Copper	7440-50-8	oral	500 mg/kg

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
acetone	67-64-1	oral	LD50	5,800 mg/kg	rat
Aluminium powder (Stabilized)	7429-90-5	inhalation: dust/mist	LC50	>0.888 mg/l/4h	rat
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	oral	LD50	>15,000 mg/kg	rat
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	inhalation: vapour	LC50	>4,951 mg/m ³ /4h	rat
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	dermal	LD50	3,160 mg/kg	rabbit
zinc	7440-66-6	oral	LD50	>2,000 mg/kg	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
butane	106-97-8	LC50	27.98 mg/l	fish	96 h
butane	106-97-8	EC50	7.71 mg/l	algae	96 h
propane	74-98-6	LC50	27.98 mg/l	fish	96 h
propane	74-98-6	EC50	7.71 mg/l	algae	96 h
acetone	67-64-1	LC50	8,120 mg/l	fish	96 h
Hydrocarbons, C9, aromatics	64742-95-6	LL50	9.2 mg/l	fish	96 h
Hydrocarbons, C9, aromatics	64742-95-6	EL50	3.2 mg/l	aquatic invertebrates	48 h
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	LL50	>1,000 mg/l	fish	48 h
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	EL50	>1,000 mg/l	aquatic invertebrates	48 h
Copper	7440-50-8	LC50	193 µg/l	fish	96 h
zinc	7440-66-6	LC50	439 µg/l	fish	96 h
zinc	7440-66-6	EC50	1,833 µg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
acetone	67-64-1	EC50	61.15 g/l	microorganisms	30 min
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	LL50	>1,000 mg/l	fish	24 h
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	EL50	>1,000 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
acetone	67-64-1	carbon dioxide generation	90.9 %	28 d
Hydrocarbons, C9, aromatics	64742-95-6	oxygen depletion	30.9 %	2 d
Naphtha, wasserstoffbehandelt, niedrig siedend	64742-48-9	oxygen depletion	7.3 %	4 d

12.3 Bioaccumulative potential

Data are not available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
acetone	67-64-1		-0.24	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

16 05 04x gases in pressure containers (including halons) containing dangerous substances

15 01 10x packaging containing residues of or contaminated by dangerous substances

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	1950
14.2	UN proper shipping name	AEROSOLS
14.3	Transport hazard class(es)	
	Class	2 (gases) (aerosol)
	Subsidiary risk(s)	2.1 (flammability)
14.4	Packing group	not assigned to a packing group
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	Special precautions for user	
	Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1950
Proper shipping name	AEROSOLS
Class	2
Classification code	5F
Danger label(s)	2.1

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D
• International Maritime Dangerous Goods Code (IMDG)	
UN number	1950
Proper shipping name	AEROSOLS
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-
• International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	1950
Proper shipping name	Aerosols, flammable
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

• Directive 75/324/EEC relating to aerosol dispensers

Classification of the gas/aerosol

Extremely flammable

Labelling

Pressurized container: may burst if heated
Keep out of the reach of children
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Do not pierce or burn, even after use
Protect from sunlight. Do not expose to temperatures exceeding 50 °C

Net contents by volume

400 ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

• **Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)**

VOC content 87.08 %
594.2 g/l

Maximum VOC content limit			
Product category	Product subcategory	Coating	VOC g/l
vehicle refinishing products	special finishes	all types	840

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Trade name: EDELSTAHLSPRAY - 400 ml	Trade name: STAINLESS STEEL SPRAY - 400 ml	yes

Abbreviations and acronyms

2017/2398/EU.	Directive of the European Parliament and of the Council amending Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work.
Acute Tox.	Acute toxicity.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Aquatic Acute.	Hazardous to the aquatic environment - acute hazard.
Aquatic Chronic.	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
ATE.	Acute Toxicity Estimate.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
CMR.	Carcinogenic, Mutagenic or toxic for Reproduction.
COD.	Chemical oxygen demand.
DGR.	Dangerous Goods Regulations (see IATA/DGR).
DMEL.	Derived Minimal Effect Level.
DNEL.	Derived No-Effect Level.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EH40/2005.	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/).
EINECS.	European Inventory of Existing Commercial Chemical Substances.
ELINCS.	European List of Notified Chemical Substances.
EmS.	Emergency Schedule.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
Flam. Sol.	Flammable solid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
IMDG.	International Maritime Dangerous Goods Code.
IOELV.	Indicative occupational exposure limit value.
Log KOW.	n-Octanol/water.
MARPOL.	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant").
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
STEL.	Short-term exposure limit.
STOT SE.	Specific target organ toxicity - single exposure.
TWA.	Time-weighted average.
VOC.	Volatile Organic Compounds.
VPvB.	Very Persistent and very Bioaccumulative.
WEL.	Workplace exposure limit.

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354072 - STAINLESS STEEL SPRAY - 400 ml



Date of compilation: 2018-04-04

List of relevant phrases (code and full text as stated in chapter 2 and 3)

H220.	Extremely flammable gas.
H222.	Extremely flammable aerosol.
H225.	Highly flammable liquid and vapour.
H226.	Flammable liquid and vapour.
H228.	Flammable solid.
H229.	Pressurized container: may burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H302.	Harmful if swallowed.
H304.	May be fatal if swallowed and enters airways.
H319.	Causes serious eye irritation.
H331.	Toxic if inhaled.
H335.	May cause respiratory irritation.
H336.	May cause drowsiness or dizziness.
H400.	Very toxic to aquatic life.
H410.	Very toxic to aquatic life with long lasting effects.
H411.	Toxic to aquatic life with long lasting effects.
H412.	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.