according to Regulation (EC) No. 1907/2006 (REACH)



Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml Trade name

Unique formula identifier (UFI) FS50-3026-A00X-5TST

Article number 4000 354076

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses General use

Paint, coating and lacquer

1.3 Details of the supplier of the safety data sheet

> NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany

Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 e-mail: sdb@nordwest.com Website: www.nordwest.com

e-mail (competent person) sdb@nordwest.com

Emergency telephone number 1.4

Poison centre							
Country	Name	Postal code/city	Telephone				
Austria	Vergiftungsinformationszentrale der Gesundheit		+43 1 406 43 43				
Germany	Beratungsstelle bei Vergiftungen Giftinformationszentrale der Länder Rheinland- Pfalz und Hessen	55131 Mainz	+49(0)6131 / 19240				
Switzerland	Tox Info Suisse		+145, 24h oder +41 44 251 51 51				

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

2.2 **Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word **Pictograms**

danger

GHS02, GHS07



Hazard statements

Extremely flammable aerosol. H222

Pressurised container: May burst if heated. Causes skin irritation. H229 H315

H319

Causes serious eye irritation. May cause drowsiness or dizziness. H336

Page: 1 / 17 Germany: en

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Revision: 2021-03-30 Version number: GHS 2.0

Replaces version of: 2020-01-17 (GHS 1)

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

P101 P102 P210 P211 P251 P271 Do not pierce or burn, even after use.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/eye protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

P280

P305+P351+P338

easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. P312

P321 P410+P412

Specific treatment (see on this label).
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Hazardous ingredients for labelling acetone

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

Substances

Not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms
CAS No 106-97-8	butane	25 - < 50	Flam. Gas 1 / H220 Press. Gas L / H280	(N) (-)
EC No 203-448-7				
Index No 601-004-00-0				
REACH Reg. No 01-2119474691-32				
CAS No 67-64-1	acetone	25 - < 50	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319	
EC No 200-662-2			SŤOT SE 3 / H336	
Index No 606-001-00-8				
REACH Reg. No 01-2119471330-49				
CAS No 7429-90-5	Aluminium powder (Stabil- ized)	10 - < 25	Flam. Sol. 1 / H228	, who
EC No 231-072-3				
Index No 013-001-00-6				
REACH Reg. No 01-2119529243-45-xxxx				
CAS No 74-98-6	propane	5 - < 10	Flam. Gas 1 / H220 Press. Gas L / H280	
EC No 200-827-9				
Index No 601-003-00-5				
REACH Reg. No 01-2119486944-21				
CAS No 1330-20-7	xylene	5 - < 10	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332	
EC No 215-535-7			Skin Irrit. 2 / H315	
Index No 601-022-00-9				
REACH Reg. No 01-2119488216-32-xxxx				

Page: 2 / 17 Germany: en

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30

Replaces version of: 2020-01-17 (GHS 1)

Identifier	Nan	ne of substance	Wt%	Classification acc. to GHS		Pictograms	
EC No 918-481-9	n-Al	lenwasserstoffe, C10-C13, kane, Isoalkane, Cyc-	5-<10	Asp. Tox. 1 / H304			
REACH Reg. No 01-2119457273-39-xxxx	Ioaii	kane, <2% Aromaten					
CAS No 75-28-5	isob	utane	1-<5	Flam. Gas 1 / H220 Press. Gas L / H280			
EC No 200-857-2							
Index No 601-004-00-0							
REACH Reg. No 01-2119485395-27	ACH Reg. No 2119485395-27						
Name of substance		Specific Conc. Limits		M-Factors	ATE	Exposure route	
xylene -		-		-	1,100 ^{mg} / _{kg} 11 ^{mg} / _l /4h	dermal inhalation: vapour	

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Germany: en Page: 3 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Packaging compatibilities

Keep only in original container.

Storage class (LGK) TRGS 510

LGK 2 B (aerosol dispensers and lighters)

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits) Ceiling-C [ppm] Ceiling-C [mg/ m³] Coun-Name of agent **CAS No** Iden-TWA **TWA** STEL STEL Nota-Source [ppm] [mg/ m³] [ppm] [mg/ m³] DE 106-97-8 AGW 1,000 2,400 4,000 9,600 butane TRGS 900 DE xylene, mixture of 1330-20-7 MAK 50 220 100 440 DFG isomers DE 1330-20-7 50 220 100 440 Н TRGS xylene, mixture of AGW DF 67-64-1 AGW 500 1.200 1.000 **TRGS** acetone 2.400 900 DE TRGS propane 74-98-6 AGW 1,000 1,800 4,000 7,200 900 DE 1.5 DFG aluminium 7429-90-5 MAK DF aluminium 7429-90-5 MAK 4 dust, i DFG DE 75-28-5 AGW 1,000 2,400 4,000 9,600 TRGS isobutane

Germany: en Page: 4 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Replaces version of: 2020-01-17 (GHS 1) Revision: 2021-03-30

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling- C [ppm]	Ceiling- C [mg/ m³]	Nota- tion	Source
EU	xylene	1330-20-7	IOELV	50	221	100	442				2000/ 39/EC
EU	acetone	67-64-1	IOELV	500	1,210						2000/ 39/EC

Notation

ceiling value is a limit value above which exposure should not occur as dust Ceiling-C

dust H

absorbed through the skin

inhalable fraction respirable fraction

respiration raction short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the bio-STEL

TWA

Υ

logical limit value (BGW) are adhered to

_			 	
R	10	Ivaica	limit val	IIAC
v	ıv	iouica	ııııı vaı	ucs

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	xylene, mixture of isomers	methylhippuric acids		BAT	2,000 mg/l	DFG
DE	xylene, mixture of isomers	methylhippuric acids		BLV	2,000 mg/l	TRGS 903
DE	acetone	acetone		BLV	80 mg/l	TRGS 903
DE	aluminium	aluminium	crea	BAT	50 μg/g	DFG
DE	aluminium	aluminium	crea	BAT (BAR)	15 μg/g	DFG
DE	aluminium	aluminium	crea	BLV	50 μg/l	TRGS 903

Notation

creatinine crea

Relevant DNELs	of c	omponent	s of	the	mixture
----------------	------	----------	------	-----	---------

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
acetone	67-64-1	DNEL	2,420 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg	human, dermal	worker (industry)	chronic - systemic ef- fects
acetone	67-64-1	DNEL	1,210 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
xylene	1330-20-7	DNEL	289 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	289 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
xylene	1330-20-7	DNEL	180 mg/kg	human, dermal	worker (industry)	chronic - systemic ef- fects
xylene	1330-20-7	DNEL	77 mg/m³	human, inhalatory	worker (industry)	chronic - systemic ef- fects

Page: 5 / 17 Germany: en

according to Regulation (EC) No. 1907/2006 (REACH)



Revision: 2021-03-30

4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0

Replaces version of: 2020-01-17 (GHS 1)

Relevant PNECs of	components o	f the mixtur	e			
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
acetone	67-64-1	PNEC	10.6 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
acetone	67-64-1	PNEC	1.06 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
acetone	67-64-1	PNEC	100 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
acetone	67-64-1	PNEC	30.4 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
acetone	67-64-1	PNEC	3.04 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
acetone	67-64-1	PNEC	21 ^{mg} / _l	aquatic organisms	water	intermittent release
xylene	1330-20-7	PNEC	0.327 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
xylene	1330-20-7	PNEC	0.327 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
xylene	1330-20-7	PNEC	12.46 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
xylene	1330-20-7	PNEC	12.46 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)
xylene	1330-20-7	PNEC	2.31 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)
xylene	1330-20-7	PNEC	0.327 ^{mg} / _l	aquatic organisms	water	intermittent release
xylene	1330-20-7	PNEC	6.58 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)

8.2 **Exposure controls**

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)







Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection Hand protection

Wear protective gloves. (Splash protection)

Type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

Breakthrough times of the glove material

>480 minutes (permeation: level 6)

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Full face mask/half mask/quarter mask (EN 136/140). Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/ White).

Page: 6 / 17 Germany: en

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state aerosol (spray aerosol)

Colourlight silverMelting point/freezing pointnot determinedBoiling point or initial boiling pointnot applicable (aerosol)

and boiling range

Flammability flammable aerosol in accordance with GHS criteria

Lower and upper explosion limit 0.6 vol% - 15 vol% **Flash point** not applicable (aerosol)

Decomposition temperature not relevant

pH (value) not applicable (aerosol)

Kinematic viscosity not relevant **Solubility(ies)** not determined

Vapour pressure 4,200 hPa at 20 °C

Density and/or relative density

Density 0.7524 g/_{ml} (calculated value)

no data available

9.2 Other information

Information with regard to physical there is no additional information

hazard classes

Other safety characteristics

Temperature class (EU, acc. to ATEX) T3 (maximum permissible surface temperature on the equipment: 200°C)

Odour characteristic

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Germany: en Page: 7 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30

Replaces version of: 2020-01-17 (GHS 1)

Acute toxicity estimate (ATE) of components of the mixture						
Name of substance CAS No Exposure route ATE						
xylene	1330-20-7	dermal	1,100 ^{mg} / _{kg}			
xylene	1330-20-7	inhalation: vapour	11 ^{mg} / _l /4h			

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes, (Recommendations)

Product

08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances

Product residues

16 05 04* Gases in pressure containers (including halons) containing hazardous substances

Germany: en Page: 8 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

Packagings

15 01 04 Metallic packaging

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN UN 1950 IMDG-Code UN 1950 ICAO-TI UN 1950

14.2 UN proper shipping name

ADR/RID/ADN AEROSOLS IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

 ADR/RID/ADN
 2 (2.1)

 IMDG-Code
 2.1

 ICAO-TI
 2.1

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code 5F Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D

International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant - Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U

Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1



Special provisions (SP)A145, A167Excepted quantities (EQ)E0Limited quantities (LQ)30 kg

Germany: en Page: 9 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Deco-Paint Directive (2004/42/EC)

VOC content		651.9 ^g / _l			
Maximum VOC conten	t limit				
Product category Product subcategory Coating Type					VOC g/I
vehicle refinishing	special finish	es	all types		840

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
xylene	1330-20-7	(17) (11)	

Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

xylenes) is exceeded (17) Total mass of xylene (ortho-xylene, meta-xylene, para-xylene)

Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
Aluminium powder (Stabilized)		A)	

Legend

A) Indicative list of the main pollutants

Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

This product is regulated by Regulation (EU) No 2019/1148: All suspicious transactions as well as the loss and theft of significant quantities must be reported to the competent authority.

Explosives precursors which are subject to restrictions						
Name of substance	CAS No	Type of registration	Remarks	Limit value	Upper limit value for the pur- pose of li- censing un- der Article 5(3)	
acetone	67-64-1	Annex II				
Aluminium powder (Stabilized)	7429-90-5	Annex II	powd d < 200 μm > 70%			

Legend

> 70% As a substance or in mixtures containing 70 % or more, by weight, of aluminium and/or magnesium. Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported

d < 200 μ m With a particle size less than 200 μ m.

oowd Powde

National regulations (Germany)

Germany: en Page: 10 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water hazard class)

2 obviously hazardous to water

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentra- tion	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 ^{kg} / _h	50 ^{mg} / _{m³}	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
1.1	Trade name: ALUMINIUM W SPRAYU WYSOKA ODPORNOŚĆ NA TEMPERAT- URĘ - 400 ml	Trade name: PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH- HITZEBESTÄNDIG - 400 ml	yes
1.1		Unique formula identifier (UFI): FS50-3026-A00X-STST	yes
1.2	Uses advised against: do not use for products which come into contact with foodstuffs		yes
1.3	Details of the supplier of the safety data sheet: Nordwest Handel AG Robert-Schuman-Str. 17 44263 Dortmund Germany Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com	Details of the supplier of the safety data sheet: NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 e-mail: sdb@nordwest.com Website: www.nordwest.com	yes
1.3	e-Mail (competent person): sdb@nordwest.com		yes
1.3		e-mail (competent person): sdb@nordwest.com	yes
1.4		Poison centre: change in the listing (table)	yes
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1	Remarks: For full text of H-phrases: see SECTION 16.		yes
2.1	The most important adverse physicochemical, human health and environmental effects: In contact with water releases flammable gases which may ignite spontaneously. Spillage and fire water can cause pollution of watercourses.		yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes

Germany: en Page: 11 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



Revision: 2021-03-30

4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Replaces version of: 2020-01-17 (GHS 1)

8.1

8.1

8.1

8.1

8 1

8.1

Biological limit values

Relevant DNELs/DMELs/PNECs and other threshold levels

relevant DNELs of components of the mixture

• relevant PNECs of components of the mixture

Safety-rel-evant Section Former entry (text/value) Actual entry (text/value) ves Pictograms: change in the listing (table) 2.2 Pictograms: change in the listing (table) yes 2.2 Pictograms: change in the listing (table) yes 2.2 Precautionary statements: change in the listing (table) yes Hazardous ingredients for labelling: Acetone. N-Butyl acetate. Hydrocarbons, C9, aromatics. Hazardous ingredients for labelling: acetone 2.2 yes Other hazards: of no significance 2.3 Other hazards: There is no additional information. yes 3.1 Substances: Not relevant (mixture) yes 3.2 Hazardous ingredients acc. to EU regulation: change in the listing (table) yes 3.2 Description of the mixture: change in the listing (table) yes Description of the mixture: change in the listing (table) 3.2 yes Following skin contact: Wash with plenty of soap and water. Take off contaminated 4.1 Following skin contact: Wash with plenty of soap and water. ves Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice. Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. 4.1 yes 5.1 Suitable extinguishing media: D-powder, dry sand Suitable extinguishing media: Water spray, BC-powder yes Special hazards arising from the substance or mixture: Product may release hydrogen gas. Increased storage temper-atures will accelerate this process. Water-reactive (in contact with water releases flammable gases). 5.2 Special hazards arising from the substance or mixture Environmental precautions:
Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority. Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. 6.2 yes Advice on how to clean up a spill: Collect spillage (universal binder). 6.3 ves 7.2 Incompatible substances or mixtures: Observe hints for combined storage. Do not allow contact with yes • Evaporative conditions: Keep container tightly closed and in a well-ventilated place. 7.2 yes 72 Consideration of other advice: Observe instructions for use. Keep out of reach of children. yes Packaging compatibilities:
Only packagings which are approved (e.g. acc. to ADR) may be used. 7.2 Packaging compatibilities: Keep only in original container. yes 7.2 Storage class (LGK) TRGS 510: LGK 2 B (aerosol dispensers and lighters) yes 8.1 National limit values yes 8.1 Occupational exposure limit values (Workplace Exposure Limits) yes

Germany: en Page: 12 / 17

Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)

Relevant DNELs of components of the mixture: change in the listing (table)

yes

yes

yes

ves

yes

yes

according to Regulation (EC) No. 1907/2006 (REACH)



Revision: 2021-03-30

4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Replaces version of: 2020-01-17 (GHS 1)

> Safety-rel-evant Section Former entry (text/value) Actual entry (text/value) Relevant PNECs of components of the mixture: change in the listing (table) 8.1 ves Individual protection measures (personal protective equipment): eye protection must be worn safety gloves must be worn do not eat or drinkPersonal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization. Individual protection measures (personal protective equipment): eye protection must be worn safety gloves must be worn do not eat or drink 8.2 yes Environmental exposure controls: Use appropriate container to avoid environmental contamination. Environmental exposure controls: Use appropriate container to avoid environmental contamina-tion. Keep away from drains, surface and ground water. 8.2 9.1 Appearance ves 9.1 Odour: characteristic yes 9.1 Other physical and chemical parameters yes Melting point/freezing point: not applicable (aerosol) Melting point/freezing point: not determined 9.1 yes Flammability (solid, gas): flammable aerosol in accordance with GHS criteria mixture which, in contact with water, emits flammable gases (in accord-ance with GHS criteria) Flammability: flammable aerosol in accordance with GHS criteria 9.1 yes 9.1 **Explosive limits** Lower and upper explosion limit: 0.6 vol% - 15 vol% yes 9.1 • lower explosion limit (LEL): 3 vol% yes • upper explosion limit (UEL): 15 vol% 9.1 yes 9.1 Decomposition temperature: not relevant yes pH (value): not applicable (aerosol) 9.1 yes 9.1 Kinematic viscosity: not relevant ves 9.1 Partition coefficient yes n-octanol/water (log KOW): This information is not available 9.1 yes Auto-ignition temperature: 287 °C 9.1 ves 9 1 Viscosity: not relevant (aerosol) yes 9.1 Explosive properties: yes 9.1 Oxidising properties: yes 9.1 Density and/or relative density 9.1 yes Density: 0.7272 ^g/_{ml} (calculated value) Density: 0.7524 ^g/_{ml} (calculated value)no data available Other information: There is no additional information. 9.2 Other information yes Information with regard to physical hazard classes: there is no additional information 9.2 ves 9.2 Other safety characteristics yes Temperature class (EU, acc. to ATEX): T3 (maximum permissible surface temperature on the equipment: 200°C) 9.2 yes Odour: characteristic 9.2 yes Reactivity:
> Concerning incompatibility: see below "Conditions to avoid" and
> "Incompatible materials". The mixture contains reactive sub-stance(s): risk of ignition, reactivity with water Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive sub-stance(s). Risk of ignition. yes 10.1 10.3 Possibility of hazardous reactions: Material reacts vigorously with water emitting flammable gases. Possibility of hazardous reactions: No known hazardous reactions.

Germany: en Page: 13 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



Revision: 2021-03-30

4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Replaces version of: 2020-01-17 (GHS 1)

Safety-rel-evant Section Former entry (text/value) Actual entry (text/value) Physical stresses which might result in a hazardous situation and have to be avoided: high temperatures 10.4 ves 10.5 Incompatible materials: water - oxidisers Incompatible materials: Oxidisers 10.5 Release of flammable materials with: yes water 11.1 \bullet Acute toxicity of components of the mixture yes Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table) 11.1 yes 11.1 • Acute toxicity of components of the mixture: change in the listing (table) yes Summary of evaluation of the CMR properties: Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant. 11.1 yes 11.1 Specific target organ toxicity (STOT) yes Germ cell mutagenicity: Shall not be classified as germ cell mutagenic. 11.1 yes Carcinogenicity: Shall not be classified as carcinogenic. 11.1 yes 11.1 Reproductive toxicity: Shall not be classified as a reproductive toxicant. ves 11.2 Information on other hazards: There is no additional information. yes Toxicity:
Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany) 12.1 Toxicity: Harmful to aquatic life with long lasting effects. Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 2 (obviously hazardous to water)

12.1	Aquatic toxicity (acute)		yes
12.1	Aquatic toxicity (acute) of components of the mixture		yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1	Aquatic toxicity (chronic): May cause long-term adverse effects in the aquatic environment.		yes
12.1	Aquatic toxicity (chronic) of components of the mixture		yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.2	Degradability of components of the mixture		yes
12.2		Degradability of components of the mixture: change in the listing (table)	yes
12.3	Bioaccumulative potential of components of the mixture		yes
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)	yes
12.2	Persistence and degradability	Persistence and degradability: Data are not available.	yes
13.1	List of wastes: 16 05 04* gases in pressure containers (including halons) containing dangerous substances 15 01 10* packaging containing residues of or contaminated by dangerous substances	List of wastes, (Recommendations)	yes
13.1		Product: 08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances	yes
13.1		Product residues: 16 05 04* Gases in pressure containers (including halons) containing hazardous substances	yes
13.1		Packagings: 15 01 04 Metallic packaging	yes
14.1	UN number: 1950	UN number or ID number	yes
en			Page: 1

according to Regulation (EC) No. 1907/2006 (REACH)



Revision: 2021-03-30

4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Replaces version of: 2020-01-17 (GHS 1)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
14.1		ADR/RID/ADN: UN 1950	yes
14.1		IMDG-Code: UN 1950	yes
14.1		ICAO-TI: UN 1950	yes
14.2	UN proper shipping name: AEROSOLS	UN proper shipping name	yes
14.2		ADR/RID/ADN: AEROSOLS	yes
14.2		IMDG-Code: AEROSOLS	yes
14.2		ICAO-TI: Aerosols, flammable	yes
14.3	Class: 2 (gases) (aerosol)		yes
14.3	Subsidiary risk(s): 2.1 (flammability)		yes
14.3		ADR/RID/ADN: 2 (2.1)	yes
14.3		IMDG-Code: 2.1	yes
14.3		ICAO-TI: 2.1	yes
14.4	Packing group: not assigned to a packing group	Packing group: not assigned	yes
14.5	Environmental hazards: none (non-environmentally hazardous acc. to the dangerous goods regulations)	Environmental hazards: non-environmentally hazardous acc. to the dangerous goods regulations	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class:		yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class: 2.1		yes
14.7		Marine pollutant:	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: Aerosols, flammable		yes
14.7	Class: 2.1		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Danger label(s): change in the listing (table)	yes
15.1	Restrictions according to REACH, Annex XVII		yes
15.1		Restrictions according to REACH, Annex XVII: change in the listing (table)	yes
15.1	Directive 75/324/EEC relating to aerosol dispensers		yes
15.1	Classification of the gas/aerosol: extremely flammable		yes

Germany: en Page: 15 / 17

Replaces version of: 2020-01-17 (GHS 1)

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel evant
15.1	Labelling: keep out of reach of children pressurized container: may burst if heated keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking do not pierce or burn, even after use protect from sunlight. Do not expose to temper- atures exceeding 50 °C/122 °F		yes
15.1	Net contents by volume: 400 ml		yes
15.1		Maximum VOC content limit: change in the listing (table)	yes
15.1		VOC content: 651.9 ⁹ / _i	yes
15.1		Maximum VOC content limit: change in the listing (table)	yes
15.1		Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR): change in the listing (table)	yes
15.1		Pollutant release and transfer registers (PRTR): change in the listing (table)	yes
15.1	Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD): none of the ingredients are listed	Water Framework Directive (WFD)	yes
15.1		List of pollutants (WFD): change in the listing (table)	yes
15.1		Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013: This product is regulated by Regulation (EU) No 2019/1148: All suspicious transactions as well as the loss and theft of significant quantities must be reported to the competent authority.	yes
15.1		Explosives precursors which are subject to restrictions: change in the listing (table)	yes
15.1	Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)		yes
15.1	Storage class (LGK): 2 B (aerosol dispensers and lighters)		yes
15.1	National inventories		yes
15.1		National inventories: change in the listing (table)	yes
15.1		National inventories	yes
15.1		National inventories: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16	Key literature references and sources for data: - Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU - Regulation (EC) No. 1272/2008 (CLP, EU GHS)	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.Transport of dan- gerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dan- gerous Goods Regulations (DGR) for the air transport (IATA).	yes
16		List of relevant phrases (code and full text as stated in chapter 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr. Descriptions of used abbreviations.

2000/39/EC. Acute Tox. ADN.

Descriptions of used abbreviations.

Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC. Acute toxicity.

Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road).

European Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).

Workplace exposure limit.

Aspiration hazard.

Acute Toxicity Estimate.

Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).

Ceiling value.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.

Dangerous Goods Regulations (see IATA/DGR).

ADR.

ADR/RID/ADN. AGW. Asp. Tox. ATE. CAS. Ceiling-C. CLP. DFG.

weinneim. Dangerous Goods Regulations (see IATA/DGR). Derived No-Effect Level. DGR. DNEL.

Germany: en Page: 16 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354076 - PROMAT CHEMICALS ALUMINIUM-SPRAY HOCH-HITZEBESTÄNDIG - 400 ml

Version number: GHS 2.0 Revision: 2021-03-30 Replaces version of: 2020-01-17 (GHS 1)

Descriptions of used abbreviations. Abbr.

Descriptions of used abbreviations.

The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).

European Inventory of Existing Commercial Chemical Substances.

European List of Notified Chemical Su EC No.

EINECS. ELINCS. EmS. Eye Dam. Eye Irrit. Flam. Gas. Flam. Liq. Flam. Sol. GHS. IATA. IATA/DGR. ICAO-TI.

ICAO. ICAO-TI. IMDG. IMDG-Code. Index No. IOELV.

LGK. NLP.

PNEC.

Ppm. Press. Gas. REACH. RID.

Persistent, Bioaccumulative and Toxic.
Predicted No-Effect Concentration.
Parts per million.
Gas under pressure.
Registration, Evaluation, Authorisation and Restriction of Chemicals.
Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Corrosive to skin.

Skin Corr

Skin Corr. Skin Irrit. STEL. STOT SE. SVHC. TRGS.

Corrosive to skin.
Irritant to skin.
Short-term exposure limit.
Specific target organ toxicity - single exposure.
Substance of Very High Concern.
Technische Regeln für GefahrStoffe (technical rules for hazardous substances, Germany).
Abbeiten Jatzenspunger (TIRCS one)

Arbeitsplatzgrenzwerte (TRGS 900). Biologische Grenzwerte (TRGS 903). Time-weighted average. Volatile Organic Compounds. Very Persistent and very Bioaccumulative. TRGS 900. TRGS 903. TWA.

VPvB.

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Extremely flammable gas.
Extremely flammable aerosol.
Highly flammable liquid and vapour.
Flammable liquid and vapour.
Flammable solid.
Pressurised container: May burst if heated.
Contains gas under pressure; may explode if heated.
May be fatal if swallowed and enters airways.
Harmful in contact with skin.
Causes skin irritation. H222. H225.

H225. H226. H228. H229. H280. H304. H312. Causes skin irritation H319 Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Page: 17 / 17 Germany: en