

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Version number: GHS 13.2  
Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name** PROMAT CHEMICALS MARKING SPRAY - 500 ml  
**Unique formula identifier (UFI)** K360-30TS-J00X-T642

### Article number

4000 354080 (rot/rouge/rood/czerwony)  
4000 354081 (blau/bleu/blauw/niebieski)  
4000 354082 (grün/vert/groen/zielony)  
4000 354083 (weiß/blanc/wit/biały)  
4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty)  
4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy)  
4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony)  
4000 354087 (leuchtpink/rose lumineux/lichtroze/jaskrawo różowy)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses** General use  
Marking paint

### 1.3 Details of the supplier of the safety data sheet

NORDWEST Handel AG  
Robert-Schuman-Straße 17  
44263 Dortmund  
Germany

Telephone: +49 (0)231 2222-3001  
Telefax: +49 (0)231 2222-3099  
e-mail: sdb@nordwest.com  
Website: www.nordwest.com

**e-mail (competent person)** sdb@nordwest.com

### 1.4 Emergency telephone number

Austria: Vergiftungsinformationszentrale (VIZ) +43 (0)1 406 43 43  
Germany: Gemeinsamen Giftinformationszentrum (GGIZ) der +49-361-730730  
Laender Mecklenburg-Vorpommern, Sachsen,  
Sachsen-Anhalt und Thuringen c/o HELIOS  
Klinikum Erfurt  
Luxembourg: Poison Centre Luxembourg (+352) 8002 5500  
Switzerland: Tox Info Suisse +145, 24h oder +41 44 251 51 51

Poison centre			
Country	Name	Postal code/city	Telephone
Austria	Vergiftungsinformationszentrale (VIZ)		+43 (0)1 406 43 43
Germany	Gemeinsamen Giftinformationszentrum (GGIZ) der Laender Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thuringen c/o HELIOS Klinikum Erfurt	99089 Erfurt	+49-361-730730
Luxembourg	Poison Centre Luxembourg		(+352) 8002 5500
Switzerland	Tox Info Suisse		+145, 24h oder +41 44 251 51 51

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 (CLP)**

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.10	aspiration hazard	1	Asp. Tox. 1	H304
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

**The most important adverse physicochemical, human health and environmental effects**

Spillage and fire water can cause pollution of watercourses.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrwo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2  
Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

**Signal word** danger

**Pictograms**

GHS02, GHS07



### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Child-resistant fastening** yes

**Tactile warning of danger** yes

**Hazardous ingredients for labelling** ethyl acetate, Naphtha (petroleum), hydrotreated light, Naphtha (petroleum), hydro-treated heavy, 1-Methoxy-2-propylacetate

## 2.3 Other hazards

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
CAS No 106-97-8 EC No 203-448-7 Index No 601-004-00-0 REACH Reg. No 01-2119474691-32-xxxx	butane	25 - < 50	Flam. Gas 1B / H221 Press. Gas C / H280		C GHS-HC U(b)	
CAS No 74-98-6 EC No 200-827-9 Index No 601-003-00-5 REACH Reg. No 01-2119486944-21	propane	10 - < 25	Flam. Gas 1A / H220 Press. Gas L / H280		GHS-HC U(c)	

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)














4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrwo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
CAS No 141-78-6  EC No 205-500-4  Index No 607-022-00-5  REACH Reg. No 01-2119475103-46-xxxx	ethyl acetate	10 – < 25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 	GHS-HC IOELV	
CAS No 64742-49-0  EC No 265-151-9  Index No 649-328-00-1	Naphtha (petroleum), hydrotreated light	5 – < 10	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	   	P(b)	
CAS No 64742-48-9  EC No 927-241-2  Index No 649-327-00-6  REACH Reg. No 01-2119471843-32-xxxx	Naphtha (petroleum), hydrotreated heavy	1 – < 5	Flam. Liq. 3 / H226 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	  	P(b)	
CAS No 108-65-6  EC No 203-603-9  Index No 607-195-00-7  REACH Reg. No 01-2119475791-29-xxxx	1-Methoxy-2-propyl-acetate	1 – < 5	Flam. Liq. 3 / H226 STOT SE 3 / H336	 	IOELV	

## Notes

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

P(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 shall apply

U(b): The allocation to the group 'compressed gas' is based on the physical state in which the gas is packaged

U(c): The allocation to the group 'liquefied gas' is based on the physical state in which the gas is packaged

## Remarks

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

## Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

## 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, BC-powder

#### Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

#### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

##### Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

##### Packaging compatibilities

Keep only in original container.

##### Storage class (Lgk) TRGS 510

LGK 2 B (aerosol dispensers or lighters)

### 7.3 Specific end use(s)

See section 16 for a general overview.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2  
Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	1-methoxy-2-propyl acetate	108-65-6	MAK	50	270	50	270				DFG
DE	2-methoxy-1-methylethyl acetate	108-65-6	AGW	50	270	50	270			Y	TRGS 900
DE	ethyl acetate	141-78-6	MAK	200	750	400	1,500				DFG
DE	ethyl acetate	141-78-6	AGW	200	730	400	1,460			Y	TRGS 900
DE	Naphtha (petroleum), hydro-treated heavy	64742-48-9	MAK	50	300	100	600				DFG
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900
EU	2-methoxy-1-methylethyl acetate	108-65-6	IOELV	50	275	100	550			H	2000/39/EC
EU	ethyl acetate	141-78-6	IOELV	200	734	400	1,468				2017/164/EU

#### Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
H	absorbed through the skin
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
Y	a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ethyl acetate	141-78-6	DNEL	1,468 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
ethyl acetate	141-78-6	DNEL	1,468 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
ethyl acetate	141-78-6	DNEL	734 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
ethyl acetate	141-78-6	DNEL	63 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
ethyl acetate	141-78-6	DNEL	734 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Naphtha (petroleum), hydrotreated light	64742-49-0	DNEL	5,306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Naphtha (petroleum), hydrotreated light	64742-49-0	DNEL	13,964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Naphtha (petroleum), hydrotreated heavy	64742-48-9	DNEL	871 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Naphtha (petroleum), hydrotreated heavy	64742-48-9	DNEL	77 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2  
Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
1-Methoxy-2-propyl-acetate	108-65-6	DNEL	275 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
1-Methoxy-2-propyl-acetate	108-65-6	DNEL	550 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
1-Methoxy-2-propyl-acetate	108-65-6	DNEL	796 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
ethyl acetate	141-78-6	PNEC	0.24 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl acetate	141-78-6	PNEC	0.024 mg/l	aquatic organisms	marine water	short-term (single instance)
ethyl acetate	141-78-6	PNEC	650 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethyl acetate	141-78-6	PNEC	1.15 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethyl acetate	141-78-6	PNEC	0.115 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethyl acetate	141-78-6	PNEC	0.148 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl acetate	141-78-6	PNEC	1.65 mg/l	aquatic organisms	water	intermittent release
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	6.35 mg/l	aquatic organisms	water	intermittent release
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.635 mg/l	aquatic organisms	freshwater	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.064 mg/l	aquatic organisms	marine water	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	3.29 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.329 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.29 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)



Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

#### Eye/face protection

Use protective eyewear to guard against splash of liquids.

#### Skin protection

#### Hand protection

Wear protective gloves. (Splash protection)

#### Type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## **Breakthrough times of the glove material**

>480 minutes (permeation: level 6)

## **Other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

## **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

Full face mask/half mask/quarter mask (EN 136/140).

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White).

## **Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

<b>Physical state</b>	aerosol (spray aerosol)
<b>Colour</b>	acc. to product description
<b>Odour</b>	like solvents
<b>Melting point/freezing point</b>	not determined
<b>Boiling point or initial boiling point and boiling range</b>	-161.5 °C at 1,013 hPa
<b>Flammability</b>	flammable aerosol in accordance with GHS criteria
<b>Lower and upper explosion limit</b>	0.6 vol% - 15 vol%
<b>Flash point</b>	-88.6 °C at 1,013 hPa
<b>Auto-ignition temperature</b>	>200 °C (auto-ignition temperature (liquids and gases))
<b>Decomposition temperature</b>	not relevant
<b>pH (value)</b>	not determined
<b>Kinematic viscosity</b>	not relevant
<b>Solubility(ies)</b>	not determined

### **Partition coefficient**

Partition coefficient n-octanol/water (log value) this information is not available

Vapour pressure 4,200 hPa at 20 °C

### **Density and/or relative density**

Density 0.6834 – 0.6843 g/ml (calculated value)

Relative vapour density information on this property is not available

### **9.2 Other information**

**Information with regard to physical hazard classes** there is no additional information

### **Other safety characteristics**

Temperature class (EU, acc. to ATEX) T3 (maximum permissible surface temperature on the equipment: 200°C)

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

### **10.2 Chemical stability**

See below "Conditions to avoid".

### **10.3 Possibility of hazardous reactions**

No known hazardous reactions.

### **10.4 Conditions to avoid**

Do not spray on an open flame or other ignition source. Keep away from heat.

### **Hints to prevent fire or explosion**

Protect from sunlight.

### **10.5 Incompatible materials**

Oxidisers

### **10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2  
Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethyl acetate	141-78-6	EC50	2,306 mg/l	aquatic invertebrates	24 h
1-Methoxy-2-propylacetate	108-65-6	LC50	63.5 mg/l	fish	14 d
1-Methoxy-2-propylacetate	108-65-6	EC50	>100 mg/l	aquatic invertebrates	21 d

### 12.2 Persistence and degradability

Degradability of components						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
ethyl acetate	141-78-6	oxygen depletion	62 %	5 d		
Naphtha (petroleum), hydro-treated light	64742-49-0	oxygen depletion	83 %	10 d		ECHA
Naphtha (petroleum), hydro-treated heavy	64742-48-9	oxygen depletion	8 %	3 d		ECHA
Naphtha (petroleum), hydro-treated heavy	64742-48-9	carbon dioxide generation	0 %	3 d		ECHA
1-Methoxy-2-propylacetate	108-65-6	carbon dioxide generation	90 %	28 d		ECHA
1-Methoxy-2-pro-	108-65-6	oxygen depletion	60 %	5.9 d		ECHA



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

Degradability of components						
Name of sub-stance	CAS No	Process	Degradation rate	Time	Method	Source
pylacetate						
1-Methoxy-2-pro-pylacetate	108-65-6	DOC removal	99 %	28 d		ECHA

## 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
ethyl acetate	141-78-6	30	0.68 (pH value: 7, 25 °C)	
Naphtha (petroleum), hydrotreated light	64742-49-0	501.2	3.6 (pH value: 7, 20 °C)	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	≥6.91 – ≤1,582	≥1.99 – ≤5.25	
1-Methoxy-2-propylacetate	108-65-6		1.2 (pH value: 6.8, 20 °C)	

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0,1%.

## 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

## 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

#### List of wastes, (Recommendations)

#### Product residues

16 05 04\* Gases in pressure containers (including halons) containing hazardous substances

#### Packagings

15 01 04 Metallic packaging

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN UN 1950

IMDG-Code UN 1950

ICAO-TI UN 1950

### 14.2 UN proper shipping name

ADR/RID/ADN AEROSOLS

IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

- 14.3 Transport hazard class(es)**  
**ADR/RID/ADN** 2 (2.1)  
**IMDG-Code** 2.1  
**ICAO-TI** 2.1
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**  
Provisions for dangerous goods (ADR) should be complied within the premises.
- 14.7 Maritime transport in bulk according to IMO instruments**  
The cargo is not intended to be carried in bulk.

## Information for each of the UN Model Regulations

### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code 5F  
Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 1 L  
Transport category (TC) 2  
Tunnel restriction code (TRC) D

### International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant -  
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 1 L  
EmS F-D, S-U  
Stowage category -

### International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

##### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

##### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

##### Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

##### Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrwo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Replaces version of: 2023-05-15 (GHS 5)

Revision: 2024-11-12

## National regulations (Germany)

**Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)**

**Wassergefährdungsklasse, WGK (water hazard class)** 2 obviously hazardous to water

## Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m <sup>3</sup>	3)

## Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m<sup>3</sup>, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

## National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed

## Legend

REACH Reg. REACH registered substances

## 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Trade name: PROMAT CHEMICALS MARKING SPRAY - 500 ml - 500 ml	Trade name: PROMAT CHEMICALS MARKING SPRAY - 500 ml	yes

## Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations.
2000/39/EC. 2017/164/EU.	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC. Commission Directive establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).
ADR/RID/ADN.	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).
AGW.	Workplace exposure limit.
Aquatic Chronic.	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
Ceiling-C.	Ceiling value.
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD.	Chemical oxygen demand.
DFG.	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DGR.	Dangerous Goods Regulations (see IATA/DGR).
DNEL.	Derived No-Effect Level.
EC50.	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
ED.	Endocrine disruptor.
EINECS.	European Inventory of Existing Commercial Chemical Substances.
ELINCS.	European List of Notified Chemical Substances.
EmS.	Emergency Schedule.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
ICAO-TI.	Technical instructions for the safe transport of dangerous goods by air.
IMDG.	International Maritime Dangerous Goods Code.
IMDG-Code.	International Maritime Dangerous Goods Code.
Index No.	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008.
IOELV.	Indicative occupational exposure limit value.
LC50.	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval.
LGK.	Lagerklasse (storage class according to TRGS 510, Germany).

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354080 (rot/rouge/rood/czerwony) - 4000 354081 (blau/bleu/blauw/niebieski) - 4000 354082 (grün/vert/groen/zielony) - 4000 354083 (weiß/blanc/wit/biały) - 4000 354084 (leuchtgelb/jaune lumineux/lichtgeel/jaskrawo żółty) - 4000 354085 (leuchtorange/orange lumineux/lichtoranje/jaskrawo pomarańczowy) - 4000 354086 (leuchtrot/rouge lumineux/lichtrood/jaskrawo czerwony) - 4000 354087 (leuchtpink/rose lumineux/ lichtroze/jaskrawo różowy) - PROMAT CHEMICALS MARKING SPRAY - 500 ml

Version number: GHS 13.2

Revision: 2024-11-12

Replaces version of: 2023-05-15 (GHS 5)

Abbr.	Descriptions of used abbreviations.
Log KOW.	n-Octanol/water.
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Skin Corr.	Corrosive to skin.
Skin Irrit.	Irritant to skin.
STEL.	Short-term exposure limit.
STOT SE.	Specific target organ toxicity - single exposure.
SVHC.	Substance of Very High Concern.
TRGS.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 900.	Arbeitsplatzgrenzwerte (TRGS 900).
TWA.	Time-weighted average.
VPvB.	Very Persistent and very Bioaccumulative.

## Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## List of relevant phrases (code and full text as stated in section 2 and 3)

H220.	Extremely flammable gas.
H221.	Flammable gas.
H222.	Extremely flammable aerosol.
H225.	Highly flammable liquid and vapour.
H226.	Flammable liquid and vapour.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H304.	May be fatal if swallowed and enters airways.
H315.	Causes skin irritation.
H319.	Causes serious eye irritation.
H336.	May cause drowsiness or dizziness.
H411.	Toxic to aquatic life with long lasting effects.
H412.	Harmful to aquatic life with long lasting effects.

## Disclaimer

This SDS has been compiled and is solely intended for this product. This information is based on the present state of our knowledge and does not constitute an assurance of product properties nor establishes contract legal rights. All data about health and safety are only for information. They should therefore not be construed as specifications.