

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Version number: GHS 5.0  
Replaces version of: 2020-01-07 (GHS 4)

Revision: 2020-05-06

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name **KLEB-UND DICHTSTOFFENTFERNER - 400 ml**

Unique formula identifier (UFI)

Article number 4000 354120

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses  
general use  
paint remover  
cleaning agent

Uses advised against  
do not use for products which come into contact with foodstuffs

### 1.3 Details of the supplier of the safety data sheet

NORDWEST Handel AG  
Robert-Schuman-Straße 17  
44263 Dortmund  
Germany

Telephone: +49 (0)231 2222-3001

Telefax: +49 (0)231 2222-3099

Website: www.nordwest.com

e-Mail (competent person): sdb@nordwest.com

### 1.4 Emergency telephone number

Austria: Vergiftungsinformationszentrale der Gesundheit +43 1 406 43 43  
Germany: Beratungsstelle bei Vergiftungen Giftinformation- +49(0)6131 / 19240  
zentrale der Länder Rheinland-Pfalz und Hessen

Switzerland: Tox Info Suisse 145, 24h oder +41 44 251 51 51

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	Cat. 1	(Aerosol 1)	H222,H229
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336

#### Remarks

For full text of H-phrases: see SECTION 16.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word **danger**

#### Pictograms

GHS02, GHS07



H222  
H229  
H336

Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
May cause drowsiness or dizziness.

P101  
P102

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.

P210  
P211  
P251  
P261  
P271  
P280

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing spray.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/eye protection.

P304+P340  
P312  
P337+P313

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTRE/doctor if you feel unwell.  
If eye irritation persists: Get medical advice/attention.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

## Hazardous ingredients for labelling:

N-Butyl acetate.

### 2.3 Other hazards

Do not mix different cleaners.







### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Description of the mixture

Hazardous ingredients acc. to EU regulation				
Name of substance	Identifier	Wt%	Classification acc. to 1272/2008/EC	Pictograms
N-butyl acetate	CAS No 123-86-4  EC No 204-658-1  REACH Reg. No 01-2119485493-29-xxxx	50 – < 75	Flam. Liq. 3 / H226 STOT SE 3 / H336	 
butane	CAS No 106-97-8  EC No 203-448-7  REACH Reg. No 01-2119474691-32	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	 
Propan	CAS No 74-98-6  EC No 200-827-9  REACH Reg. No 01-2119486944-21	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	 

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water. Take off contaminated clothing.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

water spray, BC-powder

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Collect spillage (universal binder).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice

Observe instructions for use. Keep out of reach of children.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
DE	butane	106-97-8		AGW	1,000	2,400	4,000	9,600			TRGS 900
DE	1-butyl acetate	123-86-4		MAK	100	480	200	960			DFG
DE	n-butyl acetate	123-86-4	Y	AGW	62	300	124	600			TRGS 900
DE	propane	74-98-6		AGW	1,000	1,800	4,000	7,200			TRGS 900
EU	n-butyl acetate	123-86-4		IOEL V	50	241	150	723			2019/1831/EU

Notation

Ceiling-C  
STEL

ceiling value is a limit value above which exposure should not occur  
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Y

a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

#### Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
N-butyl acetate	123-86-4	DNEL	300 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
N-butyl acetate	123-86-4	DNEL	600 mg/m³	human, inhalatory	worker (industry)	acute - local effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
N-butyl acetate	123-86-4	DNEL	48 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	960 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects

• relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
N-butyl acetate	123-86-4	PNEC	0.18 mg/l	aquatic organisms	freshwater	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.018 mg/l	aquatic organisms	marine water	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.36 mg/l	aquatic organisms	water	intermittent release
N-butyl acetate	123-86-4	PNEC	35.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
N-butyl acetate	123-86-4	PNEC	0.981 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.098 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.09 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)



Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

#### • hand protection

Wear protective gloves. (Splash protection)

#### • type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection

Full face mask/half mask/quarter mask (EN 136/140)

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White)

### Environmental exposure controls

Use appropriate container to avoid environmental contamination.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state aerosol (spray aerosol)

Colour various

Odour characteristic

#### Other physical and chemical parameters

Melting point/freezing point -159.4 °C not applicable (aerosol)

Initial boiling point and boiling range not applicable (aerosol)

Flash point not applicable (aerosol)

Flammability (solid, gas) flammable aerosol in accordance with GHS criteria

Explosive limits

• lower explosion limit (LEL) 5 vol%

• upper explosion limit (UEL) 15 vol%

Vapour pressure 4,200 hPa at 20 °C

Density 0.7741 g/ml (calculated value)

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW) This information is not available.

Auto-ignition temperature 287 °C

Viscosity not relevant (aerosol)

Explosive properties none

Oxidising properties none

(En) Germany:

Version number: GHS 5.0:

Replaces version of: 2020-01-07: (GHS 4)

Page: 5 / 12:

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

**9.2 Other information** There is no additional information.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. - Keep away from heat.

#### Hints to prevent fire or explosion

Protect from sunlight.

#### Physical stresses which might result in a hazardous situation and have to be avoided

high temperatures

### 10.5 Incompatible materials

oxidisers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

#### • Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### • Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### Other information

Repeated exposure may cause skin dryness or cracking.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## SECTION 12: Ecological information

### 12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.

Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 1 (slightly hazardous to water)

#### Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
N-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
N-butyl acetate	123-86-4	EC50	18 mg/l	fish	96 h
N-butyl acetate	123-86-4	ErC50	392 mg/l	algae	48 h

#### Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
N-butyl acetate	123-86-4	EC50	34.2 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	LC50	43.5 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h

#### Biodegradation

The relevant substances of the mixture are readily biodegradable.

### 12.2 Persistence and degradability

#### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
N-butyl acetate	123-86-4	oxygen depletion	80 %	5 d

### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
N-butyl acetate	123-86-4		2.3 (pH value: 7, 25 °C)	
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.

#### Endocrine disrupting potential

None of the ingredients are listed.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

##### List of wastes

16 05 04\* gases in pressure containers (including halons) containing dangerous substances  
15 01 10\* packaging containing residues of or contaminated by dangerous substances

##### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

- |      |  |  |
|------|--|--|
| 14.1 | UN number  | 1950   |
| 14.2 | UN proper shipping name  | AEROSOLS   |
| 14.3 | Transport hazard class(es)   |  |
|      | Class  | 2 (gases) (aerosol)  |
|      | Subsidiary risk(s)   | 2.1 (flammability)   |
| 14.4 | Packing group  | not assigned to a packing group  |
| 14.5 | Environmental hazards  | none (non-environmentally hazardous acc. to the dangerous goods regulations) |
| 14.6 | Special precautions for user   |  |
|      | Provisions for dangerous goods (ADR) should be complied within the premises. |  |
| 14.7 | Transport in bulk according to Annex II of MARPOL and the IBC Code           |  |
|      | The cargo is not intended to be carried in bulk.                             |  |

#### Information for each of the UN Model Regulations

##### • Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1950
Proper shipping name	AEROSOLS
Class	2
Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

##### • International Maritime Dangerous Goods Code (IMDG)

UN number	1950
Proper shipping name	AEROSOLS
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## • International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1950  
Proper shipping name Aerosols, flammable  
Class 2.1  
Danger label(s) 2.1



Special provisions (SP) A145, A167  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

- Restrictions according to REACH, Annex XVII

Name acc. to inventory	CAS No	Restriction	No
flammable / pyrophoric		R40	40
flammable / pyrophoric		R40	40
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
flammable / pyrophoric		R40	40

#### Legend

R3

1. Shall not be used in:
  - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
  - tricks and jokes,
  - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
  - can be used as fuel in decorative oil lamps for supply to the general public, and,
  - present an aspiration hazard and are labelled with R65 or H304,
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
  - (a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
  - (b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
  - (c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.
7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

## Legend

R40

1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- 'whoopie' cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

- List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

- Directive 75/324/EEC relating to aerosol dispensers

## Classification of the gas/aerosol

extremely flammable

## Labelling

keep out of reach of children pressurized container: may burst if heated keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking do not pierce or burn, even after use protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

## Net contents by volume

400 ml

- Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)

## VOC content

100 % 774.1 g/l

Maximum VOC content limit			
Product category	Product subcategory	Coating	VOC g/l
vehicle refinishing products	preparatory and cleaning products	preparatory products	850

- Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

- Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

- Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

none of the ingredients are listed

Regulation 648/2004/EC on detergents

Labelling of contents	
Constituents	Weight % content (or range)
aliphatic hydrocarbons	15 % or over but less than 30 %

## National regulations (Germany)

- Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

## Wassergefährdungsklasse, WGK (water hazard class)

1 (slightly hazardous to water)

- Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m <sup>3</sup>	3)

## Notation

3)

a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m<sup>3</sup>, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

- Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK):

2 B (aerosol dispensers and lighters)

## National inventories

Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed

## Legend

REACH Reg. REACH registered substances

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Trade name: ZMYWACZ DO USUWANIA KLEJU I MATERIAŁÓW USZCZELNIAJĄCYCH - 400 ml	Trade name: KLEB-UND DICHTSTOFFENTFERNER - 400 ml	yes
1.1		Unique formula identifier (UFI):	yes
1.3	Details of the supplier of the safety data sheet: Nordwest Handel AG Robert-Schuman-Str. 17 44263 Dortmund Germany  Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com	Details of the supplier of the safety data sheet: NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany  Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

## Abbreviations and acronyms

2019/1831/EU.	Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road).
AGW.	Workplace exposure limit.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
Ceiling-C.	Ceiling value.
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
CMR.	Carcinogenic, Mutagenic or toxic for Reproduction.
COD.	Chemical oxygen demand.
DFG.	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DGR.	Dangerous Goods Regulations (see IATA/DGR).
DMEL.	Derived Minimal Effect Level.
DNEL.	Derived No-Effect Level.
EC50.	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EINECS.	European Inventory of Existing Commercial Chemical Substances.
ELINCS.	European List of Notified Chemical Substances.
Ems.	Emergency Schedule.
ErC50.	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
IMDG.	International Maritime Dangerous Goods Code.
IOELV.	Indicative occupational exposure limit value.
LC50.	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval.
LGK.	Lagerklasse (storage class according to TRGS 510, Germany).
Log KOW.	n-Octanol/water.
MARPOL.	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant").
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354120 - KLEB-UND DICHTSTOFFENTFERNER - 400 ml



Version number: GHS 5.0

Replaces version of: 2020-01-07 (GHS 4)

Date of compilation: 2020-05-06

RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
STEL.	Short-term exposure limit.
STOT SE.	Specific target organ toxicity - single exposure.
SVHC.	Substance of Very High Concern.
TRGS.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 900.	Arbeitsplatzgrenzwerte (TRGS 900).
TWA.	Time-weighted average.
VOC.	Volatile Organic Compounds.
VPvB.	Very Persistent and very Bioaccumulative.

## Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## List of relevant phrases (code and full text as stated in chapter 2 and 3)

H220.	Extremely flammable gas.
H222.	Extremely flammable aerosol.
H226.	Flammable liquid and vapour.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H336.	May cause drowsiness or dizziness.

## Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.