

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Revision: 2021-08-31

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name **PROMAT CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT 400 ml**  
Unique formula identifier (UFI) 2C80-80S3-H00T-028R  
Article number 4000 354200 (RAL 3000) SDM  
4000 354201 (RAL 5010) SDM  
4000 354202 (RAL 6005) SDM  
4000 354204 (RAL 9010) SDM  
4000 354205 (RAL 1021) SDM  
4000 354207 (RAL 3000) HG  
4000 354208 (RAL 5010) HG  
4000 354209 (RAL 6005) HG  
4000 354211 (RAL 9010) HG  
4000 354212 (RAL 1021) HG  
4000 354214 (RAL 6011) HG  
4000 354215 (RAL 7035) SDM

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use  
paint, coating and lacquer  
Uses advised against do not use for products which come into contact with foodstuffs

### 1.3 Details of the supplier of the safety data sheet

NORDWEST Handel AG  
Robert-Schuman-Straße 17  
44263 Dortmund  
Germany

Telephone: +49 (0)231 2222-3001  
Telefax: +49 (0)231 2222-3099  
Website: www.nordwest.com

e-Mail (competent person): sdb@nordwest.com

### 1.4 Emergency telephone number

Austria: Vergiftungsinformationszentrale der Gesundheit +43 1 406 43 43  
Germany: Beratungsstelle bei Vergiftungen Giftinformation- +49(0)6131 / 19240  
zentrale der Länder Rheinland-Pfalz und Hessen  
Switzerland: Tox Info Suisse +145, 24h oder +41 44 251 51 51

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	Cat. 1	(Aerosol 1)	H222,H229
3.3	serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336

#### Remarks

For full text of H-phrases: see SECTION 16.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word **danger**

Pictograms

GHS02, GHS07



H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.  
Additional labelling requirements  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.  
Hazardous ingredients for labelling:

Acetone. N-Butyl acetate. Ethyl acetate.

## 2.3 Other hazards

There is no additional information.











### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Description of the mixture

Hazardous ingredients acc. to EU regulation				
Name of substance	Identifier	Wt%	Classification acc. to 1272/2008/EC	Pictograms
butane	CAS No 106-97-8  EC No 203-448-7  REACH Reg. No 01-2119474691-32	25 – < 50	Flam. Gas 1 / H220 Press. Gas L / H280	 
acetone	CAS No 67-64-1  EC No 200-662-2  REACH Reg. No 01-2119471330-49	10 – < 25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 
N-butyl acetate	CAS No 123-86-4  EC No 204-658-1  REACH Reg. No 01-2119485493-29-xxxx	10 – < 25	Flam. Liq. 3 / H226 STOT SE 3 / H336	 
Propan	CAS No 74-98-6  EC No 200-827-9  REACH Reg. No 01-2119486944-21	5 – < 10	Flam. Gas 1 / H220 Press. Gas L / H280	 
ethyl acetate	CAS No 141-78-6  EC No 205-500-4  REACH Reg. No 01-2119475103-46-xxxx	1 – < 5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Hazardous ingredients acc. to EU regulation				
Name of substance	Identifier	Wt%	Classification acc. to 1272/2008/EC	Pictograms
Titanium dioxide	CAS No 13463-67-7  EC No 236-675-5  REACH Reg. No 01-2119489379-17-xxxx	1 – < 5	Carc. 2 / H351	
isobutane	CAS No 75-28-5  EC No 200-857-2  REACH Reg. No 01-2119485395-27	1 – < 5	Flam. Gas 1 / H220 Press. Gas L / H280	 

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water. Take off contaminated clothing.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

water spray, BC-powder

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Collect spillage (universal binder).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice

Observe instructions for use. Keep out of reach of children.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Source
DE	butane	106-97-8		AGW	1,000	2,400	4,000	9,600			TRGS 900
DE	1-butyl acetate	123-86-4		MAK	100	480	200	960			DFG
DE	n-butyl acetate	123-86-4	Y	AGW	62	300	124	600			TRGS 900

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Country	Name of agent	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
DE	titanium dioxide	13463-67-7	r, multi-density	MAK		0.3		2.4			DFG
DE	ethyl acetate	141-78-6		MAK	200	750	400	1,500			DFG
DE	ethyl acetate	141-78-6	Y	AGW	200	730	400	1,460			TRGS 900
DE	acetone	67-64-1	Y	AGW	500	1,200	1,000	2,400			TRGS 900
DE	propane	74-98-6		AGW	1,000	1,800	4,000	7,200			TRGS 900
DE	isobutane	75-28-5		AGW	1,000	2,400	4,000	9,600			TRGS 900
DE	silica, amorphous	7631-86-9	i, DE-AGW-2, Y	AGW		4					TRGS 900
DE	silica, amorphous	7631-86-9	i	MAK		4					DFG
EU	n-butyl acetate	123-86-4		IOELV	50	241	150	723			2019/1831/EU
EU	ethyl acetate	141-78-6		IOELV	200	734	400	1,468			2017/164/EU
EU	acetone	67-64-1		IOELV	500	1,210					2000/39/EC

## Notation

### Ceiling-C

ceiling value is a limit value above which exposure should not occur  
Colloidal amorphous silica (7631-86-9) including fumed silica and produced in wet process silica (precipitated silica, silica gel).

### i

inhalable fraction

### multi-density

multiplied by the material density

### r

respirable fraction

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Y a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

## Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	Aceton	Aceton		BAT	50 mg/l	DFG
DE	Aceton	Aceton		BAT (BAR)	2.5 mg/l	DFG
DE	acetone	acetone		BLV	80 mg/l	TRGS 903

## Relevant DNELs/DMELs/PNECs and other threshold levels

- relevant DNELs of components of the mixture

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
 4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
 4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
 354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
 CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
 Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
acetone	67-64-1	DNEL	2,420 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
N-butyl acetate	123-86-4	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
N-butyl acetate	123-86-4	DNEL	48 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
N-butyl acetate	123-86-4	DNEL	960 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
ethyl acetate	141-78-6	DNEL	1,468 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
ethyl acetate	141-78-6	DNEL	1,468 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
ethyl acetate	141-78-6	DNEL	734 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
ethyl acetate	141-78-6	DNEL	63 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
ethyl acetate	141-78-6	DNEL	734 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
titanium dioxide	13463-67-7	DNEL	10 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects

• relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
acetone	67-64-1	PNEC	21 mg/l	aquatic organisms	water	intermittent release
N-butyl acetate	123-86-4	PNEC	0.18 mg/l	aquatic organisms	freshwater	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.018 mg/l	aquatic organisms	marine water	short-term (single instance)
N-butyl acetate	123-86-4	PNEC	0.36 mg/l	aquatic organisms	water	intermittent release
N-butyl acetate	123-86-4	PNEC	35.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
N-butyl acetate	123-86-4	PNEC	0.981 mg/kg	aquatic organisms	freshwater sedi- ment	short-term (single in- stance)
N-butyl acetate	123-86-4	PNEC	0.098 mg/kg	aquatic organisms	marine sediment	short-term (single in- stance)
N-butyl acetate	123-86-4	PNEC	0.09 mg/kg	terrestrial organisms	soil	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	0.24 mg/l	aquatic organisms	freshwater	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	0.024 mg/l	aquatic organisms	marine water	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	650 mg/l	aquatic organisms	sewage treat- ment plant (STP)	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	1.15 mg/kg	aquatic organisms	freshwater sedi- ment	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	0.115 mg/kg	aquatic organisms	marine sediment	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	0.148 mg/kg	terrestrial organisms	soil	short-term (single in- stance)
ethyl acetate	141-78-6	PNEC	1.65 mg/l	aquatic organisms	water	intermittent release
titanium dioxide	13463-67-7	PNEC	0.184 mg/l	aquatic organisms	freshwater	short-term (single in- stance)
titanium dioxide	13463-67-7	PNEC	0.0184 mg/l	aquatic organisms	marine water	short-term (single in- stance)
titanium dioxide	13463-67-7	PNEC	100 mg/l	aquatic organisms	sewage treat- ment plant (STP)	short-term (single in- stance)
titanium dioxide	13463-67-7	PNEC	1,000 mg/kg	aquatic organisms	freshwater sedi- ment	short-term (single in- stance)
titanium dioxide	13463-67-7	PNEC	100 mg/kg	aquatic organisms	marine sediment	short-term (single in- stance)
titanium dioxide	13463-67-7	PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single in- stance)
titanium dioxide	13463-67-7	PNEC	0.193 mg/l	aquatic organisms	water	intermittent release

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)



Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

#### • hand protection

Wear protective gloves. (Splash protection)

#### • type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## • breakthrough times of the glove material

>480 minutes (permeation: level 6)

## • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection

Full face mask/half mask/quarter mask (EN 136/140)

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White)

## Environmental exposure controls

Use appropriate container to avoid environmental contamination.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state aerosol (spray aerosol)  
Colour acc. to product description  
Odour characteristic

#### Other physical and chemical parameters

Melting point/freezing point not applicable (aerosol)  
Initial boiling point and boiling range not applicable (aerosol)  
Flash point not applicable (aerosol)  
Flammability (solid, gas) flammable aerosol in accordance with GHS criteria  
Explosive limits  
• lower explosion limit (LEL) 2.2 vol%  
• upper explosion limit (UEL) 15 vol%  
Vapour pressure 4,200 hPa at 20 °C  
Density 0.7708 g/ml (calculated value)  
Solubility(ies) not determined  
Partition coefficient  
n-octanol/water (log KOW) This information is not available.  
Auto-ignition temperature 287 °C (auto-ignition temperature (liquids and gases))  
Viscosity not relevant (aerosol)  
Explosive properties none  
Oxidising properties none

### 9.2 Other information

There is no additional information.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. - Keep away from heat.

#### Hints to prevent fire or explosion

Protect from sunlight.

#### Physical stresses which might result in a hazardous situation and have to be avoided

high temperatures

### 10.5 Incompatible materials

oxidisers



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

#### • Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
acetone	67-64-1	oral	LD50	5,800 mg/kg	rat
ethyl acetate	141-78-6	dermal	LD50	>20,000 mg/kg	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

#### • Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### • Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### Other information

Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological information

### 12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.

Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 1 (slightly hazardous to water)

#### Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
acetone	67-64-1	LC50	8,120 mg/l	fish	96 h
N-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
N-butyl acetate	123-86-4	EC50	18 mg/l	fish	96 h
N-butyl acetate	123-86-4	ErC50	392 mg/l	algae	48 h
ethyl acetate	141-78-6	LC50	230 mg/l	fish	96 h
ethyl acetate	141-78-6	EC50	220 mg/l	fish	96 h

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
titanium dioxide	13463-67-7	LC50	>1,000 mg/l	fish	96 h
titanium dioxide	13463-67-7	EC50	>100 mg/l	aquatic invertebrates	48 h
titanium dioxide	13463-67-7	ErC50	>50 mg/l	algae	72 h

## Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
acetone	67-64-1	EC50	61.15 g/l	microorganisms	30 min
N-butyl acetate	123-86-4	EC50	34.2 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	LC50	43.5 mg/l	aquatic invertebrates	21 d
N-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h
ethyl acetate	141-78-6	EC50	2,306 mg/l	aquatic invertebrates	24 h
titanium dioxide	13463-67-7	LC50	>20,000 mg/l	aquatic invertebrates	24 h
titanium dioxide	13463-67-7	ErC50	>50 mg/l	algae	72 d
titanium dioxide	13463-67-7	EC50	>100 mg/l	microorganisms	15 min

## 12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
acetone	67-64-1	carbon dioxide generation	90.9 %	28 d
N-butyl acetate	123-86-4	oxygen depletion	80 %	5 d
ethyl acetate	141-78-6	oxygen depletion	62 %	5 d

## 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
acetone	67-64-1		-0.24	
N-butyl acetate	123-86-4		2.3 (pH value: 7, 25 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
ethyl acetate	141-78-6	30	0.68 (pH value: 7, 25 °C)	
isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

Data are not available.

## 12.6 Other adverse effects

Data are not available.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## Endocrine disrupting potential

None of the ingredients are listed.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

##### List of wastes

16 05 04\* gases in pressure containers (including halons) containing hazardous substances  
15 01 10\* packaging containing residues of or contaminated by hazardous substances

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

- |             |  |  |
|-------------|--|--|
| <b>14.1</b> | UN number  | <b>1950</b>  |
| <b>14.2</b> | UN proper shipping name  | <b>AEROSOLS</b>  |
| <b>14.3</b> | Transport hazard class(es)   |  |
|             | Class  | 2 (gases) (aerosol)  |
|             | Subsidiary risk(s)   | 2.1 (flammability)   |
| <b>14.4</b> | Packing group  | not assigned to a packing group  |
| <b>14.5</b> | Environmental hazards  | none (non-environmentally hazardous acc. to the dangerous goods regulations) |
| <b>14.6</b> | Special precautions for user   |  |
|             | Provisions for dangerous goods (ADR) should be complied within the premises. |  |
| <b>14.7</b> | Transport in bulk according to Annex II of MARPOL and the IBC Code           |  |
|             | The cargo is not intended to be carried in bulk.                             |  |

#### Information for each of the UN Model Regulations

##### • Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1950
Proper shipping name	AEROSOLS
Class	2
Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

##### • International Maritime Dangerous Goods Code (IMDG)

UN number	1950
Proper shipping name	AEROSOLS
Class	2.1
Danger label(s)	2.1



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Special provisions (SP) 63, 190, 277, 327, 344, 381, 959  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 1 L  
EmS F-D, S-U  
Stowage category -  
• **International Civil Aviation Organization (ICAO-IATA/DGR)**  
UN number 1950  
Proper shipping name Aerosols, flammable  
Class 2.1  
Danger label(s) 2.1



Special provisions (SP) A145, A167  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

- Restrictions according to REACH, Annex XVII

Name acc. to inventory	CAS No	Restriction	No
flammable / pyrophoric		R40	40
flammable / pyrophoric		R40	40
flammable / pyrophoric		R40	40
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
flammable / pyrophoric		R40	40
substances in tattoo inks and permanent make-up		R75	75
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
flammable / pyrophoric		R40	40
substances in tattoo inks and permanent make-up		R75	75
substances in tattoo inks and permanent make-up		R75	75
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
flammable / pyrophoric		R40	40

#### Legend

R3

1. Shall not be used in:
  - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
  - tricks and jokes,
  - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
  - can be used as fuel in decorative oil lamps for supply to the general public, and
  - present an aspiration hazard and are labelled with H304.
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## Legend

- R40
- (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
- (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
- (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
- metallic glitter intended mainly for decoration,
  - artificial snow and frost,
  - 'whoopie' cushions,
  - silly string aerosols,
  - imitation excrement,
  - horns for parties,
  - decorative flakes and foams,
  - artificial cobwebs,
  - stink bombs.
2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
- 'For professional users only'.
3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## Legend

R75

1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:  
(a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;  
(b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;  
(c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;  
(d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:  
(i) 0,1 % by weight, if the substance is used solely as a pH regulator;  
(ii) 0,01 % by weight, in all other cases;  
(e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (\*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;  
(f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:  
(i) "Rinse-off products";  
(ii) "Not to be used in products applied on mucous membranes";  
(iii) "Not to be used in eye products";  
(g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;  
(h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.  
2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.  
3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.  
4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:  
(a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);  
(b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).  
5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.  
6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.  
7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:  
(a) the statement "Mixture for use in tattoos or permanent make-up";  
(b) a reference number to uniquely identify the batch;  
(c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;  
(d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;  
(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;  
(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;  
(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.  
The information shall be clearly visible, easily legible and marked in a way that is indelible.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## Legend

The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.  
Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

- List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

- Directive 75/324/EEC relating to aerosol dispensers

## Classification of the gas/aerosol

extremely flammable

## Labelling

keep out of reach of children pressurized container: may burst if heated keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking do not pierce or burn, even after use protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

## Net contents by volume

400 ml

- Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)

VOC content 81.08 % 625 g/l

Maximum VOC content limit			
Product category	Product subcategory	Coating	VOC g/l
vehicle refinishing products	special finishes	all types	840

- Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

- Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

- Water Framework Directive (WFD)

Name of substance	CAS No	Listed in	Remarks
titanium dioxide		A)	
titanium dioxide		A)	

## Legend

A) Indicative list of the main pollutants

- Explosives precursors which are subject to restrictions

Name of substance	CAS No	Type of registration	Remarks	Limit value	Upper limit value for the purpose of licensing under Article 5(3)
acetone	67-64-1	Annex II			

## Legend

annex II Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## National regulations (Germany)

• Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

**Wassergefährdungsklasse, WGK (water hazard class)** 1 (slightly hazardous to water)

• Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m <sup>3</sup>	3)

### Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m<sup>3</sup>, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

• Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK): 2 B (aerosol dispensers and lighters)

## National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed

### Legend

REACH Reg. REACH registered substances

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Unique formula identifier (UFI): 2C80-80S3-H00T-028R		yes
1.1		Unique formula identifier (UFI): 2C80-80S3-H00T-028R	yes
1.2		Uses advised against: do not use for products which come into contact with foodstuffs	yes
1.3	Details of the supplier of the safety data sheet: NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany  Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 e-mail: sdb@nordwest.com Website: www.nordwest.com	Details of the supplier of the safety data sheet: NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany  Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com	yes
1.3	e-mail (competent person): sdb@nordwest.com		yes
1.3		e-Mail (competent person): sdb@nordwest.com	yes
1.4		Emergency telephone number: change in the listing (table)	yes
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
 4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
 4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
 354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
 CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
 Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Remarks: For full text of H-phrases: see SECTION 16.	yes
2.1		Supplemental hazard information	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Precautionary statements: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Additional labelling requirements	yes
2.3	Other hazards: of no significance	Other hazards: There is no additional information.	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes
3.1	Substances: Not relevant (mixture)		yes
3.2		Description of the mixture: change in the listing (table)	yes
3.2		Hazardous ingredients acc. to EU regulation: change in the listing (table)	yes
4.1	Following skin contact: Wash with plenty of soap and water.	Following skin contact: Wash with plenty of soap and water. Take off contaminated clothing.	yes
4.1	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.	yes
6.3		Advice on how to clean up a spill: Collect spillage (universal binder).	yes
7.2		Incompatible substances or mixtures: Observe hints for combined storage.	yes
7.2		Consideration of other advice: Observe instructions for use. Keep out of reach of children.	yes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
 4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
 4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
 354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
 CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
 Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
7.2	Packaging compatibilities: Keep only in original container.	• Packaging compatibilities: Only packagings which are approved (e.g. acc. to ADR) may be used.	yes
7.2	Storage class (LGK) TRGS 510: LGK 2 B (aerosol dispensers and lighters)		yes
8.1		National limit values	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits)	yes
8.1		Biological limit values	yes
8.1		Biological limit values: change in the listing (table)	yes
8.1		Relevant DNELs/DMELs/PNECs and other threshold levels	yes
8.1		• relevant DNELs of components of the mixture	yes
8.1		• relevant PNECs of components of the mixture	yes
8.2	Individual protection measures (personal protective equipment): eye protection must be worn safety gloves must be worn do not eat or drink Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.	Individual protection measures (personal protective equipment): eye protection must be worn safety gloves must be worn do not eat or drink	yes
8.2	Environmental exposure controls: Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.	Environmental exposure controls: Use appropriate container to avoid environmental contamination.	yes
9.1		Appearance	yes
9.1		Odour: characteristic	yes
9.1		Other physical and chemical parameters	yes
9.1	Melting point/freezing point: not determined	Melting point/freezing point: not applicable (aerosol)	yes
9.1	Decomposition temperature: not relevant		yes
9.1	pH (value): not applicable (aerosol)		yes
9.1	Kinematic viscosity: not relevant		yes
9.1	Lower and upper explosion limit: 2.2 vol% - 15 vol%	Explosive limits	yes
9.1		• lower explosion limit (LEL): 2.2 vol%	yes
9.1		• upper explosion limit (UEL): 15 vol%	yes
9.1	Density and/or relative density		yes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
 4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
 4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
 354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
 CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
 Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
9.1	Relative vapour density: information on this property is not available not relevant (aerosol)		yes
9.1		Partition coefficient	yes
9.1		n-octanol/water (log KOW): This information is not available.	yes
9.1		Auto-ignition temperature: 287 °C (auto-ignition temperature (liquids and gases))	yes
9.1		Viscosity: not relevant (aerosol)	yes
9.1		Explosive properties: none	yes
9.1		Oxidising properties: none	yes
9.2	Other information	Other information: There is no additional information.	yes
9.2	Information with regard to physical hazard classes: there is no additional information		yes
9.2	Other safety characteristics		yes
9.2	Temperature class (EU, acc. to ATEX): T3 (maximum permissible surface temperature on the equipment: 200°C)		yes
9.2	Odour: characteristic		yes
10.4		Physical stresses which might result in a hazardous situation and have to be avoided: high temperatures	yes
11.1		• Acute toxicity of components of the mixture	yes
11.1		• Acute toxicity of components of the mixture: change in the listing (table)	yes
11.1	Germ cell mutagenicity: Shall not be classified as germ cell mutagenic.		yes
11.1	Carcinogenicity: Shall not be classified as carcinogenic.		yes
11.1	Reproductive toxicity: Shall not be classified as a reproductive toxicant.		yes
11.1		Summary of evaluation of the CMR properties: Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.	yes
11.1		Specific target organ toxicity (STOT)	yes
11.2	Information on other hazards: There is no additional information.		yes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
 4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
 4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
 354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
 CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
 Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
12.1	Toxicity: Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)	Toxicity: acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment. Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 1 (slightly hazardous to water)	yes
12.1		Aquatic toxicity (acute)	yes
12.1		Aquatic toxicity (acute) of components of the mixture	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.2	Persistence and degradability: Data are not available.	Persistence and degradability	yes
12.2		Degradability of components of the mixture	yes
12.2		Degradability of components of the mixture: change in the listing (table)	yes
12.3		Bioaccumulative potential of components of the mixture	yes
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)	yes
13.1	List of wastes, (Recommendations)	List of wastes: 16 05 04* gases in pressure containers (including halons) containing hazardous substances 15 01 10* packaging containing residues of or contaminated by hazardous substances	yes
13.1	Product: 08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances		yes
13.1	Product residues: 16 05 04* Gases in pressure containers (including halons) containing hazardous substances		yes
13.1	Packagings: 15 01 04 Metallic packaging		yes
14.1	UN number or ID number	UN number: 1950	yes
14.1	ADR/RID/ADN: UN 1950		yes
14.1	IMDG-Code: UN 1950		yes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.1	ICAO-TI: UN 1950		yes
14.2	ADR/RID/ADN: AEROSOLS		yes
14.2	IMDG-Code: AEROSOLS		yes
14.2	ICAO-TI: Aerosols, flammable		yes
14.3	ADR/RID/ADN: 2 (2.1)		yes
14.3	IMDG-Code: 2.1		yes
14.3	ICAO-TI: 2.1		yes
14.2	UN proper shipping name	UN proper shipping name: AEROSOLS	yes
14.3		Class: 2 (gases) (aerosol)	yes
14.3		Subsidiary risk(s): 2.1 (flammability)	yes
14.4	Packing group: not assigned	Packing group: not assigned to a packing group	yes
14.5	Environmental hazards: non-environmentally hazardous acc. to the dan- gerous goods regulations	Environmental hazards: none (non-environmentally hazardous acc. to the dangerous goods regulations)	yes
14.7		UN number: 1950	yes
14.7		Proper shipping name: AEROSOLS	yes
14.7		Class: 2	yes
14.7	Marine pollutant: -		yes
14.7		UN number: 1950	yes
14.7		Proper shipping name: AEROSOLS	yes
14.7		Class: 2.1	yes
14.7		UN number: 1950	yes
14.7		Proper shipping name: Aerosols, flammable	yes
14.7		Class: 2.1	yes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
 4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
 4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
 354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
 CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
 Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7		Danger label(s): change in the listing (table)	yes
14.7		Danger label(s): change in the listing (table)	yes
15.1		• Restrictions according to REACH, Annex XVII	yes
15.1		• Restrictions according to REACH, Annex XVII: change in the listing (table)	yes
15.1		• Directive 75/324/EEC relating to aerosol dispensers	yes
15.1		Classification of the gas/aerosol: extremely flammable	yes
15.1		Labelling: keep out of reach of children pressurized container: may burst if heated keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking do not pierce or burn, even after use protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F	yes
15.1		Net contents by volume: 400 ml	yes
15.1	VOC content: 625 g/l		yes
15.1		Maximum VOC content limit: change in the listing (table)	yes
15.1		VOC content: 81.08 % 625 g/l	yes
15.1		Maximum VOC content limit: change in the listing (table)	yes
15.1	Regulation on the marketing and use of explosives precursors: This product is regulated by Regulation (EU) No 2019/1148: All suspicious transactions as well as the loss and theft of significant quantities must be reported to the competent authority.	• Explosives precursors which are subject to restrictions	yes
15.1	Regulation on persistent organic pollutants (POP): None of the ingredients are listed.		yes
15.1	National inventories		yes
15.1		National inventories: change in the listing (table)	yes
15.1		• Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)	yes
15.1		Storage class (LGK): 2 B (aerosol dispensers and lighters)	yes
15.1		National inventories	yes
15.1		National inventories: change in the listing (table)	yes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
16		Abbreviations and acronyms: change in the listing (table)	yes
16	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU. Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	Key literature references and sources for data: - Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU - Regulation (EC) No. 1272/2008 (CLP, EU GHS)	yes

## Abbreviations and acronyms

2000/39/EC. 2017/164/EU.	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC.
2019/1831/EU.	Commission Directive establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU.
ADN.	Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.
ADR.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
AGW.	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).
BCF.	Workplace exposure limit.
BOD.	Bioconcentration factor.
Carc.	Biochemical Oxygen Demand.
CAS.	Carcinogenicity.
Ceiling-C.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
CLP.	Ceiling value.
CMR.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD.	Carcinogenic, Mutagenic or toxic for Reproduction.
DFG.	Chemical oxygen demand.
DGR.	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DMEL.	Dangerous Goods Regulations (see IATA/DGR).
DNEL.	Derived Minimal Effect Level.
EC50.	Derived No-Effect Level.
EC No.	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval.
EINECS.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
ELINCS.	European Inventory of Existing Commercial Chemical Substances.
Ems.	European List of Notified Chemical Substances.
ErC50.	Emergency Schedule.
Eye Dam.	ErC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control.
Eye Irrit.	Seriously damaging to the eye.
Flam. Gas.	Irritant to the eye.
Flam. Liq.	Flammable gas.
GHS.	Flammable liquid.
IATA.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA/DGR.	International Air Transport Association.
ICAO.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
IMDG.	International Civil Aviation Organization.
IOELV.	International Maritime Dangerous Goods Code.
LC50.	Indicative occupational exposure limit value.
LD50.	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval.
LGK.	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval.
Log KOW.	Lagerklasse (storage class according to TRGS 510, Germany).
MARPOL.	n-Octanol/water.
NLP.	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant").
PBT.	No-Longer Polymer.
PNEC.	Persistent, Bioaccumulative and Toxic.
Ppm.	Predicted No-Effect Concentration.
Press. Gas.	Parts per million.
REACH.	Gas under pressure.
RID.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
STEL.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
STOT SE.	Short-term exposure limit.
SVHC.	Specific target organ toxicity - single exposure.
TRGS.	Substance of Very High Concern.
TRGS 900.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 903.	Arbeitsplatzgrenzwerte (TRGS 900).
TWA.	Biologische Grenzwerte (TRGS 903).
VOC.	Time-weighted average.
VPvB.	Volatile Organic Compounds.
	Very Persistent and very Bioaccumulative.

## Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

## Classification procedure

Physical and chemical properties: The classification is based on tested mixture.  
Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354200 (RAL 3000) SDM - 4000 354201 (RAL 5010) SDM - 4000 354202 (RAL 6005) SDM -  
4000 354204 (RAL 9010) SDM - 4000 354205 (RAL 1021) SDM - 4000 354207 (RAL 3000) HG -  
4000 354208 (RAL 5010) HG - 4000 354209 (RAL 6005) HG - 4000 354211 (RAL 9010) HG - 4000  
354212 (RAL 1021) HG - 4000 354214 (RAL 6011) HG - 4000 354215 (RAL 7035) SDM - PROMAT  
CHEMICALS COLOR-SPRAY GLÄNZEND /SEIDENMATT - 400 ml

Version number: GHS 4.0  
Replaces version of: 2021-06-08 (GHS 3)

Date of compilation: 2021-08-31

## List of relevant phrases (code and full text as stated in chapter 2 and 3)

H220.	Extremely flammable gas.
H222.	Extremely flammable aerosol.
H225.	Highly flammable liquid and vapour.
H226.	Flammable liquid and vapour.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H319.	Causes serious eye irritation.
H336.	May cause drowsiness or dizziness.
H351.	Suspected of causing cancer.

## Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.