according to Regulation (EC) No. 1907/2006 (REACH)



Date of compilation: 2018-12-19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name NASSENTWICKLER - 500 ml

Article number 4000 354551

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use

Uses advised against do not use for products which come into contact with the food

1.3 Details of the supplier of the safety data sheet

> Nordwest Handel AG Robert-Schuman-Str. 17 44263 Dortmund Germany

Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com e-Mail (competent person):

sdb@nordwest.com

1.4 **Emergency telephone number**

> Austria: Vergiftungsinformationszentrale der Gesundheit +43 1 406 43 43 Beratungsstelle bei VergiftungenGiftinformation-szentrale der Länder Rheinland-Pfalz und Hessen +49(0)6131 / 19240 Germanv:

Switzerland: Tox Info Suisse 145, 24h oder +41 44 251 51 51

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	Cat. 1	(Aerosol 1)	H222,H229
3.3	serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336

Remarks

For full text of H-phrases: see SECTION 16.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.2 **Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Danger Signal word

Pictograms

GHS02, GHS07





H222 H229

Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261

P264

Avoid breathing spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. P271 Wear protective gloves/eye protection. P280

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. P312

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazardous ingredients for labelling:

Acetone. Propan-2-ol.

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc	c. to EU regulation			
Name of substance	Identifier	Wt%	Classification acc. to 1272/ 2008/EC	Picto- grams
butane	CAS No 106-97-8	25 - < 50	Flam. Gas 1 / H220 Press. Gas L / H280	&
	EC No 203-448-7			
	REACH Reg. No 01-2119474691-32			
Propan	CAS No 74-98-6	25 - < 50	Flam. Gas 1 / H220 Press. Gas L / H280	®
	EC No 200-827-9			
	REACH Reg. No 01-2119486944-21			
acetone	CAS No 67-64-1	10 - < 25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	⋄
	EC No 200-662-2		STOT SE 3 / H336	
	REACH Reg. No 01-2119471330-49			
2-propanol	CAS No 67-63-0	10 - < 25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	
	EC No 200-661-7		SIUI SE 3 / H330	
	REACH Reg. No 01-2119457558-25			

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water. Take off contaminated clothing.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder

Unsuitable extinguishing media

water iet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Collect spillage (universal binder).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

· Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

· Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

Observe instructions for use. Keep out of reach of children.

• Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

according to Regulation (EC) No. 1907/2006 (REACH) 4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun	Name of agent	CAS No	Nota tion	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Sourc e
DE	butane	106-97-8		AGW	1,000	2,400	4,000	9,600			TRGS 900
DE	propan-2-ol	67-63-0		AGW	200	500	400	1,000			TRGS 900
DE	acetone	67-64-1		AGW	500	1,200	1,000	2,400			TRGS 900
DE	propane	74-98-6		AGW	1,000	1,800	4,000	7,200			TRGS 900
EU	acetone	67-64-1		IOEL V	500	1,210					2017/ 2398/ EU

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 **TWA**

hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source
DE	propan-2-ol	acetone		BLV	25 mg/l	TRGS 903
DE	propan-2-ol	acetone		BLV	25 mg/l	TRGS 903
DE	acetone	acetone		BLV	80 mg/l	TRGS 903

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
acetone	67-64-1	DNEL	2,420 mg/m ³	human, inhalatory	worker (in- dustry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg	human, dermal	worker (in- dustry)	chronic - systemic ef- fects
acetone	67-64-1	DNEL	1,210 mg/m ³	human, inhalatory	worker (in- dustry)	chronic - systemic ef- fects
propan-2-ol	67-63-0	DNEL	1,723 mg/m³	human, inhalatory	worker (in- dustry)	acute - systemic ef- fects
propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (in- dustry)	chronic - systemic ef- fects
propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (in- dustry)	chronic - systemic ef- fects

according to Regulation (EC) No. 1907/2006 (REACH) 4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

• relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environment- al compart- ment	Exposure time
acetone	67-64-1	PNEC	10.6 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
acetone	67-64-1	PNEC	1.06 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
acetone	67-64-1	PNEC	100 ^{mg} / _l	aquatic organisms	sewage treat- ment plant (STP)	short-term (single in- stance)
acetone	67-64-1	PNEC	30.4 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
acetone	67-64-1	PNEC	3.04 ^{mg} / _{kg}	aquatic organisms	marine sedi- ment	short-term (single in- stance)
acetone	67-64-1	PNEC	29.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)
acetone	67-64-1	PNEC	21 ^{mg} / _l	aquatic organisms	water	intermittent release
propan-2-ol	67-63-0	PNEC	140.9 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	140.9 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	2,251 ^{mg} / _l	aquatic organisms	sewage treat- ment plant (STP)	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organisms	marine sedi- ment	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	160 ^{mg} / _{kg}	aquatic organisms	water	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	28 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)
propan-2-ol	67-63-0	PNEC	140.9 ^{mg} / _l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)



Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

hand protection

Wear protective gloves. (Splash protection)

• type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection

Full face mask/half mask/quarter mask (EN 136/140)

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White)

Environmental exposure controls

Use appropriate container to avoid environmental contamination.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state aerosol (spray aerosol)

Colour whitish
Odour characteristic

Other physical and chemical parameters

Melting point/freezing point not applicable (aerosol)
Initial boiling point and boiling range not applicable (aerosol)
Flash point not applicable (aerosol)

Flammability (solid, gas) flammable aerosol in accordance with GHS criteria

Explosive limits

lower explosion limit (LEL)upper explosion limit (UEL)15 vol%

Vapour pressure 4,200 hPa at 20 °C

Density 0.6545 g/ml (calculated value)

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW)

This information is not available.

Auto-ignition temperature 287 °C

Viscosity not relevant (aerosol)

Explosive properties none Oxidising properties none

9.2 Other information There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. - Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

high temperatures

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

(en) Germany version number GHS 1.0

Page 6 / 11

according to Regulation (EC) No. 1907/2006 (REACH) 4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
acetone	67-64-1	oral	LD50	5,800 ^{mg} / _{kg}	rat
propan-2-ol	67-63-0	dermal	LD50	4,032 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment. Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 1 (slightly hazardous to water)

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
butane	106-97-8	LC50	27.98 ^{mg} / _l	fish	96 h
butane	106-97-8	EC50	7.71 ^{mg} / _l	algae	96 h
propane	74-98-6	LC50	27.98 ^{mg} / _l	fish	96 h
propane	74-98-6	EC50	7.71 ^{mg} / _l	algae	96 h
acetone	67-64-1	LC50	8,120 ^{mg} / _l	fish	96 h
propan-2-ol	67-63-0	LC50	10,000 ^{mg} / _l	fish	96 h

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
acetone	67-64-1	EC50	61.15 ^g / _l	microorgan- isms	30 min
propan-2-ol	67-63-0	LC50	>10,000 ^{mg} / _I	aquatic inver- tebrates	24 h

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
acetone	67-64-1	carbon dioxide generation	90.9 %	28 d
propan-2-ol	67-63-0	oxygen depletion	53 %	5 d

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
acetone	67-64-1		-0.24	
propan-2-ol	67-63-0		0.2 (pH value: 7, 25 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

16 05 04x gases in pressure containers (including halons) containing dangerous substances 15 01 10x packaging containing residues of or contaminated by dangerous substances

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

according to Regulation (EC) No. 1907/2006 (REACH) 4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

SECTION 14: Transport information

14.1UN number195014.2UN proper shipping nameAEROSOLS

14.3 Transport hazard class(es)

Class 2 (gases) (aerosol)
Subsidiary risk(s) 2.1 (flammability)

14.4 Packing group not assigned to a packing group

14.5 Environmental hazards none (non-environmentally hazardous acc. to the dangerous

goods regulations)

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number 1950
Proper shipping name AEROSOLS
Class 2
Classification code 5F
Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ)E0Limited quantities (LQ)1 LTransport category (TC)2Tunnel restriction code (TRC)D

• International Maritime Dangerous Goods Code (IMDG)

UN number 1950
Proper shipping name AEROSOLS
Class 2.1
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -

• International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1950

Proper shipping name Aerosols, flammable

Class 2.1 Danger label(s) 2.1

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19



Special provisions (SP) A145, A167, A802

Excepted quantities (EQ) FΩ Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1

Relevant provisions of the European Union (EU)

Directive 75/324/EEC relating to aerosol dispensers

Classification of the gas/aerosol Extremely flammable

Labelling Keep out of reach of children

Pressurized container: may burst if heated

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not pierce or burn, even after use

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Net contents by volume 500 ml

National regulations (Germany)

• Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water 1 (slightly hazardous to water) hazard class)

• Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concen- tration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 ^{kg} / _h	50 ^{mg} / _{m³}	3)

Notation

3) A total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK): 2 B (aerosol dispensers and lighters)

15.2 **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

2017/2398/EU. Directive of the European Parliament and of the Council amending Directive 2004/37/EC on the protection of workers from the risks related to

ADN

Directive of the European Parliament and of the Council amending Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work.

Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road).

Workplace exposure limit.
Bioconcentration factor.
Biochemical Oxygen Demand.

Chemical Oxygen Demand.

Chemical Oxygen Demand.

Chemical Datstracts Service (service that maintains the most comprehensive list of chemical substances).

Ceiling value.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Carcinogenic, Mutagenic or toxic for Reproduction.

Chemical oxygen demand.

Dangerous Goods Regulations (see IATA/DGR).

Derived Minimal Effect Level.

Derived Mon-Effect Level.

The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).

European Inventory of Existing Commercial Chemical Substances.

European Inventory of Existing Commercial Chemical Substances.

European List of Notified Chemical Substances.

E ADR.

AGW. BCF. BOD. CAS. Ceiling-C. CLP. CMR. COD. DGR. DMEL. DNEL. EC NO.

EC No.

EINECS. ELINCS.

ELINCS. EmS. Eye Dam. Eye Irrit. Flam. Gas. Flam. Liq. GHS. IATA. IATA/DGR. ICAO. IMDG. IOFLV IOELV.

(en) Germany version number GHS 1.0 Page 10 / 11

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354551 - NASSENTWICKLER - 500 ml



Date of compilation: 2018-12-19

LGK. Log KOW. MARPOL. NLP. PBT. PNEC.

Ppm. Press. Gas. REACH. RID.

Lagerklasse (storage class according to TRGS 510, Germany).
n-Octanol/water.
International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant").
No-Longer Polymer.
Persistent, Bioaccumulative and Toxic.
Predicted No-Effect Concentration.
Parts per million.
Gas under pressure.
Registration, Evaluation, Authorisation and Restriction of Chemicals.
Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Short-term exposure limit.
Specific tarqet organ toxicity - single exposure.

Specific target organ toxicity - single exposure.
Technische Regeln für GefahrStoffe (technical rules for hazardous substances, Germany).
Arbeitsplatzgrenzwerte (TRGS 900).
Biologische Grenzwerte (TRGS 903).
Time-weighted average.
Very Persistent and very Bioaccumulative.

STEL. STOT SE. TRGS. TRGS 900. TRGS 903. TWA. VPVB.

Key literature references and sources for data

Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU Regulation (EC) No. 1272/2008 (CLP, EU GHS)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

ises (code and rui text as stated in chapter 2 and 3)
Extremely flammable gas.
Extremely flammable aerosol.
Highly flammable liquid and vapour.
Pressurized container: may burst if heated.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May cause drowsiness or dizziness. H220. H222. H225. H229. H280. H319. H336.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.