

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **HOLZ-GLEITMITTEL - 400 ml**

Article number: 4000 354580

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the preparation: Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Nordwest Handel AG

Berliner Str. 26 - 36

D-58135 Hagen

Phone: +49 (0)2331/4610

Fax: +49 (0)2331/461389

Further information obtainable from: Datenblatt ausstellender Bereich/fachkundige Person: sdb@nordwest.com

1.4 Emergency telephone number:

Deutschland:

Giftinformationszentrum (GIZ), Mainz - Tel. +49(0)6131/19240 (24 h von Mo. – So.)

Österreich:

Vergiftungsinformationszentrale der Gesundheit Österreich Tel. +43 1 406 43 43

Schweiz:

Tox Info Suisse Tel. 145, 24h oder +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

DE

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: **HOLZ-GLEITMITTEL - 400 ml**

(Contd. of page 1)

Dangerous components:

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane	⚠ Flam. Gas 1, H220; Press. Gas, H280	30-60%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane	⚠ Flam. Gas 1, H220; Press. Gas, H280	25-40%
CAS: 8042-47-5 EINECS: 232-455-8	Paraffinum perliquidum DAB		5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0	isobutane	⚠ Flam. Gas 1, H220; Press. Gas, H280	1-1,5%

SECTION 4: First aid measures**4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurised containers.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Recommended storage temperature: 10-30 °C.

(Contd. on page 3)

- DE -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.11.2015

Revision: 09.11.2015

Trade name: **HOLZ-GLEITMITTEL - 400 ml**

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane

AGW (Germany)	Long-term value: 2400 mg/m ³ , 1000 ppm 4(II);DFG
---------------	---

74-98-6 propane

AGW (Germany)	Long-term value: 1800 mg/m ³ , 1000 ppm 4(II);DFG
---------------	---

8042-47-5 Paraffinum perliquidum DAB

TLV - TWA (Germany)	Long-term value: 5,0 mg/m ³ Gruppenwert Ölnebel
---------------------	---

75-28-5 isobutane

AGW (Germany)	Long-term value: 2400 mg/m ³ , 1000 ppm 4(II);DFG
---------------	---

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

When used properly and under normal conditions, breathing protection is not required.

· **Protection of hands:** Not required.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **As protection from splashes gloves made of the following materials are suitable:** PVC or PE gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Light weight protective clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Colourless

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not applicable for an aerosol *

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 365 °C

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: HOLZ-GLEITMITTEL - 400 ml

(Contd. of page 3)

· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Protect from sunlight and temperatures above 50 °C. Development of explosive vapor / air mixtures.
· Explosion limits:	
Lower:	1,5 Vol %
Upper:	10,9 Vol %
· Vapour pressure at 20 °C:	4200 hPa
· Density at 20 °C:	0,568 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· 9.2 Other information	* The final mixture in the aerosol is formed only after the addition of the pressurized gas. Some data are not measurable in a hermetically sealed, pressurized container.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

LD/LC50 values relevant for classification:

8042-47-5 Paraffinum perliquidum DAB

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 5200 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitisation:** No sensitising effects known.

SECTION 12: Ecological information

- **12.1 Toxicity**

· **Aquatic toxicity:**

74-98-6 propane

EC50 / 48h	27,1 mg/l (daphnia magna)
EC50 / 72h	11,9 mg/l (Algen)
LC50 / 96 h	49,9 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 5)

DE

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: HOLZ-GLEITMITTEL - 400 ml

(Contd. of page 4)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

16 05 04*	gases in pressure containers (including halons) containing dangerous substances
15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1
Label 2.1

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Gases.
Danger code (Kemler): -
EMS Number: F-D, S-U

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 1L
Code: E0
Excepted quantities (EQ) Not permitted as Excepted Quantity
Transport category 2
Tunnel restriction code D

IMDG

Limited quantities (LQ) 1L
Code: E0
Excepted quantities (EQ) Not permitted as Excepted Quantity

(Contd. on page 6)

DE

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 09.11.2015

Revision: 09.11.2015

Trade name: HOLZ-GLEITMITTEL - 400 ml

(Contd. of page 5)

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

DE