according to Regulation (EC) No. 1907/2006 (REACH)



Revision: 2021-11-30 Version number: GHS 9.0 Replaces version of: 2021-09-20 (GHS 8)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

PROMAT CHEMICALS KONTAKTSPRAY - 400 ml Trade name

Unique formula identifier (UFI) Y470-603I-700V-R93U

Article number 4000 354655

1.2 Relevant identified uses of the substance or mixture and uses advised against

general use Relevant identified uses

rust remover

Uses advised against do not use for products which come into contact with foodstuffs

1.3 Details of the supplier of the safety data sheet

> NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany

Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com

e-Mail (competent person): sdb@nordwest.com

1.4 **Emergency telephone number**

> Vergiftungsinformationszentrale der Gesundheit +43 1 406 43 43 Germany: Berätungsstelle bei Vergiftungen Giftinformation-+49(0)6131 / 19240

szentrale der Länder Rheinland-Pfalz und Hessen Switzerland: Tox Info Suisse +145, 24h oder +41 44 251 51 51

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	Cat. 1	(Aerosol 1)	H222,H229
3.45	skin sensitisation	Cat. 1	(Skin Sens. 1)	H317
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336

Remarks

For full text of H-phrases: see SECTION 16.

2.2 **Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word danger

Pictograms

GHS02, GHS07



H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace. P271 P272 P280

Wear protective gloves.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling:

Sulfonic acids, petroleum, calcium salts. Naphtha (wasserstoffbehandelt), niedrig siedend.

2.3 Other hazards

There is no additional information.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

(En) Germany: Page: 1: / 11: Version number: GHS 9.0:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to EU regulation							
Name of substance	Identifier	Wt%	Classification acc. to 1272/ 2008/EC	Picto- grams			
butane	CAS No 106-97-8	25 - < 50	Flam. Gas 1A / H220 Press. Gas C / H280	&			
	EC No 203-448-7						
	REACH Reg. No 01-2119474691-32						
Propan	CAS No 74-98-6	25 - < 50	Flam. Gas 1A / H220 Press. Gas L / H280	⋄ ◆			
	EC No 200-827-9						
	REACH Reg. No 01-2119486944-21						
Kohlenwasserstoffe, C9-C10, n-Al- kane, iso-Alkane, cyclische Ver-	CAS No 64742-49-0	10 - < 25	Flam. Liq. 3 / H226 STOT SE 3 / H336	(b) (1)			
bindungen, <2% Aromaten	EC No 927-241-2		Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	&			
	REACH Reg. No 01-2119471843-32						
Distillates (petroleum), solvent- dewaxed heavy paraffinic	CAS No 64742-65-0	5-<10	Asp. Tox. 1 / H304	&			
	EC No 265-169-7						
	REACH Reg. No 01-2119471299-27						
White mineral oil (petroleum)	CAS No 8042-47-5	5-<10	Asp. Tox. 1 / H304	&			
	EC No 232-455-8			Ť			
	REACH Reg. No 01-2119487078-27-xxxx						
isobutane	CAS No 75-28-5	1-<5	Flam. Gas 1A / H220 Press. Gas C / H280	&			
	EC No 200-857-2						
	REACH Reg. No 01-2119485395-27						

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water. Take off contaminated clothing.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

(En) Germany: Page: 2: / 11:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, BC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Collect spillage (universal binder).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

• Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

· Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

Observe instructions for use. Keep out of reach of children.

(En) Germany: Page: 3: / 11:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

· Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Nota- tion	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling- C [ppm]	Ceiling- C [mg/ m³]	Source
DE	butane	106-97-8		AGW	1,000	2,400	4,000	9,600			TRGS 900
DE	propane	74-98-6		AGW	1,000	1,800	4,000	7,200			TRGS 900
DE	isobutane	75-28-5		AGW	1,000	2,400	4,000	9,600			TRGS 900
DE	white mineral oil (petroleum)	8042-47-5	r, Y	AGW		5		20			TRGS 900
DE	white mineral oil (petroleum)	8042-47-5	r	MAK		5		20			DFG

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified) time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 TWA

hours time-weighted average (unless otherwise specified) a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the bio-

logical limit value (BGW) are adhered to

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Naphtha (wasserstoff- behandelt), niedrig siedend	64742-49- 0	DNEL	300 mg/kg	human, dermal	worker (industry)	chronic - systemic ef- fects
Naphtha (wasserstoff- behandelt), niedrig siedend	64742-49- 0	DNEL	1,500 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects

• relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65- 0	PNEC	9.33 ^{mg} / _{kg}	aquatic organisms	water	short-term (single instance)

8.2 **Exposure controls**

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)







Eye/face protection

Use protective eyewear to guard against splash of liquids.

Page: 4: / 11: (En) Germany:

Version number: GHS 9.0:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Date of compilation: 2021-11-30 Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)

Skin protection · hand protection

Wear protective gloves. (Splash protection)

type of material

NR: natural rubber, latex, FKM: fluoro-elastomer • breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection Full face mask/half mask/quarter mask (EN 136/140)
Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/ White)

Environmental exposure controls

Use appropriate container to avoid environmental contamination.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties 9.1

Appearance

Physical state aerosol (spray aerosol)

Colour light yellow Odour characteristic

Other physical and chemical parameters

Melting point/freezing point -159.4 °C not applicable (aerosol)

Initial boiling point and boiling range not applicable (aerosol) Flash point not applicable (aerosol)

Flammability (solid, gas) flammable aerosol in accordance with GHS criteria

Explosive limits

· lower explosion limit (LEL) 0.6 vol% • upper explosion limit (UEL) 15 vol%

Vapour pressure 4,200 hPa at 20 °C

Density $0.6455 - 0.6492 \, {}^{9}/_{ml}$ (calculated value)

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW) This information is not available.

Auto-ignition temperature 287°C

Viscosity not relevant (aerosol)

Explosive properties none Oxidising properties none

Other information There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

10.2 **Chemical stability**

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. - Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

high temperatures

10.5 Incompatible materials

oxidisers

(En) Germany: Page: 5: / 11:



according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml



Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
White mineral oil (petroleum)	8042-47-5	oral	LD50	>5,000 ^{mg} / _{kg}	rat
White mineral oil (petroleum)	8042-47-5	inhalation: dust/mist	LC50	>5 ^{mg} / _l /4h	rat
White mineral oil (petroleum)	8042-47-5	dermal	LD50	>2,000 ^{mg} / _{kg}	rabbit
White mineral oil (petroleum)	8042-47-5	inhalation: va- pour	LC50	>5,000 ^{mg} / _l /4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment. Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 2 (obviously hazardous to water)

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	LL50	>100 ^{mg} / _l	fish	96 h
White mineral oil (petroleum)	8042-47-5	LL50	>100 ^{mg} / _l	fish	96 h

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	LL50	>10,000 ^{mg} / _l	aquatic inverteb- rates	24 h

(En) Germany: Page: 6: / 11:

Version number: GHS 9.0:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml



Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
Naphtha (wasserstoffbehandelt), niedrig siedend	64742-49-0	oxygen depletion	8 %	3 d

12.3 **Bioaccumulative potential**

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

16 05 04* gases in pressure containers (including halons) containing hazardous substances 15 01 10* packaging containing residues of or contaminated by hazardous substances

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	1950
14.2	UN proper shipping name	AEROSOLS

14.3 Transport hazard class(es)

2 (gases) (aerosol) Class Subsidiary risk(s) 2.1 (flammability)

14.4 Packing group not assigned to a packing group

14 5 Environmental hazards none (non-environmentally hazardous acc. to the dangerous goods regulations)

Special precautions for user 14.6

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

(En) Germany: Page: 7: / 11:


Version number: GHS 9.0:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml



Replaces version of: 2021-09-20 (GHS 8)



UN number 1950 Proper shipping name **AEROSOLS**

Class Classification code 5F Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0 Limited quantities (LQ) 1 L Transport category (TC) 2 Tunnel restriction code (TRC) D

• International Maritime Dangerous Goods Code (IMDG)

AEROSOLS Proper shipping name Class 2.1 Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0 Limited quantities (LQ) 1 L EmS F-D, S-U Stowage category

• International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1950

Proper shipping name Aerosols, flammable

Class 2.1 Danger label(s) 2.1



Special provisions (SP) A145, A167 Excepted quantities (EQ) E0 Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

· Restrictions according to REACH, Annex XVII

Name acc. to inventory	CAS No	Restriction	No
flammable / pyrophoric		R40	40
flammable / pyrophoric		R40	40
flammable / pyrophoric		R40	40
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
flammable / pyrophoric		R40	40
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3

Legend

1. Shall not be used in: R3

- ornamental articles intended to produce light or colour effects by means of different phases, for example in orna-

Page: 8: / 11: (En) Germany:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

Legend

mental lamps and ashtrays,

- tricks and jokes,

- games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market.

 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume,
- or both, if they
- can be used as fuel in decorative oil lamps for supply to the general public, and present an aspiration hazard and are labelled with H304.

- 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation
- 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following re quirements are met:
- (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil or even sucking the wick of lamps may lead to life-threatening lung damage";
- (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage'; (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';

 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended

R40

- for supply to the general public for entertainment and decorative purposes such as the following:
- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- 'whoopee' cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.
- 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.
- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
- 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
- · List of substances subject to authorisation (REACH, Annex XIV) / SVHC candidate list

none of the ingredients are listed

• Directive 75/324/EEC relating to aerosol dispensers

Classification of the gas/aerosol

extremely flammable

Labelling

keep out of reach of children pressurized container: may burst if heated keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking do not pierce or burn, even after use protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Net contents by volume 400 ml

• Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

- Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR) none of the ingredients are listed
- Water Framework Directive (WFD)

none of the ingredients are listed

• Explosives precursors which are subject to restrictions

none of the ingredients are listed

Regulation 648/2004/EC on detergents

Labelling of contents		
Constituents	Weight % content (or range)	
aliphatic hydrocarbons	30 % and more	

National regulations (Germany)

· Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water 2 (obviously hazardous to water) hazard class)

(En) Germany: Page: 9: / 11:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Date of compilation: 2021-11-30 Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)



• Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentra- tion	Notation
5.2.5	organic substances	class I	5 – < 10 wt%	0.1 ^{kg} / _h	20 ^{mg} / _{m³}	3)
5.2.5	organic substances		≥ 25 wt%	0.5 ^{kg} / _h	50 ^{mg} / _{m³}	3)

Notation

a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total 3) carbon, shall not be exceeded (except organic particulate matter)

 Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany) Storage class (LGK): 2 B (aerosol dispensers and lighters)

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
3.2		Hazardous ingredients acc. to EU regulation: change in the listing (table)	yes

Abbreviations and acronyms

Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Danger-ADN.

ADR.

AGW.

Aquatic Chronic. Asp. Tox. BCF. BOD.

CAS. Ceiling-C. CLP.

CMR. COD.

concerning the International Carriage of Dangerous Goods by Inland Waterways).

Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).

Workplace exposure limit.

Hazardous to the aquatic environment - chronic hazard.

Aspiration hazard.

Bioconcentration factor.

Biochemical Oxygen Demand.

Chemical Oxygen Demand.

Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).

Celling value.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Carcinogenic, Mutagenic or toxic for Reproduction.

Chemical oxygen demand.

Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.

Dangerous Goods Regulations (see IATA/DGR).

Derived Minimal Effect Level.

Derived Minimal Effect Level.

Derived No-Effect Level.

European List of Notified Chemical Substances.

Flammable gas.

Flammable gas.

Flammable gas.

Flammable Harmonized System of Classification and Labelling of Chemicals'' developed by the United Nations.

International Air Transport Association.

Dangerous Goods Regulations (DGR) for the air transport (IATA).

International Civil Aviation Organization.

International Maritime Dangerous Goods Code.

Lethal Concentration 50%: the LD50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval. DFG.

DGR. DMEL.

DNEL. EC No.

EINECS. ELINCS.

EmS. Flam. Gas.

Flam. Liq. GHS. IATA. IATA/DGR. ICAO. IMDG. LC50.

LD50.

val.

Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval. Lagerklasse (storage class according to TRGS 510, Germany).

Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality.

n-Octanol/water.

International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant").

No-Longer Polymer.

Persistent, Bioaccumulative and Toxic.

Predicted No-Effect Concentration.

Parts per million LGK. LL50.

LL50. Log KOW. MARPOL. NLP. PBT. PNEC.

Ppm. Press. Gas. REACH. RID.

Predicted No-Effect Concentration.
Parts per million.
Gas under pressure.
Registration, Evaluation, Authorisation and Restriction of Chemicals.
Solventian authorisation and Restriction and

STEL. STOT SE. SVHC.

Short-term exposure limit.
Specific target organ toxicity - single exposure.
Substance of Very High Concern.
Technische Regeln für GefahrStoffe (technical rules for hazardous substances, Germany).
Arbeitsplatzgrenzwerte (TRGS 900).
Time-weighted average.
Very Persistent and very Bioaccumulative.

TRGS. TRGS 900. TWA. VPvB.

(En) Germany: Page: 10: / 11:

according to Regulation (EC) No. 1907/2006 (REACH)

4000 354655 - PROMAT CHEMICALS KONTAKTSPRAY - 400 ml

Version number: GHS 9.0

Replaces version of: 2021-09-20 (GHS 8)



Date of compilation: 2021-11-30

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU Regulation (EC) No. 1272/2008 (CLP, EU GHS)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Extremely flammable gas.
Extremely flammable aerosol.
Flammable liquid and vapour.
Pressurised container: May burst if heated.
Contains gas under pressure; may explode if heated.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects. H220. H222. H226. H229. H280. H304. H317.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

(En) Germany: Version number: GHS 9.0: Page: 11: / 11: