

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name PROMAT CHEMICALS ROSTPRIMER - 400 ml
Unique formula identifier (UFI) SV60-P01C-A00D-R8CN

Article number 4000 354670 (GRAU/GRIJS/GRIS/SZARY)
4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use
Anti-corrosion coating

1.3 Details of the supplier of the safety data sheet

NORDWEST Handel AG
Robert-Schuman-Straße 17
44263 Dortmund
Germany

Telephone: +49 (0)231 2222-3001
Telefax: +49 (0)231 2222-3099
e-mail: sdb@nordwest.com
Website: www.nordwest.com

e-mail (competent person) sdb@nordwest.com

1.4 Emergency telephone number

Poison centre			
Country	Name	Postal code/city	Telephone
Austria	Vergiftungsinformationszentrale der Gesundheit		+43 1 406 43 43
Germany	Beratungsstelle bei Vergiftungen Gif tinformationszentrale der Länder Rheinland-Pfalz und Hessen	55131 Mainz	+49(0)6131 / 19240
Switzerland	Tox Info Suisse		+145, 24h oder +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222, H229
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word danger

Pictograms

GHS02, GHS07



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains 2-butanone oxime, Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

Hazardous ingredients for labelling acetone, butanone, Hydrocarbons, C9, aromatics, 1-Methoxy-2-propylacetate

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms
CAS No 67-64-1 EC No 200-662-2 Index No 606-001-00-8 REACH Reg. No 01-2119471330-49	acetone	25 – < 50	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 
CAS No 106-97-8 EC No 203-448-7 Index No 601-004-00-0 REACH Reg. No 01-2119474691-32	butane	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	 
CAS No 74-98-6 EC No 200-827-9 Index No 601-003-00-5 REACH Reg. No 01-2119486944-21	propane	5 – < 10	Flam. Gas 1 / H220 Press. Gas L / H280	 
CAS No 78-93-3 EC No 201-159-0 REACH Reg. No 01-2119457290-43-xxxx	butanone	5 – < 10	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 
CAS No 64742-95-6 EC No 265-199-0 REACH Reg. No 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics	1 – < 5	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	   

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Identifier	Name of substance	Wt%	Classification acc. to GHS	Pictograms
CAS No 1330-20-7 EC No 215-535-7 Index No 601-022-00-9 REACH Reg. No 01-2119488216-32-xxxx	xylene	1 – < 5	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315	 
CAS No 71-36-3 EC No 200-751-6 REACH Reg. No 01-2119484630-38-xxxx	Butan-1-ol	1 – < 5	Flam. Liq. 3 / H226 Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 STOT SE 3 / H335	  
CAS No 64742-94-5 EC No 265-198-5 Index No 649-424-00-3 REACH Reg. No 01-2119510128-50-xxxx	Solvent naphtha (petroleum), heavy arom.	1 – < 5	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	  
CAS No 108-65-6 EC No 203-603-9 REACH Reg. No 01-2119475791-29-xxxx	1-Methoxy-2-propylacetate	1 – < 5	Flam. Liq. 3 / H226 STOT SE 3 / H336	 
CAS No 7779-90-0 EC No 231-944-3 Index No 030-011-00-6 REACH Reg. No 01-2119485044-40-xxxx	trizinc bis(orthophosphate)	< 1	Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	
CAS No 96-29-7 EC No 202-496-6 Index No 616-014-00-0 REACH Reg. No 01-2119539477-28-xxxx	2-butanone oxime	< 1	Acute Tox. 4 / H312 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Carc. 2 / H351	  
CAS No 136-52-7 EC No 205-250-6 REACH Reg. No 01-2119524678-29-xxxx	Cobalt bis(2-ethylhexanoate)	< 1	Eye Irrit. 2 / H319 Skin Sens. 1A / H317 Repr. 1B / H360Fd Aquatic Acute 1 / H400 Aquatic Chronic 3 / H412	  
Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
xylene	-	-	1,100 mg/kg 11 mg/l/4h	dermal inhalation: vapour
Butan-1-ol	-	-	500 mg/kg	oral
2-butanone oxime	-	-	1,100 mg/kg	dermal

For full text of abbreviations: see SECTION 16.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Packaging compatibilities

Keep only in original container.

Storage class (LGK) TRGS 510

LGK 2 B (aerosol dispensers and lighters)

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
DE	hydrocarbon mixture (RCP method)		AGW		150		300				TRGS 900
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	1-methoxy-2-propyl acetate	108-65-6	MAK	50	270	50	270				DFG
DE	2-methoxy-1-methylethyl acetate	108-65-6	AGW	50	270	50	270			Y	TRGS 900
DE	xylene, mixture of isomers	1330-20-7	MAK	50	220	100	440				DFG
DE	xylene, mixture of isomers	1330-20-7	AGW	50	220	100	440			H	TRGS 900
DE	acetone	67-64-1	AGW	500	1,200	1,000	2,400			Y	TRGS 900
DE	butan-1-ol	71-36-3	AGW	100	310	100	310			Y	TRGS 900
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900
DE	butanone	78-93-3	AGW	200	600	200	600			H, Y	TRGS 900
DE	butanone oxime	96-29-7	AGW	0.3	1	2.4	8			H, Sh, Y	TRGS 900
EU	2-methoxy-1-methylethyl acetate	108-65-6	IOELV	50	275	100	550				2000/39/EC
EU	xylene	1330-20-7	IOELV	50	221	100	442				2000/39/EC
EU	acetone	67-64-1	IOELV	500	1,210						2000/39/EC

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	ethyl methyl ketone	78-93-3	IOELV	200	600	300	900				2000/39/EC

Notation

Ceiling-C

H

Sh

STEL

TWA

Y

ceiling value is a limit value above which exposure should not occur

absorbed through the skin

skin-sensitising substances

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the bio-

logical limit value (BGW) are adhered to

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	xylene, mixture of isomers	methylhippuric acids		BAT	2,000 mg/l	DFG
DE	xylene, mixture of isomers	methylhippuric acids		BLV	2,000 mg/l	TRGS 903
DE	acetone	acetone		BLV	80 mg/l	TRGS 903
DE	1-butanol	1-butanol	crea	BLV	2 mg/g	TRGS 903
DE	1-butanol	1-butanol	hydr, crea	BLV	10 mg/g	TRGS 903
DE	butanone (methyl ethyl ketone)	2-butanone		BLV	2 mg/l	TRGS 903
DE	butanone (methyl ethyl ketone)	ethyl methyl ketone		BAT	2 mg/l	DFG

Notation

crea

hydr

creatinine

hydrolysis

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
acetone	67-64-1	DNEL	2,420 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
butanone	78-93-3	DNEL	1,161 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
butanone	78-93-3	DNEL	600 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	64742-95-6	DNEL	25 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	64742-95-6	DNEL	150 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1-Methoxy-2-propyl-acetate	108-65-6	DNEL	275 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1-Methoxy-2-propyl-acetate	108-65-6	DNEL	550 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
1-Methoxy-2-propyl-acetate	108-65-6	DNEL	796 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	289 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
xylene	1330-20-7	DNEL	289 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	180 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Butan-1-ol	71-36-3	DNEL	310 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	9 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	3.33 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	1.3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	2.5 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
trizinc bis(orthophosphate)	7779-90-0	DNEL	5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
trizinc bis(orthophosphate)	7779-90-0	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Cobalt bis(2-ethylhexanoate)	136-52-7	DNEL	235.1 µg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
acetone	67-64-1	PNEC	21 mg/l	aquatic organisms	water	intermittent release
butanone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
butanone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	marine water	short-term (single instance)
butanone	78-93-3	PNEC	709 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
butanone	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
butanone	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
butanone	78-93-3	PNEC	1,000 mg/kg	aquatic organisms	water	short-term (single instance)
butanone	78-93-3	PNEC	22.5 mg/kg	terrestrial organisms	soil	short-term (single instance)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGEBRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
butanone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	water	intermittent release
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	6.35 mg/l	aquatic organisms	water	intermittent release
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.635 mg/l	aquatic organisms	freshwater	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.064 mg/l	aquatic organisms	marine water	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	3.29 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.329 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1-Methoxy-2-propyl-acetate	108-65-6	PNEC	0.29 mg/kg	terrestrial organisms	soil	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	water	intermittent release
xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Butan-1-ol	71-36-3	PNEC	0.082 mg/l	aquatic organisms	freshwater	short-term (single instance)
Butan-1-ol	71-36-3	PNEC	0.008 mg/l	aquatic organisms	marine water	short-term (single instance)
Butan-1-ol	71-36-3	PNEC	2.25 mg/l	aquatic organisms	water	intermittent release
Butan-1-ol	71-36-3	PNEC	2,476 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Butan-1-ol	71-36-3	PNEC	0.178 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Butan-1-ol	71-36-3	PNEC	0.018 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Butan-1-ol	71-36-3	PNEC	0.015 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	0.256 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	177 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
trizinc bis(orthophosphate)	7779-90-0	PNEC	20.6 µg/l	aquatic organisms	freshwater	short-term (single instance)
trizinc bis(orthophosphate)	7779-90-0	PNEC	6.1 µg/l	aquatic organisms	marine water	short-term (single instance)
trizinc bis(orthophosphate)	7779-90-0	PNEC	100 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
trizinc bis(orthophosphate)	7779-90-0	PNEC	117.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
trizinc bis(orthophosphate)	7779-90-0	PNEC	56.5 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
trizinc bis(orthophosphate)	7779-90-0	PNEC	35.6 mg/kg	terrestrial organisms	soil	short-term (single instance)
Cobalt bis(2-ethylhexanoate)	136-52-7	PNEC	0.62 µg/l	aquatic organisms	freshwater	short-term (single instance)
Cobalt bis(2-ethylhexanoate)	136-52-7	PNEC	2.36 µg/l	aquatic organisms	marine water	short-term (single instance)
Cobalt bis(2-ethylhexanoate)	136-52-7	PNEC	0.37 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Cobalt bis(2-ethylhexanoate)	136-52-7	PNEC	53.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Cobalt bis(2-ethylhexanoate)	136-52-7	PNEC	69.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Cobalt bis(2-ethylhexanoate)	136-52-7	PNEC	10.9 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)



Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

Hand protection

Wear protective gloves. (Splash protection)

Type of material

NR: natural rubber, latex, FKM: fluoro-elastomer

Breakthrough times of the glove material

>480 minutes (permeation: level 6)

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Full face mask/half mask/quarter mask (EN 136/140).

Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	aerosol (spray aerosol)
Colour	acc. to product description
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not applicable (aerosol)
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	50 g/m ³ - 350 g/m ³ / 1.5 vol% - 15 vol%
Flash point	not applicable (aerosol)
Decomposition temperature	not relevant
pH (value)	not applicable (aerosol)
Kinematic viscosity	not relevant
Solubility(ies)	not determined

Vapour pressure 4,200 hPa at 20 °C

Density and/or relative density

Density 0.9108 – 0.9127 g/ml (calculated value)

no data available

9.2 Other information

Information with regard to physical hazard classes there is no additional information

Other safety characteristics

Temperature class (EU, acc. to ATEX) T3 (maximum permissible surface temperature on the equipment: 200°C)
Odour characteristic

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapour	11 mg/l/4h
Butan-1-ol	71-36-3	oral	500 mg/kg
2-butanone oxime	96-29-7	dermal	1,100 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Contains 2-butanone oxime, Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
acetone	67-64-1	EC50	61.15 g/l	microorganisms	30 min
butanone	78-93-3	LC50	1,816 mg/l	fish	24 h
butanone	78-93-3	EC50	>345 mg/l	aquatic invertebrates	24 h
butanone	78-93-3	ErC50	1,901 mg/l	algae	24 h
Hydrocarbons, C9, aromatics	64742-95-6	EC50	>99 mg/l	microorganisms	10 min
1-Methoxy-2-propylacetate	108-65-6	LC50	63.5 mg/l	fish	14 d
1-Methoxy-2-propylacetate	108-65-6	EC50	>100 mg/l	aquatic invertebrates	21 d
Butan-1-ol	71-36-3	EC50	18 mg/l	aquatic invertebrates	21 d
Solvent naphtha (petroleum), heavy arom.	64742-94-5	LL50	17 mg/l	fish	24 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Solvent naphtha (petroleum), heavy arom.	64742-94-5	EL50	4.6 mg/l	aquatic invertebrates	24 h
Cobalt bis(2-ethylhexanoate)	136-52-7	LC50	41,625 µg/l	fish	28 d
Cobalt bis(2-ethylhexanoate)	136-52-7	EC50	82.2 µg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
acetone	67-64-1	carbon dioxide generation	90.9 %	28 d		
butanone	78-93-3	oxygen depletion	98 %	28 d		ECHA
Hydrocarbons, C9, aromatics	64742-95-6	oxygen depletion	30.9 %	2 d		ECHA
1-Methoxy-2-propylacetate	108-65-6	carbon dioxide generation	90 %	28 d		ECHA
1-Methoxy-2-propylacetate	108-65-6	oxygen depletion	60 %	5.9 d		ECHA
1-Methoxy-2-propylacetate	108-65-6	DOC removal	99 %	28 d		ECHA
Butan-1-ol	71-36-3	oxygen depletion	68 %	5 d		ECHA
Cobalt bis(2-ethylhexanoate)	136-52-7	carbon dioxide generation	60 %	10 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
acetone	67-64-1		-0.24	
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
propane	74-98-6		1.09 (pH value: 7, 20 °C)	
butanone	78-93-3		0.3 (pH value: 7, 40 °C)	
1-Methoxy-2-propylacetate	108-65-6		1.2 (pH value: 6.8, 20 °C)	
Butan-1-ol	71-36-3		1 (pH value: 7, 25 °C)	
2-butanone oxime	96-29-7	0.5 - 0.6	0.63	
trizinc bis(orthophosphate)	7779-90-0	28,960		
Cobalt bis(2-ethylhexanoate)	136-52-7	23		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes, (Recommendations)

Product

08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances

Product residues

16 05 04* Gases in pressure containers (including halons) containing hazardous substances

Packagings

15 01 04 Metallic packaging

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

ADR/RID/ADN	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant -
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167
Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Deco-Paint Directive (2004/42/EC)

VOC content	620.7 g/l			
Maximum VOC content limit				
Product category	Product subcategory	Coating	Type	VOC g/l
vehicle refinishing products	special finishes	all types		840

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
xylene	1330-20-7	(17) (11)	

Legend

- (11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded
(17) Total mass of xylene (ortho-xylene, meta-xylene, para-xylene)

Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
trizinc bis(orthophosphate)		A)	
trizinc bis(orthophosphate)		A)	
2-butanone oxime		A)	
Cobalt bis(2-ethylhexanoate)		A)	

Legend

A) Indicative list of the main pollutants

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

This product is regulated by Regulation (EU) No 2019/1148: All suspicious transactions as well as the loss and theft of significant quantities must be reported to the competent authority.

Explosives precursors which are subject to restrictions

Name of substance	CAS No	Type of registration	Remarks	Limit value	Upper limit value for the purpose of licensing under Article 5(3)
acetone	67-64-1	Annex II			

Legend

annex II Substances on their own or in mixtures or in substances for which suspicious transactions shall be reported

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK (water hazard class) 2 obviously hazardous to water

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m ³	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

National inventories

Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Unique formula identifier (UFI): SV60-P01C-A00D-R8CN		yes
1.1		Unique formula identifier (UFI): SV60-P01C-A00D-R8CN	yes
1.2	Uses advised against: do not use for products which come into contact with foodstuffs		yes
1.3	Details of the supplier of the safety data sheet: NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 Website: www.nordwest.com	Details of the supplier of the safety data sheet: NORDWEST Handel AG Robert-Schuman-Straße 17 44263 Dortmund Germany Telephone: +49 (0)231 2222-3001 Telefax: +49 (0)231 2222-3099 e-mail: sdb@nordwest.com Website: www.nordwest.com	yes
1.3	e-Mail (competent person): sdb@nordwest.com		yes
1.3		e-mail (competent person): sdb@nordwest.com	yes
1.4		Poison centre: change in the listing (table)	yes

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1	Remarks: For full text of H-phrases: see SECTION 16.		yes
2.1	Supplemental hazard information		yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Pictograms: change in the listing (table)	yes
2.2	Additional labelling requirements		yes
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		yes
2.2		Precautionary statements: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards: of no significance	yes
3.1		Substances: Not relevant (mixture)	yes
3.2		Hazardous ingredients acc. to EU regulation: change in the listing (table)	yes
3.2		Description of the mixture: change in the listing (table)	yes
3.2		Description of the mixture: change in the listing (table)	yes
4.1	Following skin contact: Wash with plenty of soap and water. Take off contaminated clothing.	Following skin contact: Wash with plenty of soap and water.	yes
4.1	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.	yes
6.2	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.	yes
6.3	Advice on how to clean up a spill: Collect spillage (universal binder).		yes
7.2	Incompatible substances or mixtures: Observe hints for combined storage.		yes
7.2	Consideration of other advice: Observe instructions for use. Keep out of reach of children.		yes
7.2	• Packaging compatibilities: Only packagings which are approved (e.g. acc. to ADR) may be used.	Packaging compatibilities: Keep only in original container.	yes
7.2		Storage class (LGK) TRGS 510: LGK 2 B (aerosol dispensers and lighters)	yes
8.1	National limit values		yes
8.1	Occupational exposure limit values (Workplace Exposure Limits)		yes

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.1	Biological limit values		yes
8.1		Biological limit values: change in the listing (table)	yes
8.1	Relevant DNELs/DMELs/PNECs and other threshold levels		yes
8.1	• relevant DNELs of components of the mixture		yes
8.1	• relevant PNECs of components of the mixture		yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
8.2	Individual protection measures (personal protective equipment): eye protection must be worn safety gloves must be worn do not eat or drink	Individual protection measures (personal protective equipment): eye protection must be worn safety gloves must be worn do not eat or drink Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.	yes
8.2	Environmental exposure controls: Use appropriate container to avoid environmental contamination.	Environmental exposure controls: Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.	yes
9.1	Appearance		yes
9.1	Odour: characteristic		yes
9.1	Other physical and chemical parameters		yes
9.1	Melting point/freezing point: not applicable (aerosol)	Melting point/freezing point: not determined	yes
9.1	Explosive limits	Lower and upper explosion limit: 50 g/m ³ - 350 g/m ³ / 1.5 vol% - 15 vol%	yes
9.1	• lower explosion limit (LEL): 1.5 vol% (50 g/m ³)		yes
9.1	• upper explosion limit (UEL): 15 vol% (350 g/m ³)		yes
9.1		Decomposition temperature: not relevant	yes
9.1		pH (value): not applicable (aerosol)	yes
9.1		Kinematic viscosity: not relevant	yes
9.1	Partition coefficient		yes
9.1	n-octanol/water (log KOW): This information is not available.		yes
9.1	Auto-ignition temperature: 220 °C (auto-ignition temperature (liquids and gases))		yes
9.1	Viscosity: not relevant (aerosol)		yes
9.1	Explosive properties: none		yes
9.1	Oxidising properties: none		yes
9.1		Density and/or relative density	yes
9.1	Density: 0.9108 - 0.9127 g/ml (calculated value)	Density: 0.9108 - 0.9127 g/ml (calculated value) no data available	yes
9.2	Other information: There is no additional information.	Other information	yes
9.2		Information with regard to physical hazard classes: there is no additional information	yes
9.2		Other safety characteristics	yes

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
9.2		Temperature class (EU, acc. to ATEX): T3 (maximum permissible surface temperature on the equipment: 200°C)	yes
9.2		Odour: characteristic	yes
10.4	Physical stresses which might result in a hazardous situation and have to be avoided: high temperatures		yes
11.1	• Acute toxicity of components of the mixture		yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes
11.1		• Acute toxicity of components of the mixture: change in the listing (table)	yes
11.1	Summary of evaluation of the CMR properties: Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.		yes
11.1	Specific target organ toxicity (STOT)		yes
11.1		Germ cell mutagenicity: Shall not be classified as germ cell mutagenic.	yes
11.1		Carcinogenicity: Shall not be classified as carcinogenic.	yes
11.1		Reproductive toxicity: Shall not be classified as a reproductive toxicant.	yes
11.2		Information on other hazards: There is no additional information.	yes
12.1	Toxicity: Harmful to aquatic life with long lasting effects. Wassergefährdungsklasse, WGK (water hazard class) (WGK; Germany): 2 (obviously hazardous to water)	Toxicity: Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)	yes
12.1	Aquatic toxicity (acute)		yes
12.1	Aquatic toxicity (acute) of components of the mixture		yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.1	Aquatic toxicity (chronic): May cause long-term adverse effects in the aquatic environment.		yes
12.1	Aquatic toxicity (chronic) of components of the mixture		yes
12.2	Degradability of components of the mixture		yes
12.3	Bioaccumulative potential of components of the mixture		yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.2		Degradability of components of the mixture: change in the listing (table)	yes
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)	yes
13.1	List of wastes: 16 05 04* gases in pressure containers (including halons) containing hazardous substances 15 01 10* packaging containing residues of or contaminated by hazardous substances	List of wastes, (Recommendations)	yes
13.1		Product: 08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances	yes
13.1		Product residues: 16 05 04* Gases in pressure containers (including halons) containing hazardous substances	yes
13.1		Packagings: 15 01 04 Metallic packaging	yes
14.1	UN number: 1950	UN number or ID number	yes

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.1		ADR/RID/ADN: UN 1950	yes
14.1		IMDG-Code: UN 1950	yes
14.1		ICAO-TI: UN 1950	yes
14.2	UN proper shipping name: AEROSOLS	UN proper shipping name	yes
14.2		ADR/RID/ADN: AEROSOLS	yes
14.2		IMDG-Code: AEROSOLS	yes
14.2		ICAO-TI: Aerosols, flammable	yes
14.3	Class: 2 (gases) (aerosol)		yes
14.3	Subsidiary risk(s): 2.1 (flammability)		yes
14.3		ADR/RID/ADN: 2 (2.1)	yes
14.3		IMDG-Code: 2.1	yes
14.3		ICAO-TI: 2.1	yes
14.4	Packing group: not assigned to a packing group	Packing group: not assigned	yes
14.5	Environmental hazards: none (non-environmentally hazardous acc. to the dangerous goods regulations)	Environmental hazards: non-environmentally hazardous acc. to the dangerous goods regulations	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class: 2		yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class: 2.1		yes
14.7		Marine pollutant: -	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: Aerosols, flammable		yes
14.7	Class: 2.1		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Danger label(s): change in the listing (table)	yes
15.1	• Restrictions according to REACH, Annex XVII		yes
15.1		• Restrictions according to REACH, Annex XVII: change in the listing (table)	yes
15.1	• Directive 75/324/EEC relating to aerosol dispensers		yes
15.1	Classification of the gas/aerosol: extremely flammable		yes

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0
Replaces version of: 2020-10-12 (GHS 2)

Revision: 2021-03-30

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1	Labelling: keep out of reach of children pressurized container: may burst if heated keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking do not pierce or burn, even after use protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F		yes
15.1	Net contents by volume: 400 ml		yes
15.1		Maximum VOC content limit: change in the listing (table)	yes
15.1		VOC content: 620.7 g/l	yes
15.1		Maximum VOC content limit: change in the listing (table)	yes
15.1		• Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR): change in the listing (table)	yes
15.1		Pollutant release and transfer registers (PRTR): change in the listing (table)	yes
15.1		List of pollutants (WFD): change in the listing (table)	yes
15.1		Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013: This product is regulated by Regulation (EU) No 2019/1148: All suspicious transactions as well as the loss and theft of significant quantities must be reported to the competent authority.	yes
15.1		Explosives precursors which are subject to restrictions: change in the listing (table)	yes
15.1	• Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)		yes
15.1	Storage class (LGK): 2 B (aerosol dispensers and lighters)		yes
15.1	National inventories		yes
15.1		National inventories: change in the listing (table)	yes
15.1		National inventories	yes
15.1		National inventories: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16	Key literature references and sources for data: - Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU - Regulation (EC) No. 1272/2008 (CLP, EU GHS)	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU. Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	yes
16		List of relevant phrases (code and full text as stated in chapter 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations.
2000/39/EC.	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC.
Acute Tox.	Acute toxicity.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road).
ADR/RID/ADN.	European Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).
AGW.	Workplace exposure limit.
Aquatic Acute.	Hazardous to the aquatic environment - acute hazard.
Aquatic Chronic.	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
ATE.	Acute Toxicity Estimate.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.
Carc.	Carcinogenicity.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
Ceiling-C.	Ceiling value.
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD.	Chemical oxygen demand.
DFG.	Deutsche Forschungsgemeinschaft MAK- und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DGR.	Dangerous Goods Regulations (see IATA/DGR).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



4000 354670 (GRAU/GRIJS/GRIS/SZARY) - 4000 354675 (ROTBRAUN/ROODBRUJN/ROUGE BRUN/CZERWONO-BRĄZOWY)) - PROMAT CHEMICALS ROSTPRIMER - 400 ml

Version number: GHS 3.0

Revision: 2021-03-30

Replaces version of: 2020-10-12 (GHS 2)

Abbr.	Descriptions of used abbreviations.
DNEL	Derived No-Effect Level.
EC50.	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EINECS.	European Inventory of Existing Commercial Chemical Substances.
EL50.	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms.
ELINCS.	European List of Notified Chemical Substances.
EmS.	Emergency Schedule.
ErC50.	= EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
ICAO-TI.	Technical instructions for the safe transport of dangerous goods by air.
IMDG.	International Maritime Dangerous Goods Code.
IMDG-Code.	International Maritime Dangerous Goods Code.
Index No.	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008.
IOELV.	Indicative occupational exposure limit value.
LC50.	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval.
LGK.	Lagerklasse (storage class according to TRGS 510, Germany).
LL50.	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality.
Log KOW.	n-Octanol/water.
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
RCP.	Reciprocal calculation procedure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
Repr.	Reproductive toxicity.
RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Skin Corr.	Corrosive to skin.
Skin Irrit.	Irritant to skin.
Skin Sens.	Skin sensitisation.
STEL.	Short-term exposure limit.
STOT SE.	Specific target organ toxicity - single exposure.
SVHC.	Substance of Very High Concern.
TRGS.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 900.	Arbeitsplatzgrenzwerte (TRGS 900).
TRGS 903.	Biologische Grenzwerte (TRGS 903).
TWA.	Time-weighted average.
VOC.	Volatile Organic Compounds.
VPvB.	Very Persistent and very Bioaccumulative.

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

H220.	Extremely flammable gas.
H222.	Extremely flammable aerosol.
H225.	Highly flammable liquid and vapour.
H226.	Flammable liquid and vapour.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H302.	Harmful if swallowed.
H304.	May be fatal if swallowed and enters airways.
H312.	Harmful in contact with skin.
H315.	Causes skin irritation.
H317.	May cause an allergic skin reaction.
H318.	Causes serious eye damage.
H319.	Causes serious eye irritation.
H332.	Harmful if inhaled.
H335.	May cause respiratory irritation.
H336.	May cause drowsiness or dizziness.
H351.	Suspected of causing cancer.
H360Fd.	May damage fertility. Suspected of damaging the unborn child.
H400.	Very toxic to aquatic life.
H410.	Very toxic to aquatic life with long lasting effects.
H411.	Toxic to aquatic life with long lasting effects.
H412.	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.