

Material Safety Data Sheet

according 1907/2006/EG

Revision : 14.12.2010

Printing Date : 02.03.2011

01. Identification of the substance/preparation and of the company/undertaking

Product name :	Now - Petroleum
Use of the substance / preparation :	SOLVENT
Manufacturer/Supplier :	Nordwest Handel AG
Street/P.O.Box :	Berliner Straße 26 - 36
Country code/Postal code/Town/City :	58135 Hagen
Telephone :	02331- 461- 0
Telefax :	02331- 461-9999
Contact :	06221/5301-0 (7.30 h - 16.00 h)
Emergency information :	Nordwest Handel AG

02. Hazards identification

Hazard designation

Directive 67/548/EEC or 1999/45/EC

Harmful: may cause lung damage if swallowed.

Classification : Xn ; R 65 · R 66

Regulation (EC) No 1272/2008 (GHS)

May be fatal if swallowed and enters airways.

Classification : Asp. Tox. 1 ; H304

03. Composition/information on ingredients

Chemical characterization

HYDROCARBONS

Hazardous components

KEROSINE)PETROLEUM), HYDRODESULFURIZED / KEROSINE - UNSPECIFIED ; EC-No. : 265-184-9; CAS-No. : 64742-81-0

Percentage : 75 - 100 %

Classification 67/548/EEC : Xn ; R65 R66

Classification 1907/2006 (GHS) : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304

For the wording of the listed risk phrases refer to section 16.

04. First-aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. For further information refer to "specifications about toxicology".

After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

After skin contact

Material Safety Data Sheet

according 1907/2006/EG

Revision : 14.12.2010

Printing Date : 02.03.2011

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Do not induce vomiting - call a physician. Drink plenty of water. Keep at rest.

05. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

07. Handling and storage

Information for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

Information about protection against explosions and fires

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Requirements to be met by storerooms and containers

Lagerung in Übereinstimmung mit der Betriebssicherheitsverordnung. Keep container tightly closed. Never use pressure to

Material Safety Data Sheet

according 1907/2006/EG

Revision : 14.12.2010

Printing Date : 02.03.2011

empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking.

Storage class (VCI) : 10

08. Exposure controls/personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

Components with critical values that require monitoring at the workplace (exposure limits)

None known.

Personal protective equipment

General protective and hygiene measures

Wash hands before breaks and after work.

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn. Depending on the boiling begin of the product: Respiration filter A (> 65 °C), or AX (< 65 °C), or air fed respirator.

Hand protection

Solvent-resistant protective gloves must be worn. Material: Neoprene, PVA. After washing hands replace lost skin fat by fat containing skin creams.

Eye protection

Use safety glasses.

Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

09. Physical and chemical properties

Image

Form : Liquid

Colour : Colourless

Relevant safety data

Boiling point / range :	(1013 hPa)	176,0 - 265,0	°C	
Flash point :	>	65,0	°C	DIN EN ISO 1523
Ignition temperature :		240,0	°C	
Lower explosion limit :		0,6	% b.v.	
Upper explosion limit :		7,0	% b.v.	
Density :	(20 °C)	0,810 - 0,830	g/cm ³	

Material Safety Data Sheet

according 1907/2006/EG

Revision : 14.12.2010

Printing Date : 02.03.2011

Density :	(20 °C)	0,810 - 0,830	g/cm ³
Solubility in water :	(20 °C)	Immiscible.	
pH value:	(20 °C / conc.)	not applicable	

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Experience on practice

Inhalation/eye contact: in high concentrations irritating to the mucous membranes, narcotic effect and influence on power of reaction and loss of coordination possible. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea. In case of contact with the product: danger of resorption through the skin, irritation of skin/mucous membranes. Eye contact: irritation.

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Additional ecological information

General ecological information

Do not empty into waters or drains.

13. Disposal considerations

In accordance with local official regulations. Remove in accordance with regulations.

Product

Waste key

140603

14. Transport information

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

15. Regulatory information

Labelling (67/548/EEC or 1999/45/EC)

Danger symbol and danger designation

Material Safety Data Sheet

according 1907/2006/EG

Revision : 14.12.2010

Printing Date : 02.03.2011



Xn ; Harmful

R-phrases

- 65 Harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.

S-phrases

- 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
35 This material and its container must be disposed of in a safe way.
24 Avoid contact with skin.

Regulation (EC) No 1272/2008 (GHS)

Classification

Hazard classes and hazard categories

Flam. Liq. 4 + Asp. Tox. 1

Labelling

Hazard pictograms



Signal word

Danger

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

- P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container according to the local regulations.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

National regulatory information

Water pollution classification

Class : 2

16. Other information

Further information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Relevant changes

15. Water pollution classification

Material Safety Data Sheet

according 1907/2006/EG

Revision : 14.12.2010

Printing Date : 02.03.2011

R-Phrases of components

- | | |
|----|---|
| 65 | Harmful: may cause lung damage if swallowed. |
| 66 | Repeated exposure may cause skin dryness or cracking. |

GHS Hazard statements of components

- | | |
|------|---|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
-

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
