MOTIP DUPLI

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.07.2013 Version number 12 Revision: 18.07.2013

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: prestolith extra fibreglass filler
- · Article number: 483060a, 483077a, 483435a, 483442a, 483800a, 601013a, 601112a, 601167a
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against --
- · Application of the substance / the preparation Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI GmbH

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49/6266/75-0

sicherheitsdatenblatt@dupli-color.de

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R10: Flammable

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Risk phrases:

10 Flammable.

- · Safety phrases:
- 2 Keep out of the reach of children.
- 23 Do not breathe vapour.

(Contd. on page 2)

Trade name: prestolith extra fibreglass filler

(Contd. of page 1)

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 100-42-5

EINECS: 202-851-5

Xn R20; Xi R36/38

R10

Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye

Irrit. 2, H319

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)

Trade name: prestolith extra fibreglass filler

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- \cdot 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL () Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Protection of hands:

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

· Eye protection: Safety glasses

GB

Printing date 18.07.2013 Version number 12 Revision: 18.07.2013

Trade name: prestolith extra fibreglass filler

(Contd. of page 3)

· 9.1 Information on basic physical and chemical properties · General Information					
Form:	Fluid				
Colour: · Odour:	According to product specification Characteristic				
· Oaour: · Odour threshold:	Not determined.				
· pH-value:	Not determined.				
· Change in condition					
Melting point/Melting range:	Undetermined.				
Boiling point/Boiling range:	145 °C				
· Flash point:	31 °C				
Flammability (solid, gaseous):	Not applicable.				
Decomposition temperature:	Not determined.				
· Self-igniting:	Product is not selfigniting.				
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.				
Explosion limits:					
Lower:	1.2 Vol %				
Upper:	8.9 Vol %				
· Vapour pressure at 20 °C:	6 hPa				
Density at 20 °C:	1.46 g/cm³				
· Relative density	Not determined.				
· Vapour density	Not determined.				
· Evaporation rate	Not determined.				
· Solubility in / Miscibility with					
water:	Not miscible or difficult to mix.				
Partition coefficient (n-octanol/wate	er): Not determined.				
· Viscosity:					
Dynamic:	Not determined.				

10 Stability and reactivity

· 9.2 Other information

· 10.1 Reactivity

Kinematic:

· Solvent content: VOC-(EU)

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

Not determined.

178.9 g/l

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB

Trade name: prestolith extra fibreglass filler

(Contd. of page 4)

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

	LD/LC50	values	relevant	for c	lassification:
--	---------	--------	----------	-------	----------------

100-42-5 styrene

 Oral
 LD50
 5000 mg/kg (rat)

 Inhalative
 LC50/4 h
 24 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information: Vapours have narcotic effect.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

•	European	waste	catalo	gue
---	----------	-------	--------	-----

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN3269

· 14.2 UN proper shipping name

· ADR 3269 POLYESTER RESIN KIT

· IMDG, IATA POLYESTER RESIN KIT

(Contd. on page 6)

Trade name: prestolith extra fibreglass filler

(Contd. of page 5) · 14.3 Transport hazard class(es) $\cdot ADR$ 3 (FT3) Flammable liquids. · Class · Label · IMDG, IATA 3 Flammable liquids. · Class · Label 3 · 14.4 Packing group · ADR, IMDG, IATA III · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Danger code (Kemler): · EMS Number: F-E,S-D· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 5L3 · Transport category

15 Regulatory information

· UN ''Model Regulation'':

· Tunnel restriction code

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

E

UN3269, POLYESTER RESIN KIT, 3, III

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

R10 Flammable.

R20 Harmful by inhalation.

R36/38 Irritating to eyes and skin.

(Contd. on page 7)

Printing date 18.07.2013 Version number 12 Revision: 18.07.2013

Trade name: prestolith extra fibreglass filler

(Contd. of page 6)

· Contact: Anwendungstechnik

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB